
AKZM 6540/IXL

12NC: 852565438110

GTIN (EAN) code: 8003437827556







30 max

30 max

Product group Pećnica Commercial code AKZM 6540/IXL Main colour of product Inox Construction type Ugradbeni Type of control Mechanical and electronic Type of control settings - Brončana Ne Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) 73 Integrated Cleaning system Ne Grids of the cavity 2 Trays 1	MAIN FEATURES	
Main colour of productInoxConstruction typeUgradbeniType of controlMechanical and electronicType of control settings-BrončanaNeWhich kind of hobs can be controlled?-Automatic programmesYesCurrent (A)13Voltage (V)220-240Frequency (Hz)50Length of Electrical Supply Cord (cm)90Plug typeNeDepth with open door 90 degree (mm)-Height of the product595Width of the product595Depth of the product564Minimum niche height0Niche depth0Net weight (kg)35.5Usable volume (of cavity)73Integrated Cleaning systemNeGrids of the cavity2	Product group	Pećnica
Construction typeUgradbeniType of controlMechanical and electronicType of control settings-BrončanaNeWhich kind of hobs can be controlled?-Automatic programmesYesCurrent (A)13Voltage (V)220-240Frequency (Hz)50Length of Electrical Supply Cord (cm)90Plug typeNeDepth with open door 90 degree (mm)-Height of the product595Width of the product595Depth of the product564Minimum niche height0Niche depth0Net weight (kg)35.5Usable volume (of cavity)73Integrated Cleaning systemNeGrids of the cavity2	Commercial code	AKZM 6540/IXL
Type of control Type of control settings Brončana Ne Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Depth with open door 90 degree (mm) Height of the product Sp5 Width of the product Minimum niche height Ne Mechanical and electronic Puss Yes Current Automatic programmes Yes Current Sp6 Ne Popth of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product Sp5 Width of the product Sp5 Depth of the product Minimum niche height O Minimum niche width Niche depth Ne Net weight (kg) Usable volume (of cavity) Ta Integrated Cleaning system Ne Grids of the cavity 2	Main colour of product	Inox
Type of control Type of control settings Brončana Ne Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Depth with open door 90 degree (mm) Height of the product Sp5 Width of the product Minimum niche height Ne Ne Ne Ne Ne Ne Ne Ne Ne N	Construction type	Ugradbeni
Brončana Ne Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) 73 Integrated Cleaning system Ne	Type of control	
Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Niche depth Ne Net weight (kg) 35.5 Usable volume (of cavity) Integrated Cleaning system Re Yes 13 10 13 Voltage (V) 20 220-240 Frequency (Hz) 50 Ne 90 Ne Ne 50 Ne 50 10 10 10 10 10 10 10 10 10	Type of control settings	-
Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product S95 Width of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Niche depth Ne Net weight (kg) 35.5 Usable volume (of cavity) Integrated Cleaning system Re Grids of the cavity 2	Brončana	Ne
Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) 73 Integrated Cleaning system Ne Grids of the cavity 2	Which kind of hobs can be controlled?	-
Voltage (V) 220-240 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) 73 Integrated Cleaning system Ne Grids of the cavity 2	Automatic programmes	Yes
Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) 73 Integrated Cleaning system Ne Grids of the cavity 2	Current (A)	13
Length of Electrical Supply Cord (cm) Plug type Depth with open door 90 degree (mm) Height of the product S95 Width of the product Depth of the product S95 Depth of the product Minimum niche height Niche depth Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Grids of the cavity 90 Net 90 90 Net 90 90 90 Net 90 90 Net 90 90 Net 90 90 90 90 90 90 90 90 90 9	Voltage (V)	220-240
Plug type Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) Integrated Cleaning system Re Grids of the cavity 2	Frequency (Hz)	50
Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) Integrated Cleaning system Grids of the cavity 2	Length of Electrical Supply Cord (cm)	90
Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) 73 Integrated Cleaning system Ne Grids of the cavity 2	Plug type	Ne
Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) 73 Integrated Cleaning system Ne Grids of the cavity 2	Depth with open door 90 degree (mm)	-
Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) 73 Integrated Cleaning system Ne Grids of the cavity 2	Height of the product	595
Minimum niche height0Minimum niche width0Niche depth0Net weight (kg)35.5Usable volume (of cavity)73Integrated Cleaning systemNeGrids of the cavity2	Width of the product	595
Minimum niche width 0 Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) 73 Integrated Cleaning system Ne Grids of the cavity 2	Depth of the product	564
Niche depth 0 Net weight (kg) 35.5 Usable volume (of cavity) 73 Integrated Cleaning system Ne Grids of the cavity 2	Minimum niche height	0
Net weight (kg) 35.5 Usable volume (of cavity) 73 Integrated Cleaning system Ne Grids of the cavity 2	Minimum niche width	0
Usable volume (of cavity) 73 Integrated Cleaning system Ne Grids of the cavity 2	Niche depth	0
Integrated Cleaning system Ne Grids of the cavity 2	Net weight (kg)	35.5
Grids of the cavity 2	Usable volume (of cavity)	73
,	Integrated Cleaning system	Ne
Trays 1	Grids of the cavity	2
	Trays	1

TECHNICAL FEATURES	
Timer	-
Time control	Electronic
Time-setting options	Start and Stop
Safety device	-
Interior light	Yes
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Rear
Oven guides of the cavity	Grids
Probe of the cavity	Ne

ENERGY LABEL	
Energy input	Electric
Type of energy of the cavity	Electrică
Energy efficiency class - NEW (2010/30/EU)	A+
Energy consumption per cycle conventional - NEW (2010/30/EU)	0.91
Energy consumption per cycle forced air convection - NEW (2010/30/EU)	0.7