Quick Reference Guide



Cooking gestures are invisible ingredients.
They turn inspiration into emotions and emotions into a masterpiece.
It's all about artisanality, that's why we take it so seriously.

Thanks for choosing

KitchenAid FOR THE WAY IT'S MADE.

Index

EN......page 3









EN

CY

Cooking gestures are invisible ingredients. They turn inspiration into emotions and emotions into a masterpiece. It's all about artisanality, that's why we take it so seriously.

Thanks for choosing

KitchenAid FOR THE WAY IT'S MADE.



•

Safety Instructions

Important To Be Read And Observed

Download the complete instruction manual on **http://docs.kitchenaid.eu** or call the phone number shown on the warranty booklet.

Before using the appliance, read these safety instructions. Keep them nearby for future reference.

These instructions and the appliance itself provide important safety warnings, to be observed at all times. The manufacturer declines any liability for failure to observe these safety instructions, for inappropriate use of the appliance or incorrect setting of controls.

⚠ These instructions are valid if the country symbol appears on the appliance. If the symbol doesn't appear on the appliance, it is necessary to refer to the technical instructions which will provide the necessary instructions concerning modification of the appliance to the conditions of use of the country.

⚠ CAUTION: The use of the gas cooking appliance results in the production of heat, moisture and products of combustion in the room in which it is installed. Ensure that the kitchen is well ventilated especially when the appliance is in use: keep natural ventilation holes open or install a mechanical ventilation device (mechanical extractor hood). Prolonged intensive use of the appliance may call for additional ventilation, for example opening of the window, or more effective ventilation, increasing the level of mechanical ventilation where present.

⚠ WARNING: The appliance and its accessible parts become hot during use. Care shoul be taken to avoid touching heating elements. Children less than 8 years of age must be kept away unless continuously supervised.

⚠ WARNING: If the hob surface is cracked, don't use the appliance – risk of electrical shock.

⚠ WARNING : Danger of fire : Do not store items on the cooking surfaces.

⚠ CAUTION: The cooking process has to be supervised. A short cooking process has to be supervised continuously.

⚠ WARNING: Unattended cooking on a hob with fat or oil can be dangerous – risk of fire. NEVER try to extinguish a fire with water, but switch off the appliance and then cover flame e.g. with a lid or a fire blanket.

△ Do not use the hob as a work surface or support. Keep clothes or other flammable materials away from the appliance, unitl all the components have cooled down completely – risk of fire.

 Δ If the information in this manual is not followed exactly, a fire or explosion, may result causing property damage or injury. ⚠ Very young children (0-3 years) should be kept away from the appliance. Young children (3-8 years) should be kept away from the appliance unless continuously supervised. Children from 8 years old and above and persons with reduced physical. sensory or mental capabilities or lack of experience and knowledge can use this appliance only if they are supervised or have been given instructions on safe use and understand the hazards involved. Children must not play with the appliance. Cleaning and user maintenance must not be carried out by children without supervision.

⚠ CAUTION: In case of hotplate glass breakage:-shut immediately off all burners and any electrical heating element and isolate the appliance from the power supply; - do not touch the appliance surface; -do not use the appliance. The glass lid can break in if it is heated up. Turn off all the burners and the electric plates before closing the lid. Do not shout down lid when burner alight.









⚠ CAUTION: the appliance is not intended to be operated by means of an external switching device, such as a timer, or separate remote controlled system.

⚠ This appliance is intended to be used in household and similar applications such as: staff kitchen areas in shops, offices and other working environments; farm houses; by clients in hotels, motels, bed & breakfast and other residential environments.

⚠ No other use is permitted (e.g. heating rooms).

⚠ This appliance is not for professional use. Do not use the appliance outdoors.

△ Use pots and pans with bottoms the same width as that of the burners or slightly larger (see specific table). Make sure pots on the grates do not protrude beyond the edge of the hob.

⚠ Improper use of the grids can result in damage to the hob: do not position the grids upside down or slide them across the hob.

Do not let the burner flame extend beyond the edge of the pan.

Do not use: Cast iron griddles, ollar stones, terracotta pots and pans. Heat diffusers such as metal mesh, or any other types. Two burners simultaneously for one receptacle (e.g. Fish kettle).

Should particular local conditions of the delivered gas make the ignition of burner difficult, it is advisable to repeat the operation with the knob turned to small flame setting. In case of installation of a hood above the cooktop, please refer to the hood instructions for the correct distance.

The protective rubber feet on the grids represent a chocking hazard for young children. After removing the grids, please ensure that all the feet are correctly fitted.

INSTALLATION

⚠ The appliance must be handled and installed by two or more persons - risk of injury. Use protective gloves to unpack and install - risk of cuts.

⚠ Installation, including water supply (if any) and electrical connections, and repairs must be carried out by a qualified technician. Do not repair or replace any part of the appliance unless specifically stated in the user manual. Keep children away from the installation site. After unpacking the appliance, make sure that it has not been damaged during transport. In the event of

problems, contact the dealer or your nearest After-sales Service. Once installed, packaging waste (plastic, Styrofoam parts etc.) must be stored out of reach of children - risk of suffocation. The appliance must be disconnected from the power supply before any installation operation - risk of electrical shock. During installation, make sure the appliance does not damage the power cable - risk of fire or electrical shock. Only activate the appliance when the installation has been completed.

⚠ The electrical and gas connections must comply with local regulation.

⚠ WARNING: Modification of the appliance and its method of installation are essential in order to use the appliance safely and correctly in all the additional countries.

△ Use pressure regulators suitable for the gas pressure indicated in the instruction.

The room must be equipped with an air extraction system that expels any combustion fumes.

⚠ The room must also allow proper air circulation, as air is needed for combustion to occur normally. The flow of air must not be less than 2 m3/h per kW of installed power.

△ The air circulation system may take air directly from the outside by means of a pipe with an inner cross section of at least 100 cm2; the opening must not be vulnerable to any type of blockages.

⚠ The system can also provide the air needed for combustion indirectly, i.e. from adjacent rooms fitted with air circulation tubes as described above. However, these rooms must not be communal rooms, bedrooms or rooms that may present a fire hazard.

⚠ Liquid petroleum gas sinks to the floor as it is heavier than air. Therefore, rooms containing LPG cylinders must also be equipped with vents to allow gas to escape in the event of a leak. As a result LPG cylinders, whether partially or completely full, must not be installed or stored in rooms or storage areas that are below ground level (cellars, etc.). It is



advisable to keep only the cylinder being used in the room, positioned so that it is not subject to heat produced by external sources (ovens, fireplaces, stoves, etc.) which could raise the temperature of the cylinder above 50°C.

△ Carry out all cabinet cutting works before fitting the appliance in the furniture and remove all wood chips and sawdust.

⚠ If the appliance is Not installed above an oven, a separator panel (not included) must be installed in the compartment under the appliance.

Should you experience difficulty in turning the burners knobs, please contact After Sales Service for replacement of the burner tap if found to be faulty.

The openings used for the ventilation and dispersion of heat must never be covered.

GAS CONNECTION

⚠ WARNING: Prior to installation, ensure that the local distribution conditions (nature of gas and gas pressure) and the adjustment of the appliance are compatible.

⚠ Check that the pressure of the gas supply is consistent with the values indicated in Table 1 ("Burner and nozzle specifications").

⚠ WARNING: The adjustment conditions for this appliance are stated on the label (or data plate).

⚠ WARNING: This appliance is not connected to a combustion products evacuation device. It shall be installed and connected in accordance with current installation regulations. Particular attention shall be given to the relevant requirements regarding ventilation.

⚠ If the appliances is connected to liquid gas, the regulation screw must be fastened as tightly as possible.

⚠ IMPORTANT: When gas cylinder is adopted, the gas cylinder or gas container must be properly settled (vertical orientation).

⚠ WARNING: This operation must be performed by a qualified technician ⚠ Use only flexible or rigid metal hose for gas connection.

⚠ Connection with a rigid pipe (copper or steel) Connection to the gas system must be carried out in such a way as not to place any strain of any kind on the appliance. There is an adjustable L-shaped pipe fitting on the appliance supply ramp and this is fitted with a seal in order to prevent leaks. The seal must always be replaced after rotating the pipe fitting (the seal is provided with the appliance). The gas supply pipe fitting is a threaded 1/2 gas cylindrical male attachment.

△ Connecting a flexible joint less stainless steel pipe to a threaded attachment The gas supply pipe fitting is a threaded 1/2 gas cylindrical male attachment. These pipes must be installed so that they are never longer than 2000 mm when fully extended. Once connection has been carried out, make sure that the flexible metal pipe does not touch any moving parts and is not compressed. Only use pipes and seals that comply with current National regulations. △ IMPORTANT: If a stainless steel hose is

used, it must be installed so as not touch any mobile part of the furniture (e.g. drawer). It must pass through an area where there are no obstructions and where it is possible to inspect it on all its length.

⚠ The appliance should be connected to the main gas supply or to gas cylinder in compliance with the current National regulations. Before carry out the connection, make sure that the appliance is compatible with the gas supply you wish to use. If this is not the case, follow the instructions indicated in the paragraph "Adapting to different types of gas".

⚠ After connection to the gas supply, check for leaks with soapy water. Light up the burners and turn the knobs from max position 1* to minimum position 2* to check flame stability.





ADAPTING TO DIFFERENT TYPES OF GAS

⚠ In order to adapt the appliance to a type of gas other than the type for which it was manufactured (indicated on the rating label), follow the dedicated steps provided after installation drawings.

ELECTRICAL WARNINGS

△ IMPORTANT: The data relevant to the voltage an power absorptions are indicated on the rating plate.

⚠ The power cable must be long enough to connect the appliance, once fitted in its housing, to the main power supply. Do not pull the power supply cable.

⚠ It must be possible to disconnect the appliance from the power supply by unplugging it if plug is accessible, or by a multi-pole switch installed upstream of the socket in accordance with the wiring rules and the appliance must be earthed in conformity with national electrical safety standards.

⚠ Do not use extension leads, multiple sockets or adapters. The electrical components must not be accessible to the user after installation. Do not use the appliance when you are wet or barefoot. Do not operate this appliance if it has a damaged power cable or plug, if it is not working properly, or if it has been damaged or dropped.

⚠ If the supply cord is damaged, it must be replaced with an identical one by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard - risk of electrical shock.

CLEANING AND MAINTENANCE

⚠ WARNING: Ensure that the appliance is switched off and disconnected from the power supply before performing any maintenance operation; never use steam cleaning equipment - risk of electric shock. ⚠ Do not use abrasive or corrosive products, chlorine-based cleaners or pan scourers.

DISPOSAL OF PACKAGING MATERIALS

The packaging material is 100% recyclable and is marked with the recycle symbol . The various parts of the packaging must therefore be

The various parts of the packaging must therefore be disposed of responsibly and in full compliance with local authority regulations governing waste disposal.

DISPOSAL OF HOUSEHOLD APPLIANCES

This appliance is manufactured with recyclable or reusable materials. Dispose of it in accordance with local waste disposal regulations. For further information on the treatment, recovery and recycling of household electrical appliances, contact your local authority, the collection service for household waste or the store where you purchased the appliance. This appliance is marked in compliance with European Directive 2012/19/EU, Waste Electrical and Electronic Equipment (WEEE). By ensuring this product is disposed of correctly, you will help prevent negative consequences for the environment and human health.

The symbol on the product or on the accompanying documentation indicates that it should not be treated as domestic waste but must be taken to an appropriate collection center for the recycling of electrical and electronic equipment.

ENERGY SAVING TIPS

Use pots and pans with bottom width equal to that of the cooking zone.

Only use flat-bottomed pots and pans.

When possible, keep pot lids on during cooking. Use a pressure cooker to save even more energy and

Place the pot in the middle of the cooking zone marked on the hob.

DECLARATION OF CONFORMITY

This appliance meets the Ecodesign requirements set out in European Regulation n. 66/2014, in conformity to the European standard EN 30-2-1.





CATEGORY II2H3+

Type of gas used	Type of burner	Injector marking	Rated thermal flow rate	Rated consumption	Reduced heat capacity	G	as press mbar	ure
			kW		kW	min.	rat.	max.
	Rapid	125 A	3,00	286 l/h	0,60			
NATURAL GAS	Semi-rapid	97 A	1,75	167 l/h	0,35			
(Methane) G20	Auxiliary	78 C	1,00	95 l/h	0,30	17	20	25
(Methane) G20	DCC - Outer + Inner	165 HI +70 HI	5,80	552 l/h	2,20			
	DCC - Inner	70 HI	0,90	86 l/h	0,30			
	Rapid	85 A	3,00	218 g/h	0,60			
LIQUEFIED	Semi-rapid	66 A	1,75	127 g/h	0,35			
PETROLEUM GAS	Auxiliary	50 A	1,00	73 g/h	0,30	20	28-30	35
(Butane) G30	DCC - Outer + Inner	102 + 44	5,25	382 g/h	2,20			
	DCC - Inner	44	0,90	65 g/h	0,30			
	Rapid	85 A	3,00	214 g/h	0,60			
LIQUEFIED	Semi-rapid	66 A	1,75	125 g/h	0,35			
PETROLEUM GAS	Auxiliary	50 A	1,00	71 g/h	0,30	25	37	45
(Propane) G31	DCC - Outer + Inner	102 + 44	5,25	375 g/h	2,20			
	DCC - Inner	44	0,90	64 g/h	0,30			

Type of gas used Model configuration 5 BURNERS		Rated thermal flowrate (kW)	Total rated consumption	Air required (m3) for burning 1m3 of gas	
G20 20 mbar	1R - 2 SR - 1 AUX - 1DCC	13,30	1267 l/h	9,52	
G30 28-30 mbar	1R - 2 SR - 1 AUX - 1DCC	12,75	927 g/h	30,94	
G31 37 mbar	1R - 2 SR - 1 AUX - 1DCC	12,75	910 g/h	23,80	

ELECTRIC SUPPLY: 220-240 V ~ 50-60 Hz - 0,6W









CATEGORY II2H3B/P

Type of gas used	Type of burner	Injector marking	Rated thermal flow rate	Rated consumption	Reduced heat capacity	Gas pressure mbar		
			kW		kW	min.	rat.	max.
	Rapid	125 A	3,00	286 l/h	0,60			
NATURAL GAS	Semi-rapid	97 A	1,75	167 l/h	0,35			
(Methane) G20	Auxiliary	78 C	1,00	95 l/h	0,30	17	20	25
(Methane) G20	DCC - Outer + Inner	165 HI +70 HI	5,80	552 l/h	2,20			
	DCC - Inner	70 HI	0,90	86 l/h	0,30			
	Rapid	85 A	3,00	218 g/h	0,60			
LIQUEFIED	Semi-rapid	66 A	1,75	127 g/h	0,35			
PETROLEUM GAS	Auxiliary	50 A	1,00	73 g/h	0,30	20	30	35
(Butane) G30	DCC - Outer + Inner	102 + 44	5,25	382 g/h	2,20			
	DCC - Inner	44	0,90	65 g/h	0,30			
	Rapid	85 A	3,00	214 g/h	0,60			
LIQUEFIED	Semi-rapid	66 A	1,75	125 g/h	0,35			
PETROLEUM GAS	Auxiliary	50 A	1,00	71 g/h	0,30	20	30	35
(Propane) G31	DCC - Outer + Inner	102 + 44	5,25	375 g/h	2,20			
	DCC - Inner	44	0,90	64 g/h	0,30			

Type of gas used	Type of gas used Model configuration 5 BURNERS		Total rated consumption	Air required (m3) for burning 1m3 of gas	
G20 20 mbar	1R - 2 SR - 1 AUX - 1DCC	13,30	1267 l/h	9,52	
G30 30 mbar	1R - 2 SR - 1 AUX - 1DCC	12,75	927 g/h	30,94	
G31 30 mbar	1R - 2 SR - 1 AUX - 1DCC	12,75	910 g/h	23,80	

ELECTRIC SUPPLY: 220-240 V ~ 50-60 Hz - 0,6W











TECHNICAL INFORMATION FOR THE INSTALLER

- Use protective gloves for handling, preparing and installing the product.
- This product can be embedded in a worktop 20 ÷ 60 mm thick.
- If there is no oven beneath the hob, insert a separator panel that has a surface at least equal to the opening in the work surface. This panel must be positioned at a maximum distance of 150 mm below the upper surface of the work surface but, in no case less than 20 mm from the bottom of the hob. In the case that you intend to install an oven beneath the hob, make sure that it is equipped with a cooling system.


DIMENSIONS AND DISTANCES TO BE MAINTAINED





NOTE: Kitchen cabinets adjacent to the appliance and taller than the top of the hob must be at least 200 mm from the edge of the hob. Hoods must be installed according to their relative installation instruction manuals and at a minimum distance of 650 mm from the hob (see figure). Place the wall cabinets adjacent to the hood at a minimum height of 420 mm from the hob (see figure). If the hob is installed beneath a wall cabinet, the latter must be situated at a minimum of 700 mm above the hob.

ASSEMBLY











NOTE: the power supply cable must be long enough to permit its upward extraction.

To secure the hob, use the brackets (A) provided with it. Fit the brackets into the relevant bores shown by the arrow and fasten them by means of their screws in accordance with the thickness of the worktop (see the following figures).








GAS CONNECTION

- Connect elbow (A)* or (B)* supplied with to the hob inlet main pipe and interpose the washer (C) supplied, in compliance with EN 549.
 - * Use elbow (A) for United Kingdom and elbow (B) for all other destinations.
- · After connection to the gas supply, check for leaks with soapy water. Light up the burners and turn the knobs from max position (a) to minimum position (a) to check flame stability.

IMPORTANT: Before connection remove a transport plug from the connecting hole of the cooker gas pipeline.







Product Description



1.	Removable panstand grids		<u>Symbols</u>	
2.	Rapid burner		Shaded circle	
3.	Semi-rapid burner		Large flame	Ġ
4.	2 Ring burner		Small flame	Ġ
5.	Semi-rapid burner			
6.	Auxiliary burner			
7.	Rapid burner control knob	: %		
8.	Semi-rapid burner control knob	3 08		
9.	2 Ring burner control knob	⊱ 8		
10	Semi-rapid burner control knob	00		

11. Auxiliary burner control knob

Daily use

HOW TO USE THE HOB

⚠ Do not let the burner flame extend beyond the edge •

IMPORTANT: when the hob is in use, the entire hob IMPORTANT: improper use of the grids can result in area may become hot.

- To ignite one of the burners, turn the relative knob anticlockwise to the maximum flame setting.
- Press the knob against the control panel to ignite the
- After the burner has ignited, keep the knob pressed for about 5-10 seconds to allow proper device operation.
- This burner safety device shuts off the gas supply to the burner if the flame goes out accidentally (because of sudden draught, an interruption in the gas delivery, boiling over of liquids, etc.).
- · The knob must not be pressed for more than 15 sec. If, after that time has elapsed, the burner does not remain lit, wait at least one minute before trying to light it again.
- NOTE: should particular local conditions of the delivered gas make the ignition of burner difficult, it is advisable to repeat the operation with the knob turned to small flame setting.

The burner might go out when the knob is released. This means that the safety device has not warmed up enough. In this case, repeat the operations described

PRACTICAL ADVICE FOR USING THE BURNERS

This hob has burners of different diameters. For better burner performance, please stick to the following rules:

- · use pots and pans with bottoms the same width as that of the burners or slightly larger (see table on the
- only use flat-bottomed pots and pans;
- use the correct amount of water for cooking foods and keep the pot covered;
- · make sure pots on the grates do not protrude beyond the edge of the hob;
- In the case of pans with convex bottoms (WOK), use the support grille (not provided), which should be positioned only on the multi-ring burner.

- · Avoid accidentally knocking the hob with pans, racks or other kitchen utensil.
- Do not leave empty steak grills over the lit burner for longer than 5 minutes.

damage to the hob: do not position the grids upside down or slide them across the hob.

BURNER	Ø COOKWARE DIAMETER
2 Ring	From 24 to 26 cm
Rapid	From 24 to 26 cm
Semi-rapid	From 16 to 22 cm
Auxiliary	From 8 to 14 cm

Do not use:

- · cast iron griddles, collar stones, terracotta pots and
- heat diffusers such as metal mesh, or any other types;
- two burners simultaneously for one receptacle (e.g. fish

Liquids spilled on hot hob area can cause glass damage.

ADAPTING TO DIFFERENT TYPES OF GAS

This operation must be performed by a qualified technician.


If the appliance is intended to operate with a different gas from the gas type stated on the rating plate and information label on the top of the hob, change the injectors.

Remove the information label and keep it with the instructions booklet.

Use pressure regulators suitable for the gas pressure indicated in the Instruction:

- the gas injector must be changed by After Sales Service or a qualified technician;
- injector not supplied with the appliance must be ordered from After Sales Service;
- adjust the minimum setting of the taps.





IMPORTANT: should you experience difficulty in • tighten screw to reduce the flame height (-); turning the burners knobs, please contact the After • found to be faulty.

cylinder or gas container must be properly settled (vertical orientation).

REPLACING THE INJECTORS (see the injector table in the Safety instructions)

- Remove grids (A).
- Extract burners (B).
- Using a socket spanner of the appropriate size unscrew the injector (**C**), unscrew the injector to be replaced.
- Replace it with the injector suitable for the new type of gas.
- Re-assemble the injector in (**D**).
- If you have a multiple crown burner use side spanner to replace the injector (E).



Before installing the hob, remember to affix the gas calibration plate supplied with the injectors in such a way that it covers the existing information relating to gas calibration.

To ensure that the minimum setting is correctly adjusted, remove the knob and proceed as follows:

- loosen screw to increase the flame height (+).

Sales Service for the replacement of the burner tap if The adjustment must be performed with the tap in minimum gas setting position (small flame):

- **IMPORTANT:** when gas cylinder is adopted, the gas The primary air of the burners does not need to be adjusted:
 - At this stage, light up the burners and turn the knobs from max position (a) to minimum position (b) to check flame stability.

Upon completion of adjustment, reseal using sealing wax or an equivalent material.





POSITIONING THE PAN SUPPORTS AND WOK SUPPORT

Position the pan supports by inserting the rubber feets located on the bottom of supports into the slots found on the surface of the metal top.









Maintenance and cleaning

⚠ Disconnect the appliance from the power supply.

CLEANING THE HOB SURFACE

- · All the enamelled and glass parts should be cleaned with warm water and neutral solution.
- Stainless steel surfaces may be stained by calcareous water or aggressive detergents if left in contact for too long. Any food spills (water, sauce, coffee, etc.) should • be wiped away before they dry.
- Clean with warm water and neutral detergent, and then dry with a soft cloth or chamois. Remove baked. • on dirt with specific cleaners for stainless steel surfaces.
- NOTE: clean stainless steel only with soft cloth or . · Do not use abrasive or corrosive products, chlorine-
- based cleaners or pan scourers.
- · Do not use steam cleaning appliances.
- Do not use flammable products.
- Do not leave acid or alkaline substances, such as vinegar, mustard, salt, sugar or lemon juice on the hob.

- Clean glass and enameled parts only with soft cloth or
- Grids, burner caps and burners can be removed to be cleaned.
- Clean them by hand with warm water and non-abrasive detergent, removing any food residues and checking that none of the burner openings is clogged.
- Rinse and dry.
- Refit burners and burner caps correctly in the respective housings.
- When replacing the grids, make sure that the panstand area is aligned with the burner.
- Models equipped with electrical ignition plugs and safety device require thorough cleaning of the plug end in order to ensure correct operation. Check these items frequently, and if necessary, clean them with a damp cloth. Any baked-on food should be removed with a toothpick or needle.

NOTE: to avoid damaging the electric ignition device, do not use it when the burners are not in their housing.

Troubleshooting

CLEANING THE HOB PARTS



1. The burner fails to ignite or the flame is not even Check that:

- the gas or electrical supplies are not shut off and especially that the gas supply tap is open;
- the gas cylinder (liquid gas) is not empty;
- · the burner openings are not clogged;
- the plug end is not dirty;
- all the burner parts have been positioned 3. The containers are not stable correctly;
- · there are no droughts near the hob.

- · when lighting the burner, the knob has been pressed for enough time to activate the protection device;
- the burner openings are not clogged near the thermocouple;
- the end of the safety device is not dirty;
- the minimum gas setting is correct (see relevant paragraph).

Check that:

- the bottom of the container is perfectly flat;
- · the container is centered on the burner;
- the grids have not been exchanged or positioned incorrectly.

If after the above checks the fault still occurs, get in touch with the nearest After Sales Service.





After-Sales Service

In order to receive a more complete assistance, please register your product on www.kitchenaid.eu/register.

BEFORE CALLING THE AFTER-SALES SERVICE:

- 1. See if you can solve the problem by yourself with the help of the suggestions given in the TROUBLESHOOTING.
- 2. Switch the appliance off and back on again to see if the fault persists.

IF AFTER THE ABOVE CHECKS THE FAULT STILL OCCURS, GET IN TOUCH WITH THE NEAREST AFTER-SALES SERVICE.

To receive assistance, call the number shown on the warranty booklet or follow the instructions on the website • www.kitchenaid.eu.

When contacting our Client After sales service, always If any repairs are required, please contact an authorized

- · a brief description of the fault;
- the type and exact model of the appliance;



the service number (number after the word Service on the rating plate). The service number is also indicated on the guarantee booklet;

SERVICE 0000 000 00000

- your full address;
- your telephone number.

after-sales service (to guarantee that original spare parts will be used and repairs carried out correctly).





Please refer to our website www.kitchenaid.eu for complete instructions for use. In addition, you will find a lot more useful information about your products, such as inspiring recipes created and tested by our brand ambassadors or the nearest KitchenAid cookery school.









via Carlo Pisacane n.1, 20016 Pero (MI),ITALY





•

Printed in Italy



KitchenAid FOR THE WAY IT'S MADE.

(