

12NC/Fx: 859991541970

GTIN (EAN) code: 8003437230929

DIMENSION	MEAS	URE
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	450	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	452	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	ո 0	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	545	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	0	mm
Space in front, which is required to install bottom trim	7	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm ²
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm ²
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear	
Minimum space for inbound ventilation (tall cabinet)	45	mm
Minimum area for inbound ventilation cavity (tall cabinet)	252	cm ²
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Rear	
Minimum space for outbound ventilation (tall cabinet)	45	mm
Minimum area for outbound ventilation cavity (tall cabinet)	252	cm ²
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	-	
Minimum space for inbound ventilation (base cabinet)	0	mm
Minimum area for inbound ventilation cavity (base cabinet)	0	cm ²
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	-	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	0	cm ²

Height of the front 455 mm Width of the front 595 mm Width of the front 595 mm Depth of the front 222 mm Maximum depth all protruding elements, e.g. handles, controls 0 mm Caterial clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 80 mm Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height form bearing area of appliances and lower handle 60 mm Frontal handle thickness 60 mm Mix Height of the product body 60 mm 60	DIMENSION		EASURE	
Width of the front 22 mm Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 mm Frontal handle thickness 0 mm MIN Height of the product body 442 mm MAX Height of the product body 442 mm Width of the product body 560 mm Lul depth of product excluding protruding interface elements 101 mm	APPLIANCE			
Depth of the front Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 mm Frontal handle thickness 0 mm Frontal handle width 0 mm MIN Height of the product body 442 mm Width of the product body 442 mm Width of the product body 450 mm Full depth of product excluding protruding interface elements 10 mm	Height of the front	455	mm	
Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 mm Frontal handle width 0 mm Frontal handle brickness 0 mm MIN Height of the product body 442 mm Midth of the product body 442 mm Width of the product body 442 mm Moth the product body 450 mm Full depth of product excluding protruding interface elements - mm - mm - mm - mm - mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Appliance Side swing door Lateral projection of front incl. controls when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace	Width of the front	595	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance 10 mm Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness Frontal handle width 0 mm MIN Height of the product body MAX Height of the product body MAX Height of the product body Mobility of the product body Sebo mm MIN Height of product excluding protruding interface elements	Depth of the front	22	mm	
neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 mm Frontal handle width 0 mm MIN Height of the product body MAX Height of the product body MAX Height of the product body Set on modulate the product body Full depth of product excluding protruding interface elements	Maximum depth all protruding elements, e.g. handles, controls	0	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 mm Frontal handle width MIN Height of the product body MAX Height of the product body Width of the product body Mobient of the product bo	, , ,	0	mm	
appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 mm Frontal handle width 0 mm MIN Height of the product body 442 mm MAX Height of the product body 560 mm Depth of the product body 560 mm Depth of the product body 560 mm	Projection of front in relation to housing of appliance	10	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 mm Frontal handle width 0 mm MIN Height of the product body 442 mm Width of the product body 560 mm Depth of the product body 450 mm - mm - mm - mm - mm - mm Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm Appliance other	· · · · · · · · · · · · · · · · · · ·	2	mm	
dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 mm Frontal handle width 0 mm MIN Height of the product body 442 mm MAX Height of the product body 560 mm Depth of the product body 560 mm Full depth of product excluding protruding interface elements 501 mm - mm	When product panel is missing, set to 0	80	mm	
Frontal handle thickness 0 mm Frontal handle width 0 mm MIN Height of the product body 442 mm MAX Height of the product body 442 mm Width of the product body 560 mm Depth of the product body 450 mm Full depth of product excluding protruding interface elements 501 mm mm mm mm mm mm mm mm - mm mm - m		207	mm	
Frontal handle width 442 mm MIN Height of the product body 442 mm MAX Height of the product body 442 mm Width of the product body 560 mm Depth of the product body 450 mm Full depth of product excluding protruding interface elements 501 mm - mm - mm mm - mm	Height from bearing area of appliances and lower handle	0	mm	
MIN Height of the product body MAX Height of the product body Width of the product body Depth of the product body Full depth of product excluding protruding interface elements	Frontal handle thickness	0	mm	
MAX Height of the product body Width of the product body Depth of the product body Full depth of product excluding protruding interface elements To mm To projection of the opened flap in relation to bearing area To mm T	Frontal handle width	0	mm	
Width of the product body Depth of the product body Full depth of product excluding protruding interface elements - mm - mm - mm - mm - mm mm - mm mm - mm mm - mm	MIN Height of the product body	442	mm	
Depth of the product body Full depth of product excluding protruding interface elements 501 mm	MAX Height of the product body	442	mm	
Full depth of product excluding protruding interface elements - mm - m	Width of the product body	560	mm	
- mm	Depth of the product body	450	mm	
- mm	Full depth of product excluding protruding interface elements	501	mm	
- mm	-	-	mm	
- mm	-	-	mm	
- mm	-	-	mm	
- mm - Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace - mm - mm No - mm No - mm No - mm No - mm Maximum angle when flap door is opened totally - mm - mm Appliance other - mm No - mm No - mm Maximum angle when door is opened totally - mm Maximum angle when door is opened totally - mm - mm - no - mm No - mm - m	-	-	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace - mm Appliance is "No" No No Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	-	-	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace No mm	-	-	mm	
Appliance Flap door Projection of the opened flap in relation to bearing area 3 mm Maximum angle when flap door is opened totally 90 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 85 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	-	-	mm	
Projection of the opened flap in relation to bearing area 3 mm Maximum angle when flap door is opened totally 90 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 85 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Appliance can be used as base for other appliances from the same manufacturer. Default is "No	" No		
Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Appliance Flap door			
Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Projection of the opened flap in relation to bearing area	3	mm	
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace O mm	Maximum angle when flap door is opened totally	90	mm	
mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Appliance Side swing door			
Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm		s 0	mm	
Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Maximum angle when door is opened totally	85	mm	
·	Appliance other			
Height from niche to bottom end of freespace for the retrace 0 mm	Depth from front end of the niche to the front end of the freespace of the retrace	0	mm	
	Height from niche to bottom end of freespace for the retrace	0	mm	