



DIMENSION	MEASURE	
OVERALL CABINET		
01. Height MIN of the base cabinet Niche, including all required space for installation or ventilation (HMIN_B)	0	mm
02. Height MAX of the base cabinet Niche, including all required space for installation or ventilation (HMAN_B)	0	mm
03. Width MIN of the base cabinet Niche, including all required space for installation or ventilation (WMIN_B)	0	mm
04.Width MAX of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B)	0	mm
05. Depth of the base cabinet Niche, including all required space for installation or ventilation (DN_B)	0	mm
06. Indicates whether a ventilation opening is needed or not. Default is "N"	No	
07. appliance can be used as base for other appliances from the same manufacturer. Default is "N"	No	
Built In - Floor Standing		
08. Height MIN Decorative Front (HMIF)	0	mm
09. Height MAX Decorative Front (HMAF)	0	mm
10. Width MIN Decorative Front (WMIF)	0	mm
11. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)	0	kg
12. Weight MIN of the decorative front panel of the Kitchen manufacturer (WEMIF)	0	kg
13. Thickness MAX of decorative front panel of the kitchen manufacturers (TMAF)	0	mm
14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG)	0	mm
APPLIANCE		
Overall Appliance		
01. Height MIN Product (HMIP)	850	mm
02. Height MAX product (HMAP)	850	mm
03. Width product (WP)	600	mm
04. Depth product without front (DP)	598	mm
05. Depth product (D)	0	mm
06. Depth MIN of plinth return front (DMIPRF)	0	mm
07. Depth MAX of plinth return front (DMAPRF)	0	mm
08. Height MIN Plinth return. Dimension is taken by minimum appliance height (HMIMIPR)	0	mm
09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMAPR)	0	mm
Built In - Floor Standing		
12. Height MIN Product Panel. When product panel is missing, set to 0 (HMIPP)	0	mm
13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)	0	mm
14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)	572.5	mm
15. Type of preparation to fix the cover door	No drilling template	
Retrace back socle		
16. Depth of the socle retrace at the rear side (DBSR)	48	mm
17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)	120	mm
TEMPLATE NAME		
00. Name of the template to be used	DISH_FREESTANDING60CM	