| PRODUCT FICHE HOOD | |
|---|-------------|
| Trademark | WHIRLPOOL |
| Model identifier | AKR 474 IXL |
| Annual Energy Consumption | 54,4 kWh/a |
| Energy Efficiency Class | А |
| Fluid Dynamic Efficiency | 31,3 |
| Fluid Dynamic Efficiency class | А |
| Lighting efficiency in lux/Watt | 29,0 lux/W |
| Lighting efficiency class | А |
| Grease filtering efficiency | 86,0 % |
| Grease filtering efficiency class | В |
| Minimum air flow | 384 m³/h |
| Maximum Air flow | 496 m³/h |
| Air flow boost | 757 m³/h |
| A-weighted sound power at min. speed | 58 dB(A) |
| A-weighted sound power at max. speed | 65 dB(A) |
| A-weighted sound power boost | 75 dB(A) |
| Power consumption in off-mode | 0,00 W |
| Power consumption in standby mode | 0,49 W |
| Time increase factor (f) | 0,9 |
| Energy Efficiency Index (EEI _{hood}) | 52,8 |
| Measured air flow rate at best efficiency point (QBEP) | 384,0 m³/h |
| Measured air pressure at best efficiency point (PBEP) | 454 Pa |
| Measured electric power input at best efficiency point (W _{BEP}) | 154,5 W |
| Nominal power of the lighting system (W _L) | 5,0 W |
| Average illumination of the lighting system on the cooking surface (E _{middle}) | 145 lux |