

AMW 730/IX

12NC/Fx: 859991010420

GTIN (EAN) code: 8003437395567

DIMENSION		MEASUR	
OVERALL CABINET			
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	380	mm	
MIN Height of the base cabinet niche, including all required space for installation or ventilatior	n 380	mn	
MAX Height of the wall cabinet niche, including all required space for installation or ventilatior	n 0	mn	
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	383	mn	
MAX Height of the base cabinet niche, including all required space for installation or ventilatio	n 383	mn	
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mn	
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mn	
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mn	
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mn	
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mn	
MAX Width of the base cabinet niche, including all required space for installation or ventilatior	n 568	mn	
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mr	
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mr	
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550	mr	
Space in front, which is required to install bottom trim	7	mr	
ndicates whether a ventilation opening is needed or not. Default is "N"	No		
WALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-		
Minimum space or inbound ventilation (wall cabinet)	0	mr	
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm	
WALL CABINET (vent-shaft outgoing)			
ndicates the position of the freespace for the outbound airflow (wall cabinet)	-		
Vinimum space or outbound ventilation (wall cabinet)	0	mr	
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm	
TALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-		
Minimum space for inbound ventilation (tall cabinet)	0	mr	
Minimum area for inbound ventilation cavity (tall cabinet)	0	cm	
TALL CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-		
Minimum space for outbound ventilation (tall cabinet)	0	mr	
Minimum area for outbound ventilation cavity (tall cabinet)	0	cm	
BASE CABINET (vent-shaft incoming)		0	
Indicates the position of the freespace for the inbound airflow (base cabinet)	-		
Minimum space for inbound ventilation (base cabinet)	0	mr	
Minimum area for inbound ventilation cavity (base cabinet)	0	cm	
BASE CABINET (vent-shaft outgoing)	U	on	
Indicates the position of the freespace for the outbound airflow (base cabinet)	-		
Minimum space for outbound ventilation (base cabinet)	0	mr	
Minimum area for outbound ventilation cavity (base cabinet)	0	cm	

DIMENSION		IEASURE		
APPLIANCE				
Height of the front	385	mm		
Width of the front	595	mm		
Depth of the front	20	mm		
Maximum depth all protruding elements, e.g. handles, controls	40	mm		
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	0	mm		
Projection of front in relation to housing of appliance	12	mm		
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	0	mm		
When product panel is missing, set to 0	120	mm		
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	290	mm		
Height from bearing area of appliances and lower handle	265	mm		
Frontal handle thickness	30	mm		
Frontal handle width	521	mm		
MIN Height of the product body	373	mm		
MAX Height of the product body	373	mm		
Width of the product body	539	mm		
Depth of the product body	494	mm		
Full depth of product excluding protruding interface elements	514	mm		
Minimum height from bottom line hood to top line air outlet	0	mm		
Maximum height from bottom line hood to top line air outlet	0	mm		
Diameter minimum air outlet	0	mm		
Diameter maximum air outlet	0	mm		
Indicates measure between center of air outlet hole and rear wall	0	mm		
Projection of the rear flap in relation to bearing area	0	mm		
Height tube connection for air outlet	0	mm		
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	-			
Appliance Flap door				
Projection of the opened flap in relation to bearing area	5	mm		
Maximum angle when flap door is opened totally	85	mm		
Appliance Side swing door				
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mm		
Lateral projection of opened front at the side where the hinge is fixed	0	mm		
Maximum angle when door is opened totally	0	mm		
Appliance other				
Depth from front end of the niche to the front end of the freespace of the retrace	0	mm		
Height from niche to bottom end of freespace for the retrace	0	mm		