

**IF A1.UK.1** 

12NC/Fx: F155623

## GTIN (EAN) code: 8050147556238

| DIMENSION ME   | EASL | JRE |
|--|------|-----|
| WOODEN CABINET - Overall Wooden Cabinet - BI   |      |     |
| 01. Height MIN of the tall cabinet Niche, including all required space for installation or ventilation (HMIN_T)                                      | 820  | mm  |
| 02. Height MAX of the tall cabinet Niche, including all required space for installation or ventilation (HMAN_T)                                      | 890  | mm  |
| 03. Width MIN of the tall cabinet Niche, including all required space for installation or ventilation (WMIN_T)                                       | 600  | mm  |
| 04. Width MAX of the tall cabinet Niche, including all required space for installation or ventilation (WMAN_T)                                       | 600  | mm  |
| 05. Depth of the tall cabinet Niche, including all required space for installation or ventilation (DN_T)   | 550  | mm  |
| 06. Height MIN of the base cabinet Niche, including all required space for installation or ventilation (HMIN_B)                                      | 820  |     |
| 07. Height MAX of the base cabinet Niche, including all required space for installation or ventilation (HMAN_B)                                      | 890  |     |
| 08. Width MIN of the base cabinet Niche, including all required space for installation or ventilation (WMIN_B)                                       | 599  |     |
| 09. Width MAX of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B)                                       | 601  |     |
| 10. Depth of the base cabinet Niche, including all required space for installation or ventilation (DN_B)   | 550  |     |
| 11. Indicates whether a ventilation opening is needed or not. Default is "N"   | No   |     |
| 12. Appliance can be used as base for other appliances from the same manufacturer. Default is "N"  | Yes  |     |
| WOODEN CABINET - Door - Drawer   |      |     |
| 13. Height MIN Decorative Front, if appliance has more than one front, only the most bottom left front is described here (HMIF)                      | 645  | mm  |
| 14. Width MIN Decorative Front, if appliance has more than one front, only the most bottom left front is described here (WMIF)                       | 586  | mm  |
| 15. Weight/Thickness of the decorative bottom front panel of the Kitchen manufacturer needs (essential)  | Yes  |     |
| 16. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)  | 0    | kg  |
| 17. Thickness MIN Decorative Front, if appliance has more than one front only the most bottom left front is described here(TMIF)                     | 0    | mm  |
| <ol> <li>Thickness MAX Decorative Front, if appliance has more than one front only the most bottom left<br/>front is described here(TMAF)</li> </ol> | 0    | mm  |
| Additional Fronts (2 doors)  |      |     |
| 19. Height MIN Decorative Front, when appliance has more than one front, upper front is discribed here (HMIFU)                                       | 0    | mm  |
| 20. Width MIN Decorative Front, when appliance has more than one front, upper front is discribed here (WMIFU)  | 0    | mm  |
| 21. Weight/Thickness of the decorative upper front panel of the Kitchen manufacturer needs (essential)   | Yes  |     |
| 22. Weight MAX of the decorative upper front panel of the Kitchen manufacturer (WEMAFU)  | 0    | kg  |
| 23. Thickness MIN Decorative Front, when appliance has more than one front, upper front is discribed here (TMIFU)                                    | 0    | mm  |
| 24. Thickness MAX Decorative Front, when appliance has more than one front, upper front is discribed here (TMAFU)                                    | 0    | mm  |
|  |      |     |

| DIMENSION   | MEASU                | RE |
|---|----------------------|----|
| APPLIANCE   |                      |    |
| Overall Appliance   |                      |    |
| 01. Height MIN Product, watch the detail drawing for the exact position of the dimension line (HMIP)                                  | 819                  | mm |
| 02. Height MAX product, watch the detail drawing for the exact position of the dimension line (HMAP)                                  | 889                  | mm |
| 03. Width product, watch the detail drawing for the exact position of the dimension line (WP)   | 597                  | mm |
| 04. Depth product without front, watch the detail drawing for the exact position of the dimension line (DP)                           | 500                  | mm |
| 05. Depth product, watch the detail drawing for the exact position of the dimension line (D)  | 545                  | mm |
| 06. Depth MIN plinth return front (DMIPRF)  | 0                    | mm |
| 07. Depth MAX plinth return front (DMAPRF)  | 93                   | mm |
| 08. Height MIN Plinth return. This dimension is taken by minimum appliance height (HMIPR)   | 198                  | mm |
| 09. Height MAX Plinth return. This dimension is taken at minimum appliance height (HMAPR)   | 268                  | mm |
| Door or Drawer  |                      |    |
| 10. Height front. When appliance has more than one front, only the most bottom left front is discribed here (HF)                      | 0                    | mm |
| 11. Width front. When appliance has more than one front, only the most bottom left front is discribed here (WF)                       | 597                  | mm |
| 12. Depth front (DF)  | 0                    | mm |
| 13. Maximum depth all protruding elements, e.g. handles, controls (DC)  | 0                    | mm |
| 14. Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than $90^\circ$ (CC) | 0                    | mm |
| 15. Projection of front in relation to housing of appliance (FPT)   | 20                   | mm |
| 16. Projection of front in relation to bearing area of the appliance. Taken at MIN height of appliance if adjustable height(FPB)      | 0                    | mm |
| 17. Height Product Panel. When product panel is missing, set to 0 (HMAPP)   | 35                   | mm |
| 18. Lateral projection of front including controls when door is opened totaly. At the side where the hinge is mounted (FPOD)          | 0                    | mm |
| 19. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)              | 638                  | mm |
| 20. Lateral projection of opened front at the side where the hinge is fixed (FPD)   | 0                    | mm |
| 21. Door hinge positiong and tipology   | Right-<br>changeable |    |
| 22. Type of preparation to fix the cover door   | Fixed mounting       |    |
| 23. Maximum angle when door is opened totaly (AOD)  | 105                  | 0  |
| 24. Maximum thickness of the upper front panel (TUFP)   | 4                    | mm |
| Additional Fronts (2 doors)   |                      |    |
| 25. Height front, when appliance has more than one front, upper front is discribed here (HUF)   | 0                    | mm |
| 26. Width front, when appliance has more than one front, upper front is discribed here (WUF)  | 0                    | mm |
| 27. Useful space between the 2 doors, including hinges size (HMAFG)   | 20                   | mm |
| 28. Distance between the bottom of the product and the center line between the fridge doors (HFG)                                     | 0                    | mm |

| TALL WOODEN CABINET - Vent-shaft incoming   |   |                 |
|---|---|-----------------|
| 25. Indicates the position of the freespace for the incoming airflow, tall wooden cabinet | - |                 |
| 26. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TI)                              | 0 | mm              |
| 27. Ventilation cavity minimum, tall wooden cabinet (VC_TI)                               | 0 | cm <sup>2</sup> |
| TALL WOODEN CABINET - Vent-shaft outgoing   |   |                 |
| 28. Indicates the position of the freespace for the outgoing airflow, tall wooden cabinet | - |                 |
| 29. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TO)                              | 0 | mm              |
| 30. Ventilation cavity minimum, tall wooden cabinet (VC_TO)                               | 0 | cm <sup>2</sup> |
| BASE WOODEN CABINET - Vent-shaft incoming   |   |                 |
| 31. Indicates the position of the freespace for the incoming airflow, base wooden cabinet | - |                 |
| 32. Clearance MIN Ventilation, base wooden cabinet (CMIV_BI)                              | 0 | mm              |
| 33. Ventilation cavity minimum, base wooden cabinet (VC_BI)                               | 0 | cm <sup>2</sup> |
| BASE WOODEN CABINET - Vent-shaft outgoing   |   |                 |
| 34. Indicates the position of the freespace for the outgoing airflow, base wooden cabinet | - |                 |
| 35. Clearance MIN Ventilation, base wooden cabinet (CMIV_BO)                              | 0 | mm              |
| 36. Ventilation cavity minimum, base wooden cabinet (VC_BO)                               | 0 | cm <sup>2</sup> |
|   |   |                 |