

12NC/Fx: 858743915900

GTIN (EAN) code: 8003437395406

DIMENSION	MEAS	URI
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	360	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	360	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	363	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	363	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	568	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	560	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	300	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	300	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	0	mm
Space in front, which is required to install bottom trim	0	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	No	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm ²
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm ²
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-	
Minimum space for inbound ventilation (tall cabinet)	0	mm
Minimum area for inbound ventilation cavity (tall cabinet)	0	cm ²
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	0	cm ²
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	-	
Minimum space for inbound ventilation (base cabinet)	0	mm
Minimum area for inbound ventilation cavity (base cabinet)	0	cm ²
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	-	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	0	cm ²

Height of the front 382 Width of the front 595 Depth of the front 21 Maximum depth all protruding elements, e.g. handles, controls 21 Maximum depth all protruding elements, e.g. handles, controls 21 Maximum depth all protruding elements, e.g. handles, controls 22 Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees 2 Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable 32 When product panel is missing, set to 0 32 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension 34 Height from bearing area of appliances and lower handle 34 Horntal handle width 34 Horntal handle width 34 Horntal handle width 34 Horntal handle width 34 Horntal handle bear and the product body 34 Handle of the product body 34 Handle of the product body 34 Horntal handle width 34 Horn	DIMENSION		EASURE	
Width of the front 21 Maximum depth all protruding elements, e.g. handles, controls 0 Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees 0 Projection of front in relation to housing of appliance 0 Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable 0 When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension 0 Height from bearing area of appliances and lower handle 0 Frontal handle thickness 0 Frontal handle width 0 MiN Height of the product body 348 MAX Height of the product body 348 Midth of the product body 348 Minimum height from bottom line hood to top line air outlet 0 Maximum height from bottom line hood to top line air outlet 0 Diameter minimum air outlet 0 Diameter minimum air outlet 0 Indicates measure between center of air outlet hole and rear wall 0 Projection of the rear flap in relation to bearing area 0 Height tube connection for air outlet 1 Appliance Flap door 1 Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally Appliance Side swing door 1 Appliance Side swing door 2 Appliance Side swing door 3 Appliance Side swing door 3 Eateral projection of opened front at the side where the hinge is fixed 3 Appliance other 1 Depth from front end of the niche to the front end of the freespace of the retrace 0 Depth from front end of the hinche to the front end of the freespace of the retrace 0	APPLIANCE			
Depth of the front Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to busing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Protrotal handle thickness Frontal handle width MIN Height of the product body MIN Height of the product body MIN Height of the product body 299 Full depth of the product body 299 Full depth of product excluding protruding interface elements Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Diameter maximum air outlet Diameter maximum air outlet O Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area O Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted of the nort end of the niche to the front end of the freespace of the retrace O Depth from front end of the niche to the front end of the freespace of the retrace Depth from front end of the niche to the front end of the freespace of the retrace	Height of the front	382	mm	
Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 Frontal handle width 0 MIN Height of the product body 348 MAX Height of the product body 348 Width of the product body 544 Depth of the product body 549 Full depth of product excluding protruding interface elements Minimum height from bottom line hood to top line air outlet 0 Diameter maximum air outlet 0 Diameter maximum air outlet 0 Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area 0 Appliance Flap door Projection of the opened flap in relation to bearing area 0 Appliance Flap door Projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of poened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 Appliance other Depth from front end of the niche to the front end of the freespace of the retrace	Width of the front	595	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness O Frontal handle width O MIN Height of the product body MAX Height of the product body Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle width O MIN Height of the product body Space in front in the product body MAX Height of the product body Space in front, which is required to guarantee full operability. The most protruding part gives this dimension MIN Height from beating area of appliances and lower handle Frontal handle width O MIN Height from bottom to body Space in front, which is required to guarantee full operability. The most protruding part gives this dimension MIN Height from bottom to body Space in front, which is required to guarantee elements MIN Height from bottom line hood to top line air outlet O Indicates measure between center of air outlet hole and rear wall O Height tube connection for air outlet Appliance and be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Auximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the f	Depth of the front	21	mm	
neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 Frontal handle width 0 MIN Height of the product body 348 MAX Height of the product body 348 Width of the product body 348 Width of the product body 348 Width of the product body 349 Full depth of product excluding protruding interface elements 316 Minimum height from bottom line hood to top line air outlet 0 Maximum height from bottom line hood to top line air outlet 0 Diameter minimum air outlet 10 Diameter maximum air outlet 0 Projection of the rear flap in relation to bearing area 0 Height tube connection for air outlet 0 Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Maximum depth all protruding elements, e.g. handles, controls	0	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 80 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 0 Frontal handle width 0 MIN Height of the product body 348 Width of the product body 348 Width of the product body 299 Full depth of product excluding protruding interface elements 316 Minimum height from bottom line hood to top line air outlet 0 Maximum height from bottom line hood to top line air outlet 0 Diameter maximum air outlet 0 Indicates measure between center of air outlet hole and rear wall 0 Projection of the rear flap in relation to bearing area 0 Height tube connection for air outlet 0 Appliance Can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally 0 Appliance Side swing door Lateral projection of opened front at the side where the hinge is mounted 1 Lateral projection of opened front at the side where the hinge is fixed 3 Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	· · · · · · · · · · · · · · · · · · ·	0	mm	
appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness O Frontal handle width MIN Height of the product body MAX Height of the product body Space in front, which is required to guarantee full operability. The most protruding part gives this dimension MIN Height of the product body MAX Height of the product body Space in the product bod	Projection of front in relation to housing of appliance	20	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle OFFORTIAL handle thickness OFFORTIAL handle width MIN Height of the product body MAX Height of the product body MAX Height of the product body S44 Depth of the product body Full depth of product excluding protruding interface elements Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet ODIAL Diameter minimum air outlet Diameter maximum air outlet Diameter maximum air outlet OPProjection of the rear flap in relation to bearing area Height tube connection for air outlet OAPpliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area OAPpliance Side swing door Lateral projection of opened front at the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace O Appliance other Depth from front end of the niche to the front end of the freespace of the retrace	, ,	14	mm	
dimension Height from bearing area of appliances and lower handle O Frontal handle thickness O Frontal handle width O MIN Height of the product body MAX Height of the product body S44 Depth of the product body Depth of the product body S44 Depth of product body S44 Depth of product body S44 Depth of product excluding protruding interface elements S316 Minimum height from bottom line hood to top line air outlet O Maximum height from bottom line hood to top line air outlet O Diameter minimum air outlet O Diameter maximum air outlet O Drojection of the rear flap in relation to bearing area O Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area O Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace O	When product panel is missing, set to 0	80	mm	
Frontal handle thickness 0 Frontal handle width 0 MIN Height of the product body 348 MAX Height of the product body 544 Width of the product body 544 Depth of the product body 544 Minimum height from bottom line hood to top line air outlet 0 Minimum height from bottom line hood to top line air outlet 0 Maximum height from bottom line hood to top line air outlet 0 Diameter minimum air outlet 0 Diameter maximum air outlet 0 Indicates measure between center of air outlet hole and rear wall 0 Projection of the rear flap in relation to bearing area 0 Height tube connection for air outlet 0 Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally 0 Appliance Side swing door 0 Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted 1 Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally 85 Appliance other 1 Depth from front end of the niche to the front end of the freespace of the retrace 0		593	mm	
Frontal handle width 0 MIN Height of the product body 348 MAX Height of the product body 544 Width of the product body 544 Depth of the product body 299 Full depth of product excluding protruding interface elements 316 Minimum height from bottom line hood to top line air outlet 0 Maximum height from bottom line hood to top line air outlet 0 Diameter minimum air outlet 0 Diameter maximum air outlet 0 Diameter maximum air outlet 1 Diameter maximum air	Height from bearing area of appliances and lower handle	0	mm	
MIN Height of the product body MAX Height of the product body Width of the product body Depth of the product body Full depth of product excluding protruding interface elements Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet O Diameter minimum air outlet Diameter maximum air outlet O Diameter maximum air outlet O Indicates measure between center of air outlet hole and rear wall O Projection of the rear flap in relation to bearing area O Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area O Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace O description of the retrace	Frontal handle thickness	0	mm	
MAX Height of the product body Width of the product body Depth of the product body Full depth of product excluding protruding interface elements 316 Minimum height from bottom line hood to top line air outlet 0 Maximum height from bottom line hood to top line air outlet 0 Diameter minimum air outlet 0 Diameter maximum air outlet 0 Indicates measure between center of air outlet hole and rear wall 0 Projection of the rear flap in relation to bearing area 0 Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0 348 348 348 348 349 348 349 340 340 341 341 342 343 348 348 348 346 347 348 348 348 348 348 348 348	Frontal handle width	0	mm	
Width of the product body Depth of the product body Pfull depth of product excluding protruding interface elements 316 Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet 0 Diameter minimum air outlet 0 Diameter maximum air outlet 0 Diameter maximum air outlet 0 Indicates measure between center of air outlet hole and rear wall 0 Projection of the rear flap in relation to bearing area 0 Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	MIN Height of the product body	348	mm	
Depth of the product body Full depth of product excluding protruding interface elements 316 Minimum height from bottom line hood to top line air outlet 0 Maximum height from bottom line hood to top line air outlet 0 Diameter minimum air outlet 0 Diameter maximum air outlet 0 Diameter maximum air outlet 0 Projection of the rear flap in relation to bearing area 0 Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally Appliance Other Depth from front end of the niche to the front end of the freespace of the retrace 0 0 0 0 0 0 0 0 0 0 0 0 0	MAX Height of the product body	348	mm	
Full depth of product excluding protruding interface elements Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Diameter minimum air outlet Diameter maximum air outlet Diame	Width of the product body	544	mm	
Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Diameter minimum air outlet Diameter maximum air outlet O Diameter maximum air outlet O Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area O Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Depth of the product body	299	mm	
Maximum height from bottom line hood to top line air outlet 0 Diameter minimum air outlet 0 Diameter maximum air outlet 0 Indicates measure between center of air outlet hole and rear wall 0 Projection of the rear flap in relation to bearing area 0 Height tube connection for air outlet 0 Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally 0 Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted 1 Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally 85 Appliance other 0 Depth from front end of the niche to the front end of the freespace of the retrace 0	Full depth of product excluding protruding interface elements	316	mm	
Diameter minimum air outlet Diameter maximum air outlet Diameter maximum air outlet O Indicates measure between center of air outlet hole and rear wall O Projection of the rear flap in relation to bearing area O Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area O Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Minimum height from bottom line hood to top line air outlet	0	mm	
Diameter maximum air outlet Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area OHeight tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area OMaximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Maximum height from bottom line hood to top line air outlet	0	mm	
Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area 0 Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Diameter minimum air outlet	0	mm	
Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally 0 Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally 85 Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Diameter maximum air outlet	0	mm	
Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Indicates measure between center of air outlet hole and rear wall	0	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally 0 Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally 85 Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Projection of the rear flap in relation to bearing area	0	mm	
Appliance Flap door Projection of the opened flap in relation to bearing area 0 Maximum angle when flap door is opened totally 0 Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally 85 Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Height tube connection for air outlet	0	mm	
Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Appliance can be used as base for other appliances from the same manufacturer. Default is "No)" -		
Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Appliance Flap door			
Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Projection of the opened flap in relation to bearing area	0	mm	
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Maximum angle when flap door is opened totally	0	mm	
mounted Lateral projection of opened front at the side where the hinge is fixed 2 Maximum angle when door is opened totally 85 Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Appliance Side swing door			
Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0		s 0	mm	
Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 0	Lateral projection of opened front at the side where the hinge is fixed	2	mm	
Depth from front end of the niche to the front end of the freespace of the retrace 0	Maximum angle when door is opened totally	85	mm	
·	Appliance other			
Height from niche to bottom end of freespace for the retrace 0	Depth from front end of the niche to the front end of the freespace of the retrace	0	mm	
	Height from niche to bottom end of freespace for the retrace	0	mm	