

CIA 640 B

12NC: F104112

GTIN (EAN) code: 5054645041121







Product group Built-in Type of control Electronic Type of control Electronic Type of control settings Number of gas burners 0 Number of electric cooking zones 4 Number of electric plates 0 Number of radiant plates 0 Number of induction plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 7200 Gas connection rating (W) 7200 Gas type N/A Current (A) 31,3 Voltage (V) 230 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 580 Height of the product 550 Depth of the product 560 Niche depth 490 Net weight (kg) 8 Automatic programmes	MAIN FEATURES	
Type of control Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) 31,3 Voltage (V) Plug type No Gas connection Plug type No Gas connection N/A Width of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) Relectroical one Electronic O Current (A) A Black Electrical Connection rating (W) O Current (A) 31,3 Voltage (V) 230 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 56 Depth of the product 56 Depth of the product 56 Ninimum niche width Niche depth Net weight (kg) 8	Product group	Hob
Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) 31,3 Voltage (V) Plug type No Gas connection Plug type No Gas connection N/A Width of the product Beach Beach Biack Black Bl	Construction type	Built-in
Number of gas burners0Number of electric cooking zones4Number of electric plates0Number of radiant plates0Number of induction plates4Number of electric warming zones0Location of control panelFrontBasic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)0Gas connection rating (W)0Gas typeN/ACurrent (A)31,3Voltage (V)230Frequency (Hz)50/60Length of Electrical Supply Cord (cm)120Plug typeNoGas connectionN/AWidth of the product56Depth of the product56Depth of the product510Minimum niche height30Minimum niche width560Niche depth490Net weight (kg)8	Type of control	Electronic
Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) 31,3 Voltage (V) 230 Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Beach Black Black Black 10 11 120 120 120 120 120 Plug type No Gas connection N/A Width of the product 560 Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) 8	Type of control settings	-
Number of electric plates 0 Number of radiant plates 0 Number of induction plates 4 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 7200 Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 230 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 580 Height of the product 56 Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Number of gas burners	0
Number of radiant plates 0 Number of induction plates 4 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 230 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 580 Height of the product 56 Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Number of electric cooking zones	4
Number of halogen plates0Number of induction plates4Number of electric warming zones0Location of control panelFrontBasic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)7200Gas connection rating (W)0Gas typeN/ACurrent (A)31,3Voltage (V)230Frequency (Hz)50/60Length of Electrical Supply Cord (cm)120Plug typeNoGas connectionN/AWidth of the product580Height of the product56Depth of the product510Minimum niche height30Minimum niche width560Niche depth490Net weight (kg)8	Number of electric plates	0
Number of induction plates4Number of electric warming zones0Location of control panelFrontBasic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)7200Gas connection rating (W)0Gas typeN/ACurrent (A)31,3Voltage (V)230Frequency (Hz)50/60Length of Electrical Supply Cord (cm)120Plug typeNoGas connectionN/AWidth of the product580Height of the product56Depth of the product510Minimum niche height30Minimum niche width560Niche depth490Net weight (kg)8	Number of radiant plates	0
Number of electric warming zones Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Minimum niche height Minimum niche width Net weight (kg) Seramic Glass Front Front Edinatic Glass Black Electrical Supol O O O O O O O O O O O O O	Number of halogen plates	0
Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 7200 Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 230 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 580 Height of the product 556 Depth of the product 550 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Number of induction plates	4
Basic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)7200Gas connection rating (W)0Gas typeN/ACurrent (A)31,3Voltage (V)230Frequency (Hz)50/60Length of Electrical Supply Cord (cm)120Plug typeNoGas connectionN/AWidth of the product580Height of the product56Depth of the product510Minimum niche height30Minimum niche width560Niche depth490Net weight (kg)8	Number of electric warming zones	0
Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Black Black Black 8 Black	Location of control panel	Front
Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Net weight (kg) No 7200 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 811,3 7200 7	Basic surface material	Ceramic Glass
Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 230 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 580 Height of the product 56 Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Main colour of product	Black
Gas type N/A Current (A) 31,3 Voltage (V) 230 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 580 Height of the product 56 Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Electrical connection rating (W)	7200
Current (A) 31,3 Voltage (V) 230 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 580 Height of the product 56 Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Gas connection rating (W)	0
Voltage (V) 230 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 580 Height of the product 56 Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Gas type	N/A
Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type No Gas connection N/A Width of the product 580 Height of the product 56 Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Current (A)	31,3
Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) 120 No 120 120 120 120 120 120 120 12	Voltage (V)	230
Plug type No Gas connection N/A Width of the product 580 Height of the product 56 Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Frequency (Hz)	50/60
Gas connection N/A Width of the product 580 Height of the product 56 Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Length of Electrical Supply Cord (cm)	120
Width of the product 580 Height of the product 56 Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Plug type	No
Height of the product 56 Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Gas connection	N/A
Depth of the product 510 Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Width of the product	580
Minimum niche height 30 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Height of the product	56
Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Depth of the product	510
Niche depth 490 Net weight (kg) 8	Minimum niche height	30
Net weight (kg) 8	Minimum niche width	560
- , -,	Niche depth	490
Automatic programmes No	Net weight (kg)	8
	Automatic programmes	No

TECHNICAL FEATURES	
Power on indicator	Yes
Number of indicators	4
Type of regulation	Induction
Type of lid	Without
Residual heat indicator	Separate
Main on/off switch	Yes
Safety device	-
Timer	Yes

PERF	ORMANCES
Energy input	Electric