

12NC/Fx: F102299

GTIN (EAN) code: 5054645022991

DIMENSION	MEAS	υR
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	870	mn
MIN Height of the base cabinet niche, including all required space for installation or ventilation	870	mn
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mn
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	872	mn
MAX Height of the base cabinet niche, including all required space for installation or ventilation	870	mn
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mn
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	562	mn
MIN Width of the base cabinet niche, including all required space for installation or ventilation	562	mn
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mn
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mn
MAX Width of the base cabinet niche, including all required space for installation or ventilation	562	mn
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mr
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mr
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550	mr
Space in front, which is required to install bottom trim	10	mr
Indicates whether a ventilation opening is needed or not. Default is "N"	-	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-	
Minimum space or inbound ventilation (wall cabinet)	0	mr
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-	
Minimum space or outbound ventilation (wall cabinet)	0	mr
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-	
Minimum space for inbound ventilation (tall cabinet)	50	mr
Minimum area for inbound ventilation cavity (tall cabinet)	281	cm
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-	
Minimum space for outbound ventilation (tall cabinet)	50	mr
Minimum area for outbound ventilation cavity (tall cabinet)	281	cm
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	-	
Minimum space for inbound ventilation (base cabinet)	50	mr
Minimum area for inbound ventilation cavity (base cabinet)	281	cm
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	-	
Minimum space for outbound ventilation (base cabinet)	50	mr
Minimum area for outbound ventilation cavity (base cabinet)	281	cm

APPLIANCE Height of the front 882 mm Width of the front 595 mm Depth of the front 25 mm Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 25 mm Frontal handle width 513 mm MIN Height of the product body MAX Height of the product body MAX Height of the product body Set of front product body Set of more product product protruding interface elements Set of more product prod	DIMENSION MEASU		JRE	
Width of the front Depth of the front 25 mm Depth of the front 25 mm Maximum depth all protruding elements, e.g. handles, controls 53 mm Lateral clearance between front edge and most protruding elements which avoid to open a 141 mm neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 15 mm Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height for the product body 15 mm Height of the product body 15 mm Height for the product body 15 mm Height Min Height meter and front 15 mm Height Min Plinth return and front 15 mm Height Min Plinth return. This dimension is taken at maximum appliance height 15 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" 15 mm Appliance Flap door 15 mm Height Max Plinth return. This dimension is taken at maximum appliance height 15 mm Appliance Side swing door 15 mm Height Max Plinth return. This dimension is taken at maximum appliance height 15 mm Appliance Side swing door 15 mm Height Max Plinthreturn to bearing area 15 mm Maximum angle when flap door is opened totally 15 mm Appliance Side swing door 15 mm Height Max Plinthreturn Appliance Side swing door 15 mm Height Max Plinthreturn Appli	APPLIANCE			
Width of the front Depth of the front 25 mm Depth of the front 25 mm Maximum depth all protruding elements, e.g. handles, controls 53 mm Lateral clearance between front edge and most protruding elements which avoid to open a 141 mm neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 15 mm Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height from bearing area of appliances and lower handle 15 mm Height for the product body 15 mm Height of the product body 15 mm Height for the product body 15 mm Height Min Height meter and front 15 mm Height Min Plinth return and front 15 mm Height Min Plinth return. This dimension is taken at maximum appliance height 15 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" 15 mm Appliance Flap door 15 mm Height Max Plinth return. This dimension is taken at maximum appliance height 15 mm Appliance Side swing door 15 mm Height Max Plinth return. This dimension is taken at maximum appliance height 15 mm Appliance Side swing door 15 mm Height Max Plinthreturn to bearing area 15 mm Maximum angle when flap door is opened totally 15 mm Appliance Side swing door 15 mm Height Max Plinthreturn Appliance Side swing door 15 mm Height Max Plinthreturn Appli	Height of the front	882	mm	
Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 25 mm Frontal handle width 513 mm MIN Height of the product body MaX Height of the product body Moth of the product body 561 mm Width of the product body 562 mm Full depth of product excluding protruding interface elements 575 mm	-			
Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 25 mm Frontal handle width 513 mm MIN Height of the product body MaX Height of the product body Moth of the product body 561 mm Width of the product body 562 mm Full depth of product excluding protruding interface elements 575 mm	Depth of the front	25	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 25 mm Frontal handle thickness 25 mm Frontal handle thickness 26 mm MINI Height of the product body 867 mm MAX Height of the product body 867 mm Width of the product body 560 mm Full depth of product excluding protruding interface elements 575 mm	·	53		
Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 115 mm Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Frontal handle thickness 25 mm Frontal handle width 513 mm MIN Height of the product body 867 mm Wax Height of the product body 561 mm Depth of the product body 561 mm Depth of the product body 561 mm Full depth of product excluding protruding interface elements 575 mm	Lateral clearance between front edge and most protruding elements which avoid to open a	41	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness Frontal handle width MIN Height of the product body MAX Height of the product body MOITH the product body MOITH the product body MOITH the product body MOITH the product excluding protruding interface elements The product excluding protruding interface elements MOITH the product excluding product excluding product excluding product excluding product elements MOITH the product excluding		15	mm	
When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 25 mm Frontal handle width 513 mm MIN Height of the product body 867 mm Wax Height of the product body 561 mm Depth of the product body 561 mm Depth of product excluding protruding interface elements 575 mm	Projection of front in relation to bearing area of the appliance. Taken at minimum height of	3	mm	
dimension Height from bearing area of appliances and lower handle Frontal handle thickness 25 mm Frontal handle width 513 mm MIN Height of the product body 867 mm MAX Height of the product body 561 mm Depth of the product body 561 mm Pull depth of product excluding protruding interface elements 575 mm		115	mm	
Frontal handle thickness 25 mm Frontal handle width 513 mm MIN Height of the product body 867 mm MAX Height of the product body 561 mm Oepth of the product body 550 mm Full depth of product excluding protruding interface elements 575 mm - MIN depth between plinth return and front 0 mm MAX depth between plinth return and front 0 mm Height MIN Plinth return. This dimension is taken by minimum appliance height 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 5 mm Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm		465	mm	
Frontal handle width 8513 mm MIN Height of the product body 867 mm MAX Height of the product body 867 mm Width of the product body 551 mm Depth of the product body 550 mm Full depth of product excluding protruding interface elements 575 mm - mm - mm - mm - mm - mm MIN depth between plinth return and front 0 mm MAX depth between plinth return and front 0 mm MAX depth between plinth return and front 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 5 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 655 mm	Height from bearing area of appliances and lower handle	439	mm	
MIN Height of the product body MAX Height of the product body Sef mm Midth of the product body Depth of the product body Full depth of product excluding protruding interface elements - mm - mm - mm MIN depth between plinth return and front MAX depth between plinth return. This dimension is taken by minimum appliance height Height MIN Plinth return. This dimension is taken at maximum appliance height Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Depth from front end of the niche to the front end of the freespace of the retrace 867 mm mm Maximum angle when door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally Appliance other	Frontal handle thickness	25	mm	
MAX Height of the product body Midth of the product body Depth of the product body Full depth of product excluding protruding interface elements The product excluding product excluding elements The product excluding product excluding elements The product excluding elements The product excluding elements The product excluding elements The p	Frontal handle width	513	mm	
Width of the product body Depth of the product body Full depth of product excluding protruding interface elements The product excluding product excluding area The pr	MIN Height of the product body	867	mm	
Depth of the product body Full depth of product excluding protruding interface elements - mm - mm -	MAX Height of the product body	867	mm	
Full depth of product excluding protruding interface elements - mm MIN depth between plinth return and front 0 mm MAX depth between plinth return and front 0 mm Height MIN Plinth return. This dimension is taken by minimum appliance height 0 mm Height MAX Plinth return. This dimension is taken at maximum appliance height 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 5 mm Maximum angle when flap door is opened totally 8 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Appliance other 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	Width of the product body	561	mm	
- mm MIN depth between plinth return and front 0 mm MAX depth between plinth return and front 0 mm Height MIN Plinth return. This dimension is taken by minimum appliance height 0 mm Height MAX Plinth return. This dimension is taken at maximum appliance height 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 5 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	Depth of the product body	550	mm	
- mm mm mm mm mm mm mm mm mm - mm mm mm mm mm mm mm mm MIN depth between plinth return and front 0 mm MAX depth between plinth return and front 0 mm Height MIN Plinth return. This dimension is taken by minimum appliance height 0 mm Height MAX Plinth return. This dimension is taken at maximum appliance height 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 5 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	Full depth of product excluding protruding interface elements	575	mm	
- mm - mMIN depth between plinth return and front omm - mMAX depth between plinth return and front omm - mm MAX depth between plinth return and front omm MAX depth between plinth return and front omm Height MIN Plinth return. This dimension is taken by minimum appliance height omm Height MAX Plinth return. This dimension is taken at maximum appliance height omm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" omm Appliance Flap door Projection of the opened flap in relation to bearing area omm Maximum angle when flap door is opened totally omm Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed omm Maximum angle when door is opened totally omm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace of 65 mm	-	-	mm	
- mm - mMIN depth between plinth return and front 0 mm MAX depth between plinth return and front 0 mm MAX depth between plinth return and front 0 mm Height MIN Plinth return. This dimension is taken by minimum appliance height 0 mm Height MAX Plinth return. This dimension is taken at maximum appliance height 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 5 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	-	-	mm	
- mm MIN depth between plinth return and front 0 mm MAX depth between plinth return and front 0 mm Height MIN Plinth return. This dimension is taken by minimum appliance height 0 mm Height MAX Plinth return. This dimension is taken at maximum appliance height 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 5 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	-	-	mm	
- mm MIN depth between plinth return and front MAX depth between plinth return and front MAX depth between plinth return and front Height MIN Plinth return. This dimension is taken by minimum appliance height O mm Height MAX Plinth return. This dimension is taken at maximum appliance height Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 5 mm		-	mm	
MIN depth between plinth return and front MAX depth between plinth return and front Height MIN Plinth return. This dimension is taken by minimum appliance height O mm Height MAX Plinth return. This dimension is taken at maximum appliance height Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	-	-	mm	
MAX depth between plinth return and front Height MIN Plinth return. This dimension is taken by minimum appliance height 0 mm Height MAX Plinth return. This dimension is taken at maximum appliance height 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 5 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm		-	mm	
MAX depth between plinth return and front Height MIN Plinth return. This dimension is taken by minimum appliance height 0 mm Height MAX Plinth return. This dimension is taken at maximum appliance height 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 5 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	MIN depth between plinth return and front	0	mm	
Height MAX Plinth return. This dimension is taken at maximum appliance height Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	·	0	mm	
Height MAX Plinth return. This dimension is taken at maximum appliance height Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	Height MIN Plinth return. This dimension is taken by minimum appliance height	0	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 5 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm		0	mm	
Projection of the opened flap in relation to bearing area 5 mm Maximum angle when flap door is opened totally 89 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm		-		
Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	Appliance Flap door			
Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	Projection of the opened flap in relation to bearing area	5	mm	
Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	Maximum angle when flap door is opened totally	89	mm	
mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm				
Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm		0	mm	
Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm	Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 65 mm		0	mm	
Depth from front end of the niche to the front end of the freespace of the retrace 65 mm				
·	• •	65	mm	
	Height from niche to bottom end of freespace for the retrace	849	mm	