AKR 363/IX

12NC: 857836338700

EAN code: -







Product group B69/GOBAHA Type of control Mechanical Type of control Mechanical Type of control setting and signalling devices Mechanic Number of gas burners 4 Number of electric cooking zones 0 Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Hob Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Width of the product 580 Mechanical Mechanical Mechanical Mechanical Mechanical Mechanical Mechanical Mechanical Mechanical Mechanical Mechanical Netherial supple on 0 Number of electric varming zones 0 O hob Front Inox Basic surface material Inox Basic surface mater	MAIN FEATURES		
Type of control Type of control setting and signalling devices Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Prequency (Hz) Length of Electrical Supply Cord (cm) Plug type Hi Gas connection Gonic Width of the product Mechanica Mechanic A Mechanic Mechanic Nechanic Do Number of electric pates O Number of electric pates O Number of alectric warming cons O Number of alectric warming zones O Number of electric warming zones O Number of lelctric warming zone O Number of lelctric pates O Number	Product group	Hob	
Type of control setting and signalling devices Number of gas burners A Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Hi Gas connection Width of the product Beside surface material Conic Width of the product Beside surface material Conic Width of the product Beside surface material A October 1 Security 1 Security 2 Security	Construction type	Вбудована	
Number of gas burners 4 Number of electric cooking zones 0 Number of electric plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Hob Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 8000 Current (A) 0,6 Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Type of control	Mechanical	
Number of electric cooking zones 0 Number of electric plates 0 Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Hob Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 8000 Current (A) 0,6 Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Type of control setting and signalling devices	Mechanic	
Number of electric plates 0 Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Hob Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 8000 Current (A) 0,6 Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Number of gas burners	4	
Number of radiant plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Hob Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 8000 Current (A) 0,6 Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Number of electric cooking zones	0	
Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Hob Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 8000 Current (A) 0,6 Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Number of electric plates	0	
Number of induction plates 0 Number of electric warming zones 0 Location of control panel Hob Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 8000 Current (A) 0,6 Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Number of radiant plates	0	
Number of electric warming zones Location of control panel Basic surface material Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Length of Electrical Supply Cord (cm) Plug type Hi Gas connection Width of the product Depth of the product Minimum niche height Niche depth Net weight (kg) Description Hob Front Hob Front Hob Front Hob Front 100 Hob F	Number of halogen plates	0	
Location of control panel Hob Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 8000 Current (A) 0,6 Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Number of induction plates	0	
Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 8000 Current (A) 0,6 Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Number of electric warming zones	0	
Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 8000 Current (A) 0,6 Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Location of control panel	Hob Front	
Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection Conic Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) O,6 8000 850 Hi Conic Width of Electrical Supply Cord (cm) 85 Hi Conic Conic Voltage (V) 500 85 Hi Conic Voltage (V) 580 Hi 580 Height of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480	Basic surface material	Inox	
Gas connection rating (W) Current (A) O,6 Voltage (V) Ength of Electrical Supply Cord (cm) Plug type Gas connection Conic Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Net weight (kg) Son O,6 O,6 O,6 O,6 O,6 O,6 O,6 O,	Main colour of product	Inox	
Current (A) 0,6 Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Electrical connection rating (W)	0	
Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Gas connection rating (W)	8000	
Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 85 Plug type Hi Gas connection Conic Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Current (A)	0,6	
Length of Electrical Supply Cord (cm) Plug type Gas connection Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) B5 Hi 40 Conic 40 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg)	Voltage (V)	230	
Plug type Hi Gas connection Conic Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Frequency (Hz)	50	
Gas connection Conic Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Length of Electrical Supply Cord (cm)	85	
Width of the product 580 Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Plug type	Hi	
Height of the product 40 Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Gas connection	Conic	
Depth of the product 510 Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Width of the product	580	
Minimum niche height 20 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Height of the product	40	
Minimum niche width 560 Niche depth 480 Net weight (kg) 10.50	Depth of the product	510	
Niche depth 480 Net weight (kg) 10.50	Minimum niche height	20	
Net weight (kg) 10.50	Minimum niche width	560	
5 , 5,	Niche depth	480	
Automatic programmes Hi	Net weight (kg)	10.50	
	Automatic programmes	Hi	

TECHNICAL FEATURES		
Power on indicator	Hi	
Plate on indicator	0	
Type of regulation	Power burner	
Type of lid	Glass	
Residual heat indicator	without	
Main on/off switch	Hi	
Safety device	Yes	
Timer	Hi	

ENERGY LABEL	
Energy input	Gas