

TABLE 1 - Table valid only for UK								
Burner and nozzle specifications			Liquid gas				Natural gas	
Burner	Thermal Power kW (gross heat value)*		By-pass 1/100 (mm)	Nozzle 1/100	Flow* g/h		Nozzle 1/100 (mm)	Flow* l/h
	Nominal	Reduced			***	**		
Oven	2.60	1.00	46	75	189	186	119	248
Supply Pressures	Nominal (mbar)				28-30	37	20	
	Minimum (mbar)				20	25	17	
	Maximum (mbar)				35	45	25	

\* At 15°C and 1013,25 mbar-dry gas

\*\* Propane P.C.S. = 50.37 MJ/Kg

\*\*\* Butane P.C.S. = 49.47 MJ/Kg

Natural P.C.S. = 37.78 MJ/m<sup>3</sup>

City P.C.S. = 15.87 MJ/m<sup>3</sup>

Gas Part	
Category	Nominal Power kW
I12H3+	2.6 (189 g/h - G30) (186 g/h - G31)

TABLEAU 1 - Tableau valable uniquement pour la FRANCE									
Spécifications des brûleurs et des buses			Gaz liquide				Gaz naturel		
Brûleur	Puissance thermique kW (pouvoir calorifique supérieur)*		By-pass 1/100 (mm)	Buse 1/100	Débit* g/h		Buse 1/100 (mm)	Débit* l/h	
	Nominale	Réduite			***	**		G20	G25
Four	2,60	1.00	46	75	189	186	119	248	288
Pressions d'alimentation	Nominales (mbar)				28 - 30	37	20		25
	Minimums (mbar)				20	25	17		20
	Maximums (mbar)				35	45	25		30

\* À 15°C et 1013,25 mbar-gaz naturel

\*\* P.C.S. du propane = 50,37 MJ/Kg

\*\*\* P.C.S. du butane = 49,47 MJ/Kg

P.C.S. du gaz naturel = 37,78 MJ/m<sup>3</sup>

P.C.S. du gaz de ville = 15,87 MJ/m<sup>3</sup>

Partie gaz	
Catégorie	Puissance nominale kW
I12E+3+	2.6 (189 g/h - G30) (186 g/h - G31)

TABLA 1 - Tabla válida solo para ESPAÑA								
Especificaciones de los quemadores e inyectores			Gas licuado				Gas natural	
Quemador	Potencia térmica kW (poder calorífico bruto)*		Derivación 1/100 (mm)	Inyector 1/100	Caudal* g/h		Inyector 1/100 (mm)	Caudal* l/h
	Nominal	Capacidad			***	**		
Horno	2,60	1,00	46	75	189	186	119	248
Presiones de suministro	Nominal (mbar)				28-30	37	20	
	Mínimo (mbar)				20	25	17	
	Máximo (mbar)				35	45	25	

\* A 15°C y 1013,25 mbar- gas seco

\*\* Propano P.C.S. = 50.37 MJ/Kg

\*\*\* Butano P.C.S. = 49.47 MJ/Kg

Natural P.C.S. = 37.78 MJ/m<sup>3</sup>

Ciudad P.C.S. = 15.87 MJ/m<sup>3</sup>

Zona de gas	
Categoría	Potencia nominal kW
I12H3+	2.6 (189 g/h - G30) (186 g/h - G31)

**TABELA 1 - Tabela válida apenas para PORTUGAL**

Especificações dos queimadores e dos bicos			Gás liquefeito				Gás natural	
Queimador	Potência térmica kW (poder calorífico superior)*		Desvio 1/100 (mm)	Bicos 1/100	Fluxo* g/h		Bico 1/100 (mm)	Fluxo* l/h
	Nominal	Capacidade			***	**		
O forno	2,60	1,00	46	75	189	186	119	248
Pressões de alimentação	Nominal (mbar)				28-30	37	20	
	Mínima (mbar)				20	25	17	
	Máxima (mbar)				35	45	25	

\* A 15 °C e 1013,25 mbar-gás seco

\*\* P.C.S. Propano = 50,37 MJ/kg

\*\*\* P.C.S. Butano = 49,47 MJ/kg

P.C.S. Natural = 37,78 MJ/m<sup>3</sup>

P.C.S. Cidade = 15,87 MJ/m<sup>3</sup>

Parte do gás	
Categoria	Potência nominal kW
I12H3+	2,6 (189 g/h - G30)
	(186 g/h - G31)

الجدول 1 - الجدول يسري فقط على الجزائر/البحرين/مصر/العراق /الأردن/الكويت/لبنان/ليبيا/عمان/قطر/الإمارات العربية المتحدة								
الغاز الطبيعي		الغاز المسال				مواصفات الشعلة والفوهة		
التدفق* لتر/ساعة	الفوهة 100/1 (مم)	التدفق* جم/ساعة		الفوهة 100/1	التوصيلة الفرعية 100/1 (مم)	الطاقة الحرارية كيلواط (القيمة الإجمالية للحرارة)*		الشعلة
		**	***			مخفض	الاسمي	
248	119	186	189	75	46	1.00	2.60	الفرن
		37	30-28			الاسمي (مللي بار)		معدلات ضغط الإمداد
		25	20			الحد الأدنى (مللي بار)		
		45	35			الحد الأقصى (مللي بار)		

\* عند 15°م و 1013,25 مللي بار- غاز جاف

\*\* بروبان P.C.S. = 50.37 ميغا جول/كجم

\*\*\* بيوتان P.C.S. = 49.47 ميغا جول/كجم

غاز طبيعي P.C.S. = 37.78 ميغا جول/م<sup>3</sup>

مرفق غاز المدينة P.C.S. = 15.87 ميغا جول/م<sup>3</sup>

جزء الغاز	
القدرة الاسمية كيلواط	الفئة
(189 جم/ساعة - G30)	I12H3+
(186 جم/ساعة - G31)	

## SAFETY INSTRUCTIONS

### IMPORTANT TO BE READ AND OBSERVED

⚠ These instructions are valid if the country symbol appears on the appliance. If the symbol does not appear on the appliance, please refer to the technical instructions which will provide the necessary instructions concerning modification of the appliance to the conditions of use of the country.

⚠ CAUTION : Use of the gas cooking appliance results in the production of heat, moisture and products of combustion in the room in which it is installed. Ensure that the kitchen is well ventilated, especially when the appliance is in use: keep natural ventilation holes open or install a mechanical ventilation device (mechanical extractor hood). Prolonged intensive use of the appliance may call for additional ventilation, such as opening a window, or more effective ventilation, for example increasing the level of mechanical ventilation (if possible).

⚠ Failure to follow the information in this manual exactly may cause a fire or explosion, resulting in property damage or personal injury.

Before using the appliance, read these safety instructions. Keep them nearby for future reference.

These instructions and the appliance itself provide important safety warnings, to be observed at all times. The manufacturer declines any liability for failure to observe these safety instructions, for inappropriate use of the appliance or incorrect setting of controls.

⚠ Very young children (0-3 years) should be kept away from the appliance. Young children (3-8 years) should be kept away from the appliance unless continuously supervised. Children from 8 years old and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge can use this appliance only if they are supervised or have been given instructions on safe use and understand the hazards involved. Children must not play with the appliance. Cleaning and user maintenance must not be carried out by children without supervision.

⚠ WARNING: The appliance and its accessible parts become hot during use. Care should be taken to avoid touching heating elements. Children less than 8 years of age must be kept away unless continuously supervised.

⚠ Never leave the appliance unattended during food drying. If the appliance is suitable for probe usage, only use a temperature probe recommended for this oven - risk of fire.

⚠ Keep clothes or other flammable materials away from the appliance, until all the components have cooled down completely - risk of fire. Always be vigilant when cooking foods rich in fat, oil or

when adding alcoholic beverages - risk of fire. Use oven gloves to remove pans and accessories. At the end of cooking, open the door with caution, allowing hot air or steam to escape gradually before accessing the cavity - risk of burns. Do not obstruct hot air vents at the front of the oven - risk of fire.

⚠ Exercise caution when the oven door is in the open or down position, to avoid hitting the door. When you place the rack inside, make sure that the stop is directed upwards and in the back of the cavity.

The device shall not be operated for more 15 s. If after 15s the burner has not lit, stop operating the device and open the compartment door and/or wait at least 1 min before attempting a further ignition of the burner.

### PERMITTED USE

⚠ CAUTION: The appliance is not intended to be operated by means of an external switching device, such as a timer, or separate remote controlled system.

⚠ This appliance is intended to be used in household and similar applications such as: staff kitchen areas in shops, offices and other working environments; farm houses; by clients in hotels, motels, bed & breakfast and other residential environments.

⚠ No other use is permitted (e.g. heating rooms).

⚠ This appliance is not for professional use. Do not use the appliance outdoors.

⚠ Do not store explosive or flammable substances (e.g. gasoline or aerosol cans) inside or near the appliance - risk of fire.

### INSTALLATION

⚠ The appliance must be handled and installed by two or more persons - risk of injury. Use protective gloves to unpack and install - risk of cuts.

⚠ The electrical and gas connections must comply with local regulations.

⚠ Installation, including water supply (if any), electrical connections and repairs must be carried out by a qualified technician. Do not repair or replace any part of the appliance unless specifically stated in the user manual. Keep children away from the installation site. After unpacking the appliance, make sure that it has not been damaged during transport. In the event of problems, contact the dealer or your nearest Aftersales Service. Once installed, packaging waste (plastic, styrofoam parts etc.) must be stored out of reach of children - risk of suffocation. The appliance must be disconnected from the power supply before any installation operation - risk of electric shock. During installation, make sure the appliance does not damage the power cable - risk of fire or electric shock. Only activate the appliance when the installation has been completed.

**⚠ WARNING :** Modification of the appliance and its method of installation are essential in order to use the appliance safely and correctly in all the additional countries

**⚠** Use pressure regulators suitable for the gas pressure indicated in the instructions.

**⚠** The room must be equipped with an air extraction system that expels any combustion fumes.

**⚠** The room must also allow proper air circulation, as air is needed for combustion to occur normally. The flow of air must not be less than 2 m<sup>3</sup>/h per kW of installed power.

**⚠** The air circulation system may take air directly from the outside by means of a pipe with an inner cross section of at least 100 cm<sup>2</sup>; the opening must not be susceptible to blockages.

**⚠** The system can also provide the air needed for combustion indirectly, i.e. from adjacent rooms fitted with air circulation tubes as described above. However, these rooms must not be communal rooms, bedrooms or rooms that may present a fire hazard.

**⚠** Liquid petroleum gas sinks to the floor as it is heavier than air. Therefore, rooms containing LPG cylinders must also be equipped with vents to allow gas to escape in the event of a leak. This means LPG cylinders, whether partially or completely full, must not be installed or stored in rooms or storage areas that are below ground level (cellars, etc.). It is advisable to keep only the cylinder being used in the room, positioned so that it is not subject to heat produced by external sources (ovens, fireplaces, stoves, etc. ) which could raise the temperature of the cylinder above 50°C.

Should you find it difficult to turn the knobs for the burner, please contact the After-sales Service, who can replace of the burner tap if found to be faulty.

The openings use for the ventilation and dispersion of heat must never be covered.

**⚠** Carry out all cabinet cutting works before fitting the appliance in the furniture and remove all wood chips and sawdust.

Do not remove the appliance from its polystyrene foam base until the time of installation.

**⚠** After installation, the bottom of the appliance must no longer be accessible - risk of burn.

**Connection with rigid pipe (copper or steel):**

If the gas pressure is different from the recommended pressure, a suitable pressure regulator must be fitted to the inlet pipe in accordance with the current national regulations.

Use an appropriate cabinet to ensure that the appliance operates properly: To install the oven under the counter (see diagram) or in a kitchen unit, the cabinet must have the dimensions as the picture.

To ensure adequate ventilation, the back panel of the cabinet must be removed. It is advisable

to install the oven so that it rests on two strips of wood, or on a completely flat surface with an opening of at least 45 x 560 mm as the picture.

**⚠** Do not install the appliance behind a decorative door - risk of fire.

**⚠** If the appliance is installed under the worktop, do not obstruct the minimum gap between the worktop and the upper edge of the oven - risk of burns.

### **GAS CONNECTION**

**⚠ WARNING :** Prior to installation, ensure that the local distribution conditions (type of gas and gas pressure) and the configuration of the appliance are compatible.

**⚠** Check that the pressure of the gas supply is consistent with the values indicated in Table 1 ("Burner and nozzle specifications").

**⚠ WARNING :** The configuration conditions of this appliance are stated on the label (or data plate).

**⚠ WARNING :** This appliance is not connected to a combustion products evacuation device. It must be installed and connected in accordance with current installation regulations. Particular attention must be paid to the relevant requirements regarding ventilation.

**⚠** If the appliance is connected to liquid gas, the regulation screw must be fastened as tightly as possible.

**⚠ IMPORTANT :** When the gas cylinder or gas container is installed, it must be properly settled (vertical orientation).

**⚠ WARNING :** This operation must be performed by a qualified technician

**⚠** Use only flexible or rigid metal hose for gas connection.

**⚠** Connection with a rigid pipe (copper or steel)  
Connection to the gas system must be carried out in such a way as not to place any strain of any kind on the appliance. There is an adjustable L-shaped pipe fitting on the appliance supply ramp and this is fitted with a seal in order to prevent leaks. The seal must always be replaced after rotating the pipe fitting (the seal is provided with the appliance). The gas supply pipe fitting is a threaded 1/2 gas cylindrical male attachment.

**⚠** Connecting a flexible jointless stainless steel pipe to a threaded attachment

The gas supply pipe fitting is a threaded 1/2 gas cylindrical male attachment. These pipes must be installed so that they are never longer than 2000 mm when fully extended. Once connection has been made, make sure that the flexible metal pipe does not touch any moving parts and is not compressed. Only use pipes and seals that comply with current national regulations.

**⚠ IMPORTANT :** If a stainless steel hose is used, it must be installed so as not touch any moving

part of the furniture (e.g.drawer). It must pass through an area where there are no obstructions and where it is possible to inspect it across its entire length.

⚠ The appliance should be connected to the main gas supply or to a gas cylinder in compliance with the current national regulations. Before making the connection, make sure that the appliance is compatible with the gas supply you wish to use. If it is not, follow the instructions indicated in the paragraph "Adapting to different types of gas".

⚠ After connection to the gas supply, check for leaks with soapy water. Light up the burners and turn the knobs from max position 1\* to minimum position 2\* to check flame stability.

⚠ Connection to the gas network or the gas cylinder may be carryout using a flexible rubber or steel hose, in accordance with current national legislation.

### ADAPTING TO DIFFERENT TYPES OF GAS

(This operation needs to be carried out by a qualified technician.)


⚠ In order to adapt the appliance to a type of gas other than the type for which it was manufactured (indicated on the rating label), follow the dedicated steps provided after installation drawings.

#### Adapting to different types of gas


To adapt the oven to a type of gas other than the type for which it was manufactured (indicated on the label), follow these simple steps:

#### Replacing the oven burner nozzle


1. Open the oven door fully.
2. Slide out the bottom of the oven.



3. Unscrew the burner fastening screws.
4. Remove screw "V" and then the oven burner



5. Unscrew the oven burner nozzle using the special socket spanner for the nozzles, or better still a 7 mm socket spanner, and replace it with a nozzle suited to the new type of gas (see Table 1).



6. Replace all the parts, following the steps described above in the reverse order.

Take care to replace also the bottom of the oven in its original position.

### ELECTRICAL WARNINGS

⚠ **IMPORTANT:** Information about current and voltage consumption is provided on the rating plate.

⚠ The rating plate is on the front edge of the oven (visible when the door is open).

⚠ It must be possible to disconnect the appliance from the power supply by unplugging it if plug is accessible, or by a multi-pole switch installed upstream of the socket in accordance with the wiring rules and the appliance must be earthed in conformity with national electrical safety standards.

⚠ The power cable must be long enough to connect the appliance, once fitted in its housing, to the main power supply. Do not pull the power supply cable.

⚠ Do not use extension leads, multiple sockets or adapters. The electrical components must not be accessible to the user after installation. Do not use the appliance when you are wet or barefoot. Do not operate this appliance if it has a damaged power cable or plug, if it is not working properly, or if it has been damaged or dropped.

⚠ If the supply cord is damaged, it must be replaced with an identical one by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard - risk of electric shock.

⚠ If the power cable needs to be replaced, contact an authorized service center.

### CLEANING AND MAINTENANCE

⚠ **WARNING:** Ensure that the appliance is switched off and disconnected from the power supply before performing any maintenance operation; never use steam cleaning equipment - risk of electric shock.

⚠ Do not use harsh abrasive cleaners or metal scrapers to clean the door glass since they can scratch the surface, which may result in shattering of the glass.

⚠ Make sure the appliance has cooled down before cleaning or performing maintenance. - risk of burns.


⚠ **WARNING:** Switch off the appliance before replacing the lamp - risk of electric shock.

⚠ To avoid damaging the electric ignition device, do not use it when the burners are not in their housing.


---

Wear protective gloves for cleaning and maintenance.

### **DISPOSAL OF PACKAGING MATERIALS**

The packaging material is 100% recyclable and is marked with the recycle symbol . The various parts of the packaging must therefore be disposed of responsibly and in full compliance with local authority regulations governing waste disposal.

### **DISPOSAL OF HOUSEHOLD APPLIANCES**

This appliance is manufactured with recyclable or reusable materials. Dispose of it in accordance with local waste disposal regulations. For further information on the treatment, recovery and recycling of household electrical appliances, contact your local authority, the collection service for household waste or the store where you purchased the appliance. This appliance is marked in compliance with European Directive 2012/19/EU, Waste Electrical and Electronic Equipment (WEEE). By ensuring this product is disposed of correctly, you will help prevent negative consequences for the environment and human health. The symbol  on the product or on the accompanying documentation indicates that it should not be treated as domestic waste but must be taken to an appropriate collection centre for the recycling of electrical and electronic equipment.

### **ENERGY SAVING TIPS**

Only preheat the oven if specified in the cooking table or your recipe. Use dark lacquered or enamelled baking trays as they absorb heat better. Food requiring prolonged cooking will continue to cook even once the oven is switched off.

### **DECLARATION OF CONFORMITY**

This appliance meets Ecodesign requirements of European Regulation 65/2014 in compliance with the European standard EN 15181.



Whirlpool EMEA S.p.A.  
Via Carlo Pisacane n. 1  
20016 Pero (Mi), Italia



400010881884