

ADMC 1918/IX

12NC/Fx: 857781043000

GTIN (EAN) code: 8003437219993

DIMENSION	MEAS	MEASUR	
OVERALL CABINET			
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	870	mm	
MIN Height of the base cabinet niche, including all required space for installation or ventilation	870	mm	
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	872	mm	
MAX Height of the base cabinet niche, including all required space for installation or ventilation	870	mm	
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	562	mm	
MIN Width of the base cabinet niche, including all required space for installation or ventilation	562	mm	
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm	
MAX Width of the base cabinet niche, including all required space for installation or ventilation	562	mm	
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mn	
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550	mn	
Space in front, which is required to install bottom trim	10	mn	
Indicates whether a ventilation opening is needed or not. Default is "N"	-		
WALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-		
Minimum space or inbound ventilation (wall cabinet)	0	mn	
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm	
WALL CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-		
Minimum space or outbound ventilation (wall cabinet)	0	mn	
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm	
TALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-		
Minimum space for inbound ventilation (tall cabinet)	50	mn	
Minimum area for inbound ventilation cavity (tall cabinet)	281	cm	
TALL CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-		
Minimum space for outbound ventilation (tall cabinet)	50	mn	
Minimum area for outbound ventilation cavity (tall cabinet)	281	cm	
BASE CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (base cabinet)	-		
Minimum space for inbound ventilation (base cabinet)	50	mn	
Minimum area for inbound ventilation cavity (base cabinet)	281	cm	
BASE CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (base cabinet)	-		
Minimum space for outbound ventilation (base cabinet)	50	mn	
Minimum area for outbound ventilation cavity (base cabinet)	281	cm	

	IEASURE	
APPLIANCE		
Height of the front	882	mn
Width of the front	595	mn
Depth of the front	25	mn
Maximum depth all protruding elements, e.g. handles, controls	44	mn
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	50	mn
Projection of front in relation to housing of appliance	15	mn
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	3	mn
When product panel is missing, set to 0	115	mn
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	465	mn
Height from bearing area of appliances and lower handle	439	mn
Frontal handle thickness	25	mn
Frontal handle width	495	mn
MIN Height of the product body	867	mr
MAX Height of the product body	867	mr
Width of the product body	561	mr
Depth of the product body	550	mr
Full depth of product excluding protruding interface elements	575	mr
-	-	mr
	-	mn
-	-	mn
	-	mr
	-	mr
	_	mr
MIN depth between plinth return and front	0	mr
MAX depth between plinth return and front	0	mr
Height MIN Plinth return. This dimension is taken by minimum appliance height	0	mr
Height MAX Plinth return. This dimension is taken at maximum appliance height	0	mr
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	-	
Appliance Flap door		
Projection of the opened flap in relation to bearing area	5	mr
Maximum angle when flap door is opened totally	89	mr
Appliance Side swing door	00	
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mr
Lateral projection of opened front at the side where the hinge is fixed	0	mn
Maximum angle when door is opened totally	0	mr
Appliance other	0	
	65	mr
Depth from front end of the niche to the front end of the freespace of the retrace		