


PSLCSE 65F AS X

12NC: F103827

GTIN (EAN) code: 5054645038275

Hotpoint



MAIN FEATURES

Product group	Hood
Colour body	Inox
Material body	Metal
Colour chimney	N/A
Material chimney	N/A
Typology	Built-in/Built-under
Installation type	Free-standing
Type of control	N/A
Type of control settings	-
Decor panel options	Possible and included
Motor location	Integrated motor in hood body
Operating Mode	Convertible
Electrical connection rating (W)	133
Current (A)	0,94
Voltage (V)	220-240
Frequency (Hz)	50/60
Length of Electrical Supply Cord (cm)	150
Plug type	No
Chimney height (mm)	0
Height of product, without chimney (mm)	0
Height of the product	130
Width of the product	599
Depth of the product	515
Minimum niche height	0
Minimum niche width	0
Niche depth	0
Net weight (kg)	5.2

TECHNICAL FEATURES

Type of manual control devices	N/A
Type of automatic control devices	-
Number of motors	1
Total power of the motors (W)	105
Number of speed settings: boost option availability	3
Boost presence	No
Maximum output air extraction (m ³ /h)	175
Boost position air extraction (m ³ /h)	0
Maximum output recirculating air (m ³ /h)	95
Boost position output recirculating (m ³ /h)	0
Light Control Type	On/Off
Number of lights	1
Type of lamps used	Halogen
Total power of the lamps (W)	28
Diameter of air outlet (mm)	120
No-return airflow flap	No
Grease filter material	Not washable synthetic
Odour filter	Yes

PERFORMANCES

Sound power at min. speed (2010/30/EU)	62
Sound power at max. speed (2010/30/EU)	69
Noise level with boost position (dB(A) re 1 pW)	0