



| DIMENSION  | MEASURE      |    |
|--|--------------|----|
| <b>APPLIANCE</b>   |              |    |
| Product width  | 860          | mm |
| Product depth  | 510          | mm |
| Radius of product corner   | 5            | mm |
| Product height (MAX protrusion from the worktop)                           | 60           | mm |
| Underneath the bearing area of the appliance                               | 40           | mm |
| Distance between cut out and top frontal projection                        | 12           | mm |
| Distance between cut out and top lateral projection                        | 10           | mm |
| Plateau thickness  | 10           | mm |
| Gas outlet positioning   | Rear right   |    |
| Gas outlet X positioning   | 35           | mm |
| Gas outlet Y positioning   | 38           | mm |
| Power cable  | With product |    |
| Power cable positioning  | Rear         |    |
| <b>CUT OUT</b>   |              |    |
| MIN front distance from cut-out to end worktop                             | 0            | mm |
| MIN rear distance from cut out to wall/furniture                           | 55           | mm |
| MIN lateral distance from cut out to wall/furniture                        | 110          | mm |
| MIN height from worktop to above furniture                                 | 530          | mm |
| MIN cut out width  | 837          | mm |
| MAX cut out width  | 839          | mm |
| MIN cut out depth  | 486          | mm |
| MAX cut out depth  | 488          | mm |
| MIN cut out radius   | 6.5          | mm |
| MAX cut out radius   | 8            | mm |
| <b>FLUSH INSTALLATION</b>  |              |    |
| Indicates whether a flush installation is possible. Default is "N"         | Yes          |    |
| MIN Milling rabbet width   | 863          | mm |
| MAX Milling rabbet width   | 865          | mm |
| MIN Milling rabbet depth   | 513          | mm |
| MAX Milling rabbet depth   | 515          | mm |
| Milling rabbet thickness   | 12           | mm |
| Radius milling rabbet  | 6.5          | mm |
| Flush installation KIT (2)   | N/A          |    |
| Indicates the minum worktop thickness with standard installation for gas   | 20           | mm |
| Indicates the maximum worktop thickness with standard installation for gas | 60           | mm |
| Indicates the minum worktop thickness with flush installation for gas      | 30           | mm |
| Indicates the maximum worktop thickness with flush installation for gas    | 68           | mm |
| <b>WITH OVEN</b>   |              |    |
| Indicates whether the cooktop can be installed above oven. Default is "Y"  | Yes          |    |
| MIN worktop thickness with oven  | 0            | mm |
| MAX worktop thickness with oven  | 0            | mm |

| DIMENSION   | MEASURE      |                 |
|---|--------------|-----------------|
| Indicates whether a protection tray against heat or contact is needed with oven. Default is "N"                     | No           |                 |
| Indicates whether a ventilation opening in the back side of cabinet is needed or not with oven. Default is "Y"      | No           |                 |
| Indicates the position of the opening in the back side of the cabinet with oven                                     | N/A          |                 |
| MIN Width of rear opening required with oven  | 0            | mm              |
| MIN Depth of rear opening required with oven.   | 0            | mm              |
| MIN AREA of rear opening required with oven   | 0            | cm <sup>2</sup> |
| MIN distance from cabinet to rear wall, with oven   | 0            | mm              |
| Indicates whether a ventilation opening in the top front side of cabinet is needed or not with oven. Default is "N" | No           |                 |
| MIN Frontal gap required, with oven (2)   | 0            | mm              |
| MIN frontal opening area required with oven   | 0            | cm <sup>2</sup> |
| <b>WITH CABINET</b>   |              |                 |
| MIN worktop thickness with cabinet  | 0            | mm              |
| MAX worktop thickness with cabinet  | 0            | mm              |
| Indicates whether a protection tray against heat or contact is needed. Default is "Y"                               | Yes          |                 |
| MIN distance from bottom line of appliance to protection tray   | 20           | mm              |
| Indicates whether a ventilation opening in the tray is needed or not with cabinet                                   | No           |                 |
| Recess dimension X  | 0            | mm              |
| Recess dimension Y  | 0            | mm              |
| Positioning dimension X by axis   | 0            | mm              |
| Distance of the tray from the back panel/wall   | 0            | mm              |
| Indicates whether a divider is available  | N/A          |                 |
| Indicates whether a ventilation opening in the back side of cabinet is needed or not. Default is "Y"                | No           |                 |
| Indicates the position of the opening in the back side of the cabinet.  | N/A          |                 |
| MIN Width of rear opening of the cabinet  | 0            | mm              |
| MIN Depth of rear opening of the cabinet  | 0            | mm              |
| MIN AREA of rear opening of the cabinet   | 0            | cm <sup>2</sup> |
| MIN distance from cabinet to rear wall  | 0            | mm              |
| Indicates whether a ventilation opening in the top front side of cabinet is needed or not. Default is "N"           | No           |                 |
| MIN Frontal gap of the cabinet  | 0            | mm              |
| MIN frontal opening area of the cabinet   | 0            | cm <sup>2</sup> |
| <b>INSTALLATION SPACE</b>   |              |                 |
| Depth of immersion underneath the appliance   | 9            | mm              |
| Width protruding area below bottom box  | 95           | mm              |
| Depth protruding area below bottom box  | 78           | mm              |
| Protruding area: X positioning  | 3            | mm              |
| Protruding area: Y positioning  | 14           | mm              |
| <b>ACCESSORIES FOR INSTALLATION</b>   |              |                 |
| Gasket  | Separate KIT |                 |
| Clips   | Separate     |                 |

**DIMENSION****MEASURE**

|   |                 |    |
|---|-----------------|----|
|   | KIT             |    |
| Injector KIT                                    | Separate<br>KIT |    |
| Elbow KIT                                       | N/A             |    |
| <b>COOKTOP HOOD INSTALLATION ONLY FOR GAS</b>   |                 |    |
| MIN distance from cooktop to above furniture    | 700             | mm |
| MIN distance between cabinets above the cooktop | 600             | mm |
| MAX distance between cabinets above the cooktop | 750             | mm |