

IGESM 53 G3

12NC/Fx: F158786

GTIN (EAN) code: 8050147587867

DIMENSION		MEASUR	
OVERALL CABINET			
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	590	mm	
MIN Height of the base cabinet niche, including all required space for installation or ventilation	592	mm	
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	592	mm	
MAX Height of the base cabinet niche, including all required space for installation or ventilation	600	mm	
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	866	mm	
MIN Width of the base cabinet niche, including all required space for installation or ventilation	866	mm	
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	870	mm	
MAX Width of the base cabinet niche, including all required space for installation or ventilation	870	mm	
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mm	
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550	mn	
Space in front, which is required to install bottom trim	2	mn	
ndicates whether a ventilation opening is needed or not. Default is "N"	Yes		
WALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-		
Minimum space or inbound ventilation (wall cabinet)	0	mn	
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm	
WALL CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-		
Minimum space or outbound ventilation (wall cabinet)	0	mm	
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm	
TALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear		
Minimum space for inbound ventilation (tall cabinet)	35	mn	
Minimum area for inbound ventilation cavity (tall cabinet)	283	cm	
TALL CABINET (vent-shaft outgoing)	200	•	
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Rear		
Minimum space for outbound ventilation (tall cabinet)	35	mm	
Minimum area for outbound ventilation cavity (tall cabinet)	283	cm	
BASE CABINET (vent-shaft incoming)	200	•	
Indicates the position of the freespace for the inbound airflow (base cabinet)	Rear		
Minimum space for inbound ventilation (base cabinet)	35	mm	
Minimum area for inbound ventilation cavity (base cabinet)	283	cm	
BASE CABINET (vent-shaft outgoing)	200		
Indicates the position of the freespace for the outbound airflow (base cabinet)	Rear		
Minimum space for outbound ventilation (base cabinet)	35	mm	
Minimum area for outbound ventilation cavity (base cabinet)	283	cm	
while a real for outbound ventuation cavity (base cabinet)	200	UII	

APPLIANCE		
Height of the front	595	mm
Width of the front	896	mm
Depth of the front	24	mm
Maximum depth all protruding elements, e.g. handles, controls	47	mm
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	152	mm
Projection of front in relation to housing of appliance	18	mm
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	1	mm
When product panel is missing, set to 0	110	mm
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	445	mm
Height from bearing area of appliances and lower handle	452	mm
Frontal handle thickness	30	mm
Frontal handle width	590	mm
MIN Height of the product body	551	mm
MAX Height of the product body	576	mm
Width of the product body	865	mm
Depth of the product body	545	mm
Full depth of product excluding protruding interface elements	569	mm
	-	mm
-	-	mm
	-	mm
-	-	mm
-	-	mm
- · · · · · · · · · · · · · · · · · · ·	-	mm
Appliance can be used as base for other appliances from the same manufacturer. Default is "No	' No	
Appliance Flap door		
Projection of the opened flap in relation to bearing area	0	mm
Maximum angle when flap door is opened totally	87	mm
Appliance Side swing door		
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge i mounted	s 0	mm
Lateral projection of opened front at the side where the hinge is fixed	0	mm
Maximum angle when door is opened totally	0	mm
Appliance other		
Depth from front end of the niche to the front end of the freespace of the retrace	238	mn
Height from niche to bottom end of freespace for the retrace	545	mn