



| DIMENSION | MEASURE | | DIMENSION | MEASURE | |
|--|--------------|----|---|--------------|-----------------|
| APPLIANCE | | | Indicates whether a protection tray against heat or contact is needed with oven. Default is "N" | No | |
| Product width | 730 | mm | Indicates whether a ventilation opening in the back side of cabinet is needed or not with oven. Default is "Y" | No | |
| Product depth | 510 | mm | Indicates the position of the opening in the back side of the cabinet with oven | N/A | |
| Radius of product corner | 6 | mm | MIN Width of rear opening required with oven | 0 | mm |
| Product height (MAX protrusion from the worktop) | 60 | mm | MIN Depth of rear opening required with oven. | 0 | mm |
| Underneath the bearing area of the appliance | 42 | mm | MIN AREA of rear opening required with oven | 0 | cm ² |
| Distance between cut out and top frontal projection | 15 | mm | MIN distance from cabinet to rear wall, with oven | 0 | mm |
| Distance between cut out and top lateral projection | 85 | mm | Indicates whether a ventilation opening in the top front side of cabinet is needed or not with oven. Default is "N" | No | |
| Plateau thickness | 7 | mm | MIN Frontal gap required, with oven (2) | 0 | mm |
| Gas outlet positioning | Rear right | | MIN frontal opening area required with oven | 0 | cm ² |
| Gas outlet X positioning | 112 | mm | WITH CABINET | | |
| Gas outlet Y positioning | 25 | mm | MIN worktop thickness with cabinet | 0 | mm |
| Power cable | With product | | MAX worktop thickness with cabinet | 0 | mm |
| Power cable positioning | Rear | | Indicates whether a protection tray against heat or contact is needed. Default is "Y" | Yes | |
| CUT OUT | | | MIN distance from bottom line of appliance to protection tray | 20 | mm |
| MIN front distance from cut-out to end worktop | 0 | mm | Indicates whether a ventilation opening in the tray is needed or not with cabinet | No | |
| MIN rear distance from cut out to wall/furniture | 55 | mm | Recess dimension X | 0 | mm |
| MIN lateral distance from cut out to wall/furniture | 185 | mm | Recess dimension Y | 0 | mm |
| MIN height from worktop to above furniture | 420 | mm | Positioning dimension X by axis | 0 | mm |
| MIN cut out width | 560 | mm | Distance of the tray from the back panel/wall | 0 | mm |
| MAX cut out width | 562 | mm | Indicates whether a divider is available | N/A | |
| MIN cut out depth | 480 | mm | Indicates whether a ventilation opening in the back side of cabinet is needed or not. Default is "Y" | No | |
| MAX cut out depth | 482 | mm | Indicates the position of the opening in the back side of the cabinet. | N/A | |
| MIN cut out radius | 0 | mm | MIN Width of rear opening of the cabinet | 0 | mm |
| MAX cut out radius | 8 | mm | MIN Depth of rear opening of the cabinet | 0 | mm |
| FLUSH INSTALLATION | | | MIN AREA of rear opening of the cabinet | 0 | cm ² |
| Indicates whether a flush installation is possible. Default is "N" | Yes | | MIN distance from cabinet to rear wall | 0 | mm |
| MIN Milling rabbet width | 733 | mm | Indicates whether a ventilation opening in the top front side of cabinet is needed or not. Default is "N" | No | |
| MAX Milling rabbet width | 735 | mm | MIN Frontal gap of the cabinet | 0 | mm |
| MIN Milling rabbet depth | 513 | mm | MIN frontal opening area of the cabinet | 0 | cm ² |
| MAX Milling rabbet depth | 515 | mm | INSTALLATION SPACE | | |
| Milling rabbet thickness | 12 | mm | Depth of immersion underneath the appliance | 10 | mm |
| Radius milling rabbet | 6.5 | mm | Width protruding area below bottom box | 61 | mm |
| Flush installation KIT (2) | With product | | Depth protruding area below bottom box | 62 | mm |
| Indicates the minum worktop thickness with standard installation for gas | 20 | mm | Protruding area: X positioning | 74 | mm |
| Indicates the maximum worktop thickness with standard installation for gas | 60 | mm | Protruding area: Y positioning | 9 | mm |
| Indicates the minum worktop thickness with flush installation for gas | 30 | mm | ACCESSORIES FOR INSTALLATION | | |
| Indicates the maximum worktop thickness with flush installation for gas | 68 | mm | Gasket | Separate KIT | |
| WITH OVEN | | | Clips | Separate | |
| Indicates whether the cooktop can be installed above oven. Default is "Y" | Yes | | | | |
| MIN worktop thickness with oven | 0 | mm | | | |
| MAX worktop thickness with oven | 0 | mm | | | |

DIMENSION**MEASURE**

| | | |
|---|-----------------|----|
| | KIT | |
| Injector KIT | Separate KIT | |
| Elbow KIT | N/A | |
| COOKTOP HOOD INSTALLATION ONLY FOR GAS | | |
| MIN distance from cooktop to above furniture | 700 | mm |
| MIN distance between cabinets above the cooktop | 600 | mm |
| MAX distance between cabinets above the cooktop | 750 | mm |