
## WHFG 63 F LE X

12NC: 859991550490

GTIN (EAN) code: 8003437233838







- Maximum noise level 67 dBA
- Noise Level (min. max.): 29-67 dBA
- Air Flow (min. max.): 115, 580, booster 680 m3/h
- Maximum extraction rate: 580 (m3/h)
- Energy class B
- 3 speed settings
- Odour Filter
- 2 LED, 5 W lamps
- 1 x 250 W motor
- Electronic Buttons
- 1 Washable aluminium filter
- Inox and Glass Hood
- Grease Filtering Efficiency Class: D
- Lighting Efficiency Class: A
- Fluid Dynamic Efficiency Class: B
- Filter Saturation Indicator
- Operating Mode: Air extraction, Recirculating air

# Whirlpool wall mounted cooker hood - WHFG 63 F LE X

This Whirlpool wall mounted Cooker Hood features: dishwasher-safe, washable aluminium grease filters. LED lights for ideal lighting. An outstanding cooker extractor fan, ensuring a fresh, grease-free cooking environment. Less than 60cm wide appliance. New design ensuring extra silent performance.



### **LED lighting**

Increased energy and cost efficiency. The LED lighting system lasts 10 times longer than traditional bulbs and uses 90% less energy.



## **Electronic control**

Effortless control. This Whirlpool Hood includes an intuitive electronic user interface, designed to provide you with the simplest, most satisfying user experience ever.



## **Carbon Filter Included**

Enjoy fresh air in your kitchen, always. This Whirlpool Hood includes a carbon purifying air filter, that effectively protects your kitchen from odours and grease.



## 3 Speeds

Versatile performance. This Whirlpool Hood offers 3 speed options, giving you complete control over the extraction rate.



## Wall-mounted installation

Wall-mounted installation. This wall-mounted Whirlpool Hood is a breeze to install.



## Total annual energy consumption

Ideal performance, outstanding savings. Whirlpool Hoods are designed to provide exceptional results, while reducing energy costs.



## **Flexible Installation**

Flexible installation options. This Whirlpool Hood can be operated in either Ducted or Recirculated mode (filter needed), so you can enjoy complete freedom when designing your kitchen.



#### **Grease Filter**

Odour-free cooking. This Whirlpool Hood features an efficient grease filter, that protects your kitchen surfaces and ensures pleasant, odour-free cooking.



## **TIMER**

Perfect timing. This Whirlpool Hood includes an intuitive timer, for added convenience.



## Glass design

Designed to delight. Modern, sleek and beautiful, this glass hood is designed to be an eye-catching addition to your home.

# WHFG 63 F LE X

12NC: 859991550490

GTIN (EAN) code: 8003437233838



MAIN FEATURES		
Product group	Hood	
Colour body	Inox	
Material body	Stainless steel / glass	
Colour chimney	Inox	
Material chimney	N/A	
Typology	Wall-mounted	
Installation type	Wall-mounted	
Type of control	Electronic	
Type of control settings	-	
Decor panel options	N/A	
Motor location	Integrated motor in hood chimney	
Operating Mode	Convertible	
Electrical connection rating (W)	255	
Current (A)	0	
Voltage (V)	220-240	
Frequency (Hz)	50/60	
Length of Electrical Supply Cord (cm)	150	
Plug type	Schuko	
Chimney height (mm)	-	
Height of product, without chimney (mm)	0	
Height of the product	1131	
Width of the product	598	
Depth of the product	450	
Minimum niche height	0	
Minimum niche width	0	
Niche depth	0	
Net weight (kg)	13.1	

TECHNICAL FEATURES		
Type of manual control devices	Buttons	
Type of automatic control devices	-	
Number of motors	1	
Total power of the motors (W)	250	
Number of speed settings: boost option availability	3	
Boost presence	No	
Maximum output air extraction (m³/h)	713	
Boost position air extraction (m³/h)	713	
Maximum output recirculating air (m³/h)	0	
Boost position output recirculating (m³/h)	0	
Light Control Type	On/Off	
Number of lights	2	
Type of lamps used	LED	
Total power of the lamps (W)	5	
Diameter of air outlet (mm)	150	
No-return airflow flap	No	
Grease filter material	Washable aluminium	
Odour filter	Yes	

PERFORMANCES	
Sound power at min. speed (2010/30/EU)	29
Sound power at max. speed (2010/30/EU)	67
Noise level with boost position (dB(A) re 1 pW)	0

