

PRODUCT FICHE HOOD

Trademark	INDESIT
Model identifier	ISLK 66 AS K
Annual Energy Consumption	99,4 kWh/a
Energy Efficiency Class	E
Fluid Dynamic Efficiency	5,2
Fluid Dynamic Efficiency class	F
Lighting efficiency in lux/Watt	3,0 lux/W
Lighting efficiency class	G
Grease filtering efficiency	86,0 %
Grease filtering efficiency class	B
Minimum air flow	95 m ³ /h
Maximum Air flow	208 m ³ /h
Air flow boost	0 m ³ /h
A-weighted sound power at min. speed	48 dB(A)
A-weighted sound power at max. speed	67 dB(A)
A-weighted sound power boost	0 dB(A)
Power consumption in off-mode	0,00 W
Power consumption in standby mode	0,00 W
Time increase factor (f)	1,8
Energy Efficiency Index (EEI_{hood})	104,5
Measured air flow rate at best efficiency point (Q_{BEP})	115,0 m ³ /h
Measured air pressure at best efficiency point (P_{BEP})	145 Pa
Measured electric power input at best efficiency point (W_{BEP})	89,0 W
Nominal power of the lighting system (W_L)	56,0 W
Average illumination of the lighting system on the cooking surface (E_{middle})	168 lux