

## HSFCIH 4798 FS UK

12NC/Fx: F162384

## GTIN (EAN) code: 5054645623846

01Hogin Win Of the base cabinet Niche, including all required space for installation or ventilation (HMN B)0mm03Webh MiN of the base cabinet Niche, including all required space for installation or ventilation (HMAN B)00mm04With MAX of the base cabinet Niche, including all required space for installation or ventilation (MAN B)00mm05Webh MiN of the base cabinet Niche, including all required space for installation or ventilation (MAN B)00mm05Indicates whether a ventilation space for installation or ventilation (MAN B)No0mm05Indicates whether a ventilation space for installation or ventilation (MAN B)NoNo0mm05Indicates whether a ventilation space for installation or ventilation (MAN B)NoNo0mm06Indicates whether a ventilation or develoption of the space for installation or ventilation (MAN B)No	DIMENSION	MEASURE	
02. Heigh MAX of the base caloret Niche, Including all required space for installation or ventilation (WMAN_B)     0     mm       03. Width MIA for the base caloret Niche, Including all required space for installation or ventilation (WMAN_B)     0     0     mm       04. Width MAX of the base caloret Niche, Including all required space for installation or ventilation (WMAN_B)     No     0       05. Depth of the base caloret Niche, Including all required space for installation or ventilation (WMAN_B)     No     0       05. Includies Winther a ventilation or inc. Default is 'N'     No     0       06. Includies Winther a ventilation or inc. Default is 'N'     No     0     mm       08. Heigh MIN Decorative Front (HMF)     0     mm     0     mm       09. Heigh MAX of the decorative born fort panel of the Kitchen manufacturer (WEMF)     0     mm       10. Width MIN Decorative front (MMF)     0     mm       11. Weight MAX of the decorative fort panel of the Kitchen manufacturer (WEMF)     0     mm       12. Weight MIN Decorative front panel of the Kitchen manufacturer (WEMF)     0     mm       13. The canore and the decorative font panel of the Kitchen manufacturer (WEMF)     0     mm       14. Minitrum height dago betweight dago b	OVERALL CABINET		
03. Wdth MIN of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B)     0     mm       04. Wdth MAX of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B)     0     mm       05. Dept of the base cabinet Niche, including all required space for installation or ventilation (VMAN_B)     0     mm       05. Incluses whether a ventilation poening is needed or not. Default is "N"     No     No       07. appliance can be used as base for other appliances from the same manufacturer (VEMAF)     0     mm       08. Height MIN Decorative Front (HMF)     0     mm       09. Height MAX decorative front (MMF)     0     mm       10. Width MIN Decorative Front (MMF)     0     mm       11. Weight MAX of decorative front panel of the Kitchen manufacturer (WEMF)     0     mm       12. Weight MAX of decorative front panel of the Kitchen manufacturer (WEMF)     0     mm       13. Tincheres MAX of decorative front panel of the Kitchen manufacturer (WEMF)     0     mm       14. Minnum height of gap between front and front underneeth, with MAX thickness of front (HMFG)     0     mm       14. Minnum height of gap between front and front underneeth, with MAX thickness of front (HMFG)     0     mm       05. Dept MAX product (HMP)     0     mm     0     mm       05. Dept MAX of polith return front (DMFRF)     0     mm       05. Dept MAX	01. Height MIN of the base cabinet Niche, including all required space for installation or ventilation (HMIN_B)	0	mm
04 Widt MXX of the base cabinet Niche, including all required space for installation or venillation (VMAA_B)     0     mm       05 Depth of the base cabinet Niche, including all required space for installation (ON_B)     0     mm       05 Indicates whether a ventilation opening is needed or not. Default is "N     No     No       07. appliance can be used as base for other appliances from the same manufacturer. Default is "N     No     No       08. Height MIX Decorative Front (HMF)     0     mm       09. Height MXD decorative Front (HMF)     0     mm       09. Height MXD decorative Front (HMF)     0     mm       10. Width MIN Decorative Front (HMF)     0     mm       10. Width MIN Decorative Front (HMF)     0     mm       11. Weight MXA of the decorative borton front panel of the Kitchen manufacturer (WEMAF)     0     mm       11. Weight MXA of decorative front panel of the Kitchen manufacturer (WEMAF)     0     mm       12. Weight MIX of decorative front panel of the Kitchen manufacturer (WEMAF)     0     mm       13. Thickness MAX of decorative front panel of the Kitchen manufacturer (WEMAF)     0     mm       21. Weight MIX of decorative front panel of the Kitchen manufacturer (WEMAF)     0     mm       22. Weight MIN product (MMP)     0     mm     mm       21. Height MIX product (MAP)     0     mm       21. Height MIN product (MP)     So	02. Height MAX of the base cabinet Niche, including all required space for installation or ventilation (HMAN_B)	0	mm
95. Depth of the base cabine Niche, including all required space for installation or ventilation (OV,B)     0     0     0       05. Indects which are ventilation opening is needed or not. Default is "N"     No     1       06. Indects which are ventilation opening is needed or not. Default is "N"     No     1       07. appliance can be used as base for other appliances from the same manufacturer. Default is "N"     No     1       08. Height MIX Decorative Forn (HMF)     0     nm       09. Height MAX Decorative Forn (HMF)     0     nm       10. Word MIX Decorative Forn (HMF)     0     nm       10. Word MIX Decorative Forn (HMF)     0     nm       11. Weight MIN of the decorative forn tip anel of the Kitchen manufacturer (WEMF)     0     nm       13. Thickness MAX of decorative forn tip anel of the Kitchen manufacturer (MEMF)     0     nm       14. Minimum height of gas between front and front underteath, with MAX thickness of front (HMF)     0     nm       10. Height MIX Product (HMAP)     6     nm     nm       10. Height MIX Product (HMAP)     6     nm       10. Height MIN Product (HMAP)     6     nm       10. Height MIX Product (MAP)     6     nm	03. Width MIN of the base cabinet Niche, including all required space for installation or ventilation (WMIN_B)	0	mm
06     Indicates whether a venilation opening is needed or not. Default is "N"     No       07. appliance can be used as base for other appliances from the same manufacturer. Default is "N"     No       08. Height MIX Decorative Ford (HMF)     0     nm       09. Height MIX Decorative Ford (HMF)     0     nm       10. Width MIN Decorative Ford (HMF)     0     nm       10. Width MIX Decorative Ford (HMF)     0     mm       11. Weight MIX of the decorative ford panel of the Kitchen manufacturer (WEMF)     0     mm       12. Weight MIX of the decorative ford panel of the Kitchen manufacturer (WEMF)     0     mm       13. Thickness MAX of decorative ford panel of the Kitchen manufacturer (MEMF)     0     mm       4PLIANCE     0     mm       02. Height MIX product (HMIP)     850     mm       03. Hindry fould the Max product (HMIP)     450     mm       04. Depth product without fond (DP)     450     mm       05. Depth product (MMP)     450     mm       06. Depth product without fond (DP)     450     mm       06. Depth product without fond (DP)     450     mm       07. Depth MAX of plint return fond (DMIPRF)     0     mm       09. Height MIX A plint return fond (DMIPRF)     0     mm       09. Height MIX A plint return fond (DMIPRF)     0     mm       09. Height MIX	04.Width MAX of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B)	0	mm
97. appliance can be used as base for other appliances from the same manufacturer. Default is "N"     No     No       Built In Floor Standing     0     nm       03. Height MIN Decorative Front (HMIF)     0     nm       03. Height MIN Decorative Front (HMIF)     0     nm       10. Width MIN Decorative Front (HMIF)     0     nm       10. Width MIN Decorative Fort (MMF)     0     No       10. Width MIN Decorative fort (MMF)     0     No       11. Weight MIX of the decorative bottom fort panel of the kitchen manufacturer (WEMF)     0     No       12. Weight MIX of the decorative fort panel of the kitchen manufacturer (WEMF)     0     No       13. Thickness MAX of decorative fort applie of the kitchen manufacturer (WEMF)     0     No       14. Minimum height of gap between fort and front underneath, with MAX thickness of front (HMIFG)     0     No       20. Height MIX product (HMAP)     850     nm       21. Height MIX product (HMAP)     850     nm       23. Widht product (WHAP)     850     nm       34. Widht product (MMAP)     850     nm       35. Weight MAX of printer turn front (DMIPRF)     0     nm       36. Depth MIX of printer turn front (DMIPRF)     0     nm       36. Height MIX Product Panel. When product panel is missing, set to (HMIMPR)     0     nm       36. Height MIX Product Panel.	05. Depth of the base cabinet Niche, including all required space for installation or ventilation (DN_B)	0	mm
Built or Floor Standing         Instrume           08. Height MIN Decorative Front (MMF)         0.0         mm           09. Height MIX Decorative Front (MMF)         0.0         mm           10. Width MIX Decorative Front (MMF)         0.0         mm           10. Width MIX Decorative Front (MMF)         0.0         mm           11. Weight MIX of the decorative totan total pail of the Kitchen manufacturer (WEMF)         0.0         mm           12. Weight MIX of the decorative front panel of the Kitchen manufacturer (MEMF)         0.0         mm           13. Thickness MAX of decorative front panel of the Kitchen manufacturer (MEMF)         0.0         mm           14. Huinnum height of gap betwein tont and front underneative. (WEMF)         0.0         mm           02. Height MIX Product (MMP)         800         mm           03. Hold product (MMP)         800         mm           04. Height MIX product (MMP)         800         mm           03. Widh product (MMP)         800         mm           04. Depth product (MMP)         800         mm           05. Depth product (MMP)         900         mm           05. Depth product (MMP)         900         mm           05. Depth product (MMP)         900         mm           05. Depth product (MMP)	06. Indicates whether a ventilation opening is needed or not. Default is "N"	No	
08. Height MIN Decorative Front (HMIF)     0     mm       09. Height MAX Decorative Front (HMAF)     0     mm       10. Width MIN Decorative Front (WMF)     0     mm       11. Weight MAX of the decorative bottom front panel of the kitchen manufacturer (WEMF)     0     kg       12. Weight MIN of the decorative front panel of the kitchen manufacturer (WEMF)     0     mm       13. Thickness MAX of decorative front panel of the kitchen manufacturers (TMAF)     0     mm       14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG)     0     mm       14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG)     850     mm       01. Height MIN Product (HMIP)     850     mm       02. Height MAX product (MMP)     850     mm       03. With product (MMP)     850     mm       04. Depth product (MMP)     850     mm       05. Depth In ort (IMAPF)     9     mm       05. Depth MIN or plint return front (DMIPF)     0     mm       06. Depth MIN Product (MIPF)     0     mm       07. Depth MAX or plint return front (DMAPF)     0     mm       08. Height MAX Product Densities is aken by minimum appliance height (HMIMPR)     0     mm       09. Height MAX Product Panel. When product panel is missing, set to (HMIPP)     0     mm       <	07. appliance can be used as base for other appliances from the same manufacturer. Default is "N"	No	
98. Height MAX Decorative Front (MMF)     0     mm       10. Widht MAX of the decorative Front panel of the Kitchen manufacturer (WEMAF)     0     mm       11. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)     0     mm       12. Weight MAX of the decorative front panel of the Kitchen manufacturer (WEMAF)     0     mm       13. Thickness MAX of decorative front panel of the kitchen manufacturer (MEMF)     0     mm       APPLANCE     0     mm       Overall Appliance     850     mm       01. Height MAX product (HMP)     850     mm       02. Height MAX product (HMP)     850     mm       03. Widh product (WP)     850     mm       04. Depth product (WP)     850     mm       05. Depth MAX of plinth return front (DMRFF)     0     mm       06. Depth MAX of plinth return front (DMRFF)     0     mm       07. Depth MAX of plinth return front (DMRFF)     0     mm       08. Height MAX Product Planel withinum appliance height (HMIMPR)     0     mm       09. Height MAX Product Planel withinum appliance height (HMIMPR)     0     mm       09. Height MAX Product Panel. When product panel is missing, set to (HMIMPR)     mm     mm       09. Height MAX Product Panel. When product panel is missing, set to (HMIMPR)     mm     mm       11. Height MAX Product Panel. When produ	Built In - Floor Standing		
10. Width MIN Decorative Front (WMIF)     0     mm       11. Weigh MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMIF)     0     kg       12. Weigh MIN of the decorative front panel of the Kitchen manufacturer (WEMIF)     0     mm       13. Thickness MAX of decorative front panel of the Kitchen manufacturers (TMAF)     0     mm       14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG)     0     mm       20. Height MAX product (HMP)     0     mm       01. Height MIN Product (HMAP)     850     mm       02. Height MAX product (HMAP)     850     mm       03. Width product (HMAP)     850     mm       04. Depth product (HMAP)     6     mm       05. Depth product (MIN (DNIFF)     0     mm       06. Depth product (WIN (DNIFF)     0     mm       07. Depth MAX of plinth return front (DMIPRF)     0     mm       08. Height MIX of plinth return front (DMIPRF)     0     mm       09. Height MAX of plinth return front (DMIPRF)     0     mm       11. Height MAX Product Panel. When product panel is missing, set to 0 (HMIPR)     0     mm       12. Height MIX Product Panel. When product panel is missing, set to 0 (HMIPR)     0     mm       13. Height MAX Product Panel. When product panel is missing, set to 0 (HMIPP)     mm     mm       13	08. Height MIN Decorative Front (HMIF)	0	mm
11. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)     0     kg       12. Weight MIN of the decorative front panel of the Kitchen manufacturer (WEMF)     0     mm       13. Thickness MAX of decorative front panel of the Kitchen manufacturer (WEMF)     0     mm       14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG)     0     mm       APPLIACE     0     mm       Overall Appliance     850     mm       01. Height MIN Product (HMIP)     850     mm       03. With product (HMAP)     850     mm       04. Depth product (MP)     850     mm       05. Depth product (MP)     598     mm       06. Depth MIN of pintn return front (DMIPRF)     0     mm       07. Depth MAX of pintn return front (DMIPRF)     0     mm       08. Height MIN X pintneturn front (DMIPRF)     0     mm       09. Height MAX Product Panel. When product panel is missing, set to (HMIPR)     0     mm       13. Height MAX Product Panel. When product panel is missing, set to (HMAPP)     0     mm       14. Space in front, with is required to guarantee full operability. The most protuding part gives this dimension (RSF)     0     mm       14. Height MIN Product Panel. When product panel is missing. set to (HMAPP)     0     mm       15. Type of prearation to fix the caver door     No dri	09. Height MAX Decorative Front (HMAF)	0	mm
12. Weight MIN of the decorative front panel of the Kitchen manufacturer (WEMIF)       0       mm         13. Thickness MAX of decorative front panel of the kitchen manufacturers (TMAF)       0       mm         14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG)       0       mm         APPLIANCE       0       mm       0       mm         01. Height MIN Product (HMP)       850       mm         02. Height MAX product (HMAP)       850       mm         03. Width product (MAP)       850       mm         03. Width product (MAP)       988       mm         04. Depth product without front (DP)       0       mm         05. Depth product (D)       0       mm         06. Depth MIN of plinth return front (DMIPRF)       0       mm         07. Depth MAX of plinth return. Dimension is taken by minimum appliance height (HMIMPR)       0       mm         08. Height MIN Product Panel. When product panel is missing, set to 0 (HMIPP)       0       mm         14. Height MAX Product Panel. When product panel is missing, set to 0 (HMIPP)       0       mm         14. Space in fort, which is required to guarantee full perability. The most protruding pat types this dimension (RSF)       S7.5       mm         14. Space in fort, which is required to guarantee full perability. The most protruding pat	10. Width MIN Decorative Front (WMIF)	0	mm
13. Thickness MAX of decorative front panel of the kitchen manufacturers (TMAF)       0       mm         14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG)       0       mm         APPLLANCE       0	11. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)	0	kg
14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG)       0       mm         APPLIANCE       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIPR)       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIFG)       Import and front underneath, with MAX thickness of front (HMIPR)       Import and front underneath, with front (DMIPRF)       Import and front underneath, with front (DMIPRF)       Import and front underneath, front (DMIPRF)       Import and front underneath, f	12. Weight MIN of the decorative front panel of the Kitchen manufacturer (WEMIF)	0	kg
APPLIANCE       Include	13. Thickness MAX of decorative front panel of the kitchen manufacturers (TMAF)	0	mm
Overall Appliance       Immediate         01. Height MIN Product (HMIP)       850       mm         02. Height MAX product (HMAP)       850       mm         03. Wicht product (WP)       50       mm         04. Depth product without front (DP)       598       mm         05. Depth product (IMP optimite fromt fort(DMIPRF)       0       mm         06. Depth MIN Priotur front (DMIPRF)       0       mm         07. Depth MAX of plinth return front (DMAPRF)       0       mm         08. Height MIN Priotur fort (DMAPRF)       0       mm         09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMPR)       0       mm         12. Height MIN Product Panel. When product panel is missing, set to 0 (HMAPR)       0       mm         13. Height MAX Product Panel. When product panel si missing, set to 0 (HMAPR)       mm       mm         14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)       State       mm         15. Type of preparation to fix the cover door       Mo drilling template       mm         16. Depth of the socle retrace at the rear side (DBSR)       mm       mm         17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)       Mo       mm         17. He	14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG)	0	mm
01. Height MAX product (HMP)       850       mm         02. Height MAX product (HMAP)       850       mm         03. Width product (WP)       450       mm         04. Depth product without front (DP)       50       mm         05. Depth product without front (DMIPRF)       0       mm         06. Depth MIN of plinth return front (DMAPRF)       0       mm         08. Height MAX Product Parter front (DMAPRF)       0       mm         08. Height MAX Plinth return. Dimension is taken by minimum appliance height (HMIMPR)       0       mm         08. Height MAX Plinth return. Dimension is taken at minimum appliance height (MMAPR)       0       mm         01. Height MAX Product Panel. When product panel is missing, set to 0 (HMIPP)       0       mm         13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)       0       mm         14. Space in fond, which is required to guarantee full operability. The most porturing part gives this dimension (RSF)       S72.5       mm         15. Type of preparation to fix the cover door       No drilling template       mm         16. Depth of the socie retrace at the rear side (DSR)       48       mm         17. Height of the socie retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)       48       mm <td>APPLIANCE</td> <td></td> <td></td>	APPLIANCE		
02. Height MAX product (HMAP)       850       mm         03. Width product (WP)       450       mm         04. Depth product without front (DP)       598       mm         05. Depth product (MIAP F)       0       mm         06. Depth MIN of plinth return front (DMIPRF)       0       mm         07. Depth MAX of plinth return front (DMAPRF)       0       mm         08. Height MIN Plinth return. Dimension is taken by minimum appliance height (HMIMPR)       0       mm         08. Height MIN Plinth return. Dimension is taken at minimum appliance height (HMIMAPR)       0       mm         08. Height MIX Product Panel. When product panel is missing, set to 0 (HMIPP)       0       mm         13. Height MIX Product Panel. When product panel is missing, set to 0 (HMAPP)       0       mm         14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)       57.5       mm         15. Type of preparation to fix the cover door       Mod filling template       mm         16. Depth of the socle retrace at the rear side (DBSR)       48       mm         17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)       10       mm         17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)       10       mm	Overall Appliance		
3. Widh product (WP)       450       mm         04. Depth product without front (DP)       598       mm         05. Depth product (D)       0       mm         06. Depth MIX of plinth return front (DMIPRF)       0       mm         07. Depth MAX of plinth return. fort (DMAPRF)       0       mm         08. Height MIN Plinth return. Dimension is taken by minimum appliance height (HMIMPR)       0       mm         09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMPR)       0       mm         09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMAPR)       0       mm         01. Height MIN Product Panel. When product panel is missing, set to 0 (HMIPP)       0       mm         13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)       0       mm         14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)       57.5       mm         15. Type of preparation to fix the cover door       No drilling template       mm         16. Depth of the socle retrace at the rear side (DBSR)       48       mm         17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)       120       mm         17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height	01. Height MIN Product (HMIP)	850	mm
04. Depth product without front (DP)598mm05. Depth product (D)0mm06. Depth MIN of plinth return front (DMIPRF)0mm07. Depth MAX of plinth return front (DMAPRF)0mm08. Height MIN Plinth return. Dimension is taken by minimum appliance height (HMIMPR)0mm09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMPR)0mm12. Height MIN Product Panel. When product panel is missing, set to 0 (HMAPP)0mm13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)0mm14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)S72.5mm15. Type of preparation to fix the cover doorNo drilling templatemm16. Depth of the socle retrace at the rear side (DBSR)48mm17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)120mm	02. Height MAX product (HMAP)	850	mm
05. Depth product (D)0mm06. Depth MIN of plinth return front (DMIPRF)0mm07. Depth MAX of plinth return front (DMAPRF)0mm08. Height MIN Plinth return. Dimension is taken by minimu appliance height (HMIMPR)0mm09. Height MAX Plinth return. Dimension is taken by minimu appliance height (HMIMPR)0mm09. Height MIN Plinth return. Dimension is taken by minimu appliance height (HMIMPR)0mm12. Height MIN Product Panel. When product panel is missing, set to 0 (HMIPP)0mm13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)0mm14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)52.5mm15. Type of preparation to fix the cover doormmmmmm16. Depth of the socle retrace at the rear side (DBSR)84mm17. Height of the socle retrace at the rear side. Distance in timinum appliance height (HBSR)120mm17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)120mm	03. Width product (WP)	450	mm
06. Depth MIN of plinth return front (DMIPRF)       0       mm         07. Depth MAX of plinth return front (DMAPRF)       0       mm         08. Height MIN Plinth return. Dimension is taken by minimum appliance height (HMIMPR)       0       mm         09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMAPR)       0       mm         Built In - Floor Standing       Imm       Imm         12. Height MIN Product Panel. When product panel is missing, set to 0 (HMAPP)       0       mm         13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)       0       mm         14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)       S72.5       Mo         15. Type of preparation to fix the cover door       Retrace back socle       No drilling template       mm         16. Depth of the socle retrace at the rear side (DBSR)       48       mm         17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)       120       mm	04. Depth product without front (DP)	598	mm
07. Depth MAX of plinth return front (DMAPRF)       0       mm         08. Height MIN Plinth return. Dimension is taken by minimum appliance height (HMIMPR)       0       mm         09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMAPR)       0       mm         Built In - Floor Standing       0       mm         12. Height MIN Product Panel. When product panel is missing, set to 0 (HMAPP)       0       mm         13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)       0       mm         14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)       Not return to mentation to fix the cover door       Not return to mentation to fix the cover door       mm         16. Depth of the socle retrace at the rear side (DBSR)       14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)       Not return to mentation to fix the cover door       Not return to mentation to fix the cover door       Not return to mentation to fix the cover door       Not return to mentation to fix the cover door       Not return to mentation to fix the cover door       Not return to mentation to fix the cover door       Not return to mentation to fix the cover door       Not return to mentation to fix the cover door       Not return to mentation to fix the cover door       Not return to mentation to fix the cover door       Not return to fix the cover door       Not return to fix the cover door	05. Depth product (D)	0	mm
08. Height MIN Plinth return. Dimension is taken by minimum appliance height (HMIMPR)       0       mm         09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMAPR)       0       mm         Built n - Floor Standing       1 <t< td=""><td>06. Depth MIN of plinth return front (DMIPRF)</td><td>0</td><td>mm</td></t<>	06. Depth MIN of plinth return front (DMIPRF)	0	mm
09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMAPR)       0       mm         Built In - Floor Standing       1 <td< td=""><td>07. Depth MAX of plinth return front (DMAPRF)</td><td>0</td><td>mm</td></td<>	07. Depth MAX of plinth return front (DMAPRF)	0	mm
Built In - Floor Standing       Indexted Standing       Indexted Standing         12. Height MIN Product Panel. When product panel is missing, set to 0 (HMIPP)       0       mm         13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)       0       mm         14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)       572.5       mm         15. Type of preparation to fix the cover door       No drilling template       7         Retrace back socle       10       10       10         16. Depth of the socle retrace at the rear side (DBSR)       48       mm         17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)       120       mm         TEMPLATE NAME       120       mm       120	08. Height MIN Plinth return. Dimension is taken by minimum appliance height (HMIMIPR)	0	mm
12. Height MIN Product Panel. When product panel is missing, set to 0 (HMIPP)       0       mm         13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)       0       mm         14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)       572.5       mm         15. Type of preparation to fix the cover door       No drilling template       0       mm         16. Depth of the socle retrace at the rear side (DBSR)       48       mm         17. Height of the socle retrace at the rear side (DBSR)       120       mm         17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)       120       mm         TEMPLATE NAME       Interval       Interval       Interval	09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMAPR)	0	mm
13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)nm14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)572.5mm15. Type of preparation to fix the cover doorNo drilling templatemmRetrace back socle16. Depth of the socle retrace at the rear side (DBSR)48mm17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)120mmTEMPLATE NAME	Built In - Floor Standing		
14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)       572.5       mm         15. Type of preparation to fix the cover door       No drilling template          Retrace back socle       10       10       10         16. Depth of the socle retrace at the rear side (DBSR)       48       mm         17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)       120       mm         TEMPLATE NAME       Imm       Imm       Imm	12. Height MIN Product Panel. When product panel is missing, set to 0 (HMIPP)	0	mm
15. Type of preparation to fix the cover door       No drilling template         Retrace back socle       Image: Complex Co	13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)	0	mm
Retrace back socle     Image: Constraint of the socle retrace at the rear side (DBSR)       16. Depth of the socle retrace at the rear side (DBSR)     48     mm       17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)     120     mm       TEMPLATE NAME     Constraints     Constraints     Constraints	14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)	572.5	mm
16. Depth of the socle retrace at the rear side (DBSR)       48       mm         17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)       120       mm         TEMPLATE NAME       120       120       120       120	15. Type of preparation to fix the cover door	No drilling template	
17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)       120       mm         TEMPLATE NAME       0       0       0	Retrace back socle		
TEMPLATE NAME	16. Depth of the socle retrace at the rear side (DBSR)	48	mm
	17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)	120	mm
00. Name of the template to be used DISH_FREESTANDING45CM	TEMPLATE NAME		
	00. Name of the template to be used	DISH_FREESTANDING4	5CM