

## PRODUCT FICHE HOOD

<b>Trademark</b>	HOTPOINT
<b>Model identifier</b>	PHFG6.5FABX
<b>Annual Energy Consumption</b>	100,1 kWh/a
<b>Energy Efficiency Class</b>	C
<b>Fluid Dynamic Efficiency</b>	20,0
<b>Fluid Dynamic Efficiency class</b>	C
<b>Lighting efficiency in lux/Watt</b>	9,0 lux/W
<b>Lighting efficiency class</b>	E
<b>Grease filtering efficiency</b>	66,0 %
<b>Grease filtering efficiency class</b>	D
<b>Minimum air flow</b>	240 m <sup>3</sup> /h
<b>Maximum Air flow</b>	496 m <sup>3</sup> /h
<b>Air flow boost</b>	559 m <sup>3</sup> /h
<b>A-weighted sound power at min. speed</b>	46 dB(A)
<b>A-weighted sound power at max. speed</b>	63 dB(A)
<b>A-weighted sound power boost</b>	67 dB(A)
<b>Power consumption in off-mode</b>	0,00 W
<b>Power consumption in standby mode</b>	0,49 W
<b>Time increase factor (f)</b>	1,3
<b>Energy Efficiency Index (EEI<sub>hood</sub>)</b>	83,8
<b>Measured air flow rate at best efficiency point (Q<sub>BEP</sub>)</b>	288,0 m <sup>3</sup> /h
<b>Measured air pressure at best efficiency point (P<sub>BEP</sub>)</b>	374 Pa
<b>Measured electric power input at best efficiency point (W<sub>BEP</sub>)</b>	149,5 W
<b>Nominal power of the lighting system (W<sub>L</sub>)</b>	40,0 W
<b>Average illumination of the lighting system on the cooking surface (E<sub>middle</sub>)</b>	360 lux