



DIMENSION			MEASURE			DIMENSION			MEASURE		
APPLIANCE						Indicates whether a protection tray against heat or contact is needed with oven. Default is "N"			No		
Product width	730	mm				Indicates whether a ventilation opening in the back side of cabinet is needed or not with oven. Default is "Y"			No		
Product depth	510	mm				Indicates the position of the opening in the back side of the cabinet with oven			N/A		
Radius of product corner	8.5	mm				MIN Width of rear opening required with oven			0	mm	
Product height (MAX protrusion from the worktop)	50	mm				MIN Depth of rear opening required with oven.			0	mm	
Underneath the bearing area of the appliance	42	mm				MIN AREA of rear opening required with oven			0	cm ²	
Distance between cut out and top frontal projection	10	mm				MIN distance from cabinet to rear wall, with oven			0	mm	
Distance between cut out and top lateral projection	85	mm				Indicates whether a ventilation opening in the top front side of cabinet is needed or not with oven. Default is "N"			No		
Plateau thickness	7	mm				MIN Frontal gap required, with oven (2)			0	mm	
Gas outlet positioning	Rear right					MIN frontal opening area required with oven			0	cm ²	
Gas outlet X positioning	97	mm				WITH CABINET					
Gas outlet Y positioning	38	mm				MIN worktop thickness with cabinet			0	mm	
Power cable	With product					MAX worktop thickness with cabinet			0	mm	
Power cable positioning	Rear					Indicates whether a protection tray against heat or contact is needed. Default is "Y"			Yes		
CUT OUT						MIN distance from bottom line of appliance to protection tray			20	mm	
MIN front distance from cut-out to end worktop	0	mm				Indicates whether a ventilation opening in the tray is needed or not with cabinet			No		
MIN rear distance from cut out to wall/furniture	55	mm				Recess dimension X			0	mm	
MIN lateral distance from cut out to wall/furniture	185	mm				Recess dimension Y			0	mm	
MIN height from worktop to above furniture	420	mm				Positioning dimension X by axis			0	mm	
MIN cut out width	560	mm				Distance of the tray from the back panel/wall			0	mm	
MAX cut out width	562	mm				Indicates whether a divider is available			N/A		
MIN cut out depth	480	mm				Indicates whether a ventilation opening in the back side of cabinet is needed or not. Default is "Y"			No		
MAX cut out depth	482	mm				Indicates the position of the opening in the back side of the cabinet.			N/A		
MIN cut out radius	6.5	mm				MIN Width of rear opening of the cabinet			0	mm	
MAX cut out radius	8	mm				MIN Depth of rear opening of the cabinet			0	mm	
FLUSH INSTALLATION						MIN AREA of rear opening of the cabinet			0	cm ²	
Indicates whether a flush installation is possible. Default is "N"	No					MIN distance from cabinet to rear wall			0	mm	
MIN Milling rabbet width	0	mm				Indicates whether a ventilation opening in the top front side of cabinet is needed or not. Default is "N"			No		
MAX Milling rabbet width	0	mm				MIN Frontal gap of the cabinet			0	mm	
MIN Milling rabbet depth	0	mm				MIN frontal opening area of the cabinet			0	cm ²	
MAX Milling rabbet depth	0	mm				INSTALLATION SPACE					
Milling rabbet thickness	0	mm				Depth of immersion underneath the appliance			3	mm	
Radius milling rabbet	0	mm				Width protruding area below bottom box			53	mm	
Flush installation KIT (2)	N/A					Depth protruding area below bottom box			75	mm	
Indicates the minum worktop thickness with standard installation for gas	20	mm				Protruding area: X positioning			6	mm	
Indicates the maximum worktop thickness with standard installation for gas	60	mm				Protruding area: Y positioning			21	mm	
Indicates the minum worktop thickness with flush installation for gas	0	mm				ACCESSORIES FOR INSTALLATION					
Indicates the maximum worktop thickness with flush installation for gas	0	mm				Gasket			Separate KIT		
WITH OVEN											
Indicates whether the cooktop can be installed above oven. Default is "Y"	Yes										
MIN worktop thickness with oven	0	mm									
MAX worktop thickness with oven	0	mm									

DIMENSION**MEASURE**

Clips	Separate KIT	
Injector KIT	Separate KIT	
Elbow KIT	N/A	
COOKTOP HOOD INSTALLATION ONLY FOR GAS		
MIN distance from cooktop to above furniture	750	mm
MIN distance between cabinets above the cooktop	600	mm
MAX distance between cabinets above the cooktop	750	mm