## **0MK58HU1X**


12NC: 859991659970

GTIN (EAN) code: 8003437939259



SENSING THE DIFFERENCE





Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 551 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	MAIN FEATURES	
Main colour of product  Construction type Built-in Type of control Type of control Electronic Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 13 Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 595 Depth of the product 595 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Product group	Oven
Construction type Type of control Type of control Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 13 Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 595 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) Tintegrated Cleaning system Hydrolytic Grids of the cavity 1	Commercial code	0MK58HU1X
Type of control Type of control Electronic Type of control settings Are any hobs controls integrated? No Which kind of hobs can be controlled? Automatic programmes Yes Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) Plug type No Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Width of the product 595 Depth of the product 551 Minimum niche height 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) Tintegrated Cleaning system Hydrolytic Grids of the cavity 1	Main colour of product	Инокс
Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 551 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Construction type	Built-in
Are any hobs controls integrated?  Which kind of hobs can be controlled?  Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  No  Depth with open door 90 degree (mm)  Height of the product  595  Width of the product  595  Width of the product  595  Depth of the product  595  Minimum niche height  0  Minimum niche width  0  Net weight (kg)  27.55  Usable volume (of cavity)  Integrated Cleaning system  Hydrolytic  Grids of the cavity  1	Type of control	Electronic
Which kind of hobs can be controlled?  Automatic programmes  Current (A)  13  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  No  Depth with open door 90 degree (mm)  Height of the product  595  Width of the product  595  Width of the product  595  Depth of the product  551  Minimum niche height  0  Minimum niche width  0  Net weight (kg)  27.55  Usable volume (of cavity)  Integrated Cleaning system  Hydrolytic  Grids of the cavity  1	Type of control settings	-
Automatic programmes  Current (A)  13  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  No  Depth with open door 90 degree (mm)  Height of the product  595  Width of the product  595  Depth of the product  595  Depth of the product  551  Minimum niche height  0  Minimum niche width  0  Net weight (kg)  27.55  Usable volume (of cavity)  Integrated Cleaning system  Hydrolytic  Grids of the cavity  1	Are any hobs controls integrated?	No
Current (A)         13           Voltage (V)         220-240           Frequency (Hz)         50/60           Length of Electrical Supply Cord (cm)         100           Plug type         No           Depth with open door 90 degree (mm)         -           Height of the product         595           Width of the product         595           Depth of the product         551           Minimum niche height         0           Minimum niche width         0           Niche depth         0           Net weight (kg)         27.55           Usable volume (of cavity)         71           Integrated Cleaning system         Hydrolytic           Grids of the cavity         1	Which kind of hobs can be controlled?	-
Voltage (V) 220-240  Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 100  Plug type No  Depth with open door 90 degree (mm)  Height of the product 595  Width of the product 595  Depth of the product 551  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 27.55  Usable volume (of cavity) 71  Integrated Cleaning system Hydrolytic  Grids of the cavity 1	Automatic programmes	Yes
Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 100  Plug type No  Depth with open door 90 degree (mm) -  Height of the product 595  Width of the product 595  Depth of the product 551  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 27.55  Usable volume (of cavity) 71  Integrated Cleaning system Hydrolytic  Grids of the cavity 1	Current (A)	13
Length of Electrical Supply Cord (cm) Plug type No Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 551 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) Integrated Cleaning system Hydrolytic Grids of the cavity 1	Voltage (V)	220-240
Plug type       No         Depth with open door 90 degree (mm)       -         Height of the product       595         Width of the product       595         Depth of the product       551         Minimum niche height       0         Minimum niche width       0         Niche depth       0         Net weight (kg)       27.55         Usable volume (of cavity)       71         Integrated Cleaning system       Hydrolytic         Grids of the cavity       1	Frequency (Hz)	50/60
Depth with open door 90 degree (mm)  Height of the product  S95  Width of the product  595  Depth of the product  Minimum niche height  Minimum niche width  O  Niche depth  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Hydrolytic  Grids of the cavity  1	Length of Electrical Supply Cord (cm)	100
Height of the product 595 Width of the product 595 Depth of the product 551 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Plug type	No
Width of the product 595  Depth of the product 551  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 27.55  Usable volume (of cavity) 71  Integrated Cleaning system Hydrolytic  Grids of the cavity 1	Depth with open door 90 degree (mm)	-
Depth of the product 551  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 27.55  Usable volume (of cavity) 71  Integrated Cleaning system Hydrolytic  Grids of the cavity 1	Height of the product	595
Minimum niche height     0       Minimum niche width     0       Niche depth     0       Net weight (kg)     27.55       Usable volume (of cavity)     71       Integrated Cleaning system     Hydrolytic       Grids of the cavity     1	Width of the product	595
Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Depth of the product	551
Niche depth 0  Net weight (kg) 27.55  Usable volume (of cavity) 71  Integrated Cleaning system Hydrolytic  Grids of the cavity 1	Minimum niche height	0
Net weight (kg) 27.55  Usable volume (of cavity) 71  Integrated Cleaning system Hydrolytic  Grids of the cavity 1	Minimum niche width	0
Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Niche depth	0
Integrated Cleaning system Hydrolytic Grids of the cavity 1	Net weight (kg)	27.55
Grids of the cavity 1	Usable volume (of cavity)	71
•	Integrated Cleaning system	Hydrolytic
Trays 2	Grids of the cavity	1
	Trays	2

TECHNICAL FEATURES	
Timer	Yes
Time control	Electronic
Time-setting options	Stop
Safety device	-
Interior light	Yes
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Front left
Oven guides of the cavity	Telescopic
Probe of the cavity	No

ENERGY LABEL	
Energy input	Electric
Type of energy of the cavity	електрически
Energy efficiency class - NEW (2010/30/EU)	A+
Energy consumption per cycle conventional - NEW (2010/30/EU)	0.89
Energy consumption per cycle forced air convection - NEW (2010/30/EU)	0.69