



DIMENSION	MEASURE	DIMENSION	MEASURE
WOODEN CABINET - Overall Wooden Cabinet - BI		APPLIANCE	
Overall Appliance		Overall Appliance	
01. Height MIN of the tall cabinet Niche, including all required space for installation or ventilation (HMIN_T)	1776 mm	01. Height MIN Product, watch the detail drawing for the exact position of the dimension line (HMIP)	1770 mm
02. Height MAX of the tall cabinet Niche, including all required space for installation or ventilation (HMAN_T)	1786 mm	02. Height MAX product, watch the detail drawing for the exact position of the dimension line (HMAP)	1770 mm
03. Width MIN of the tall cabinet Niche, including all required space for installation or ventilation (WMIN_T)	560 mm	03. Width product, watch the detail drawing for the exact position of the dimension line (WP)	540 mm
04. Width MAX of the tall cabinet Niche, including all required space for installation or ventilation (WMAN_T)	570 mm	04. Depth product without front, watch the detail drawing for the exact position of the dimension line (DP)	0 mm
05. Depth of the tall cabinet Niche, including all required space for installation or ventilation (DN_T)	550 mm	05. Depth product, watch the detail drawing for the exact position of the dimension line (D)	545 mm
06. Height MIN of the base cabinet Niche, including all required space for installation or ventilation (HMIN_B)	0	06. Depth MIN plinth return front (DMIPRF)	0 mm
07. Height MAX of the base cabinet Niche, including all required space for installation or ventilation (HMAN_B)	0	07. Depth MAX plinth return front (DMAPRF)	41 mm
08. Width MIN of the base cabinet Niche, including all required space for installation or ventilation (WMIN_B)	0	08. Height MIN Plinth return. This dimension is taken by minimum appliance height (HMIPR)	56 mm
09. Width MAX of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B)	0	09. Height MAX Plinth return. This dimension is taken at minimum appliance height (HMAPR)	56 mm
10. Depth of the base cabinet Niche, including all required space for installation or ventilation (DN_B)	0	Door or Drawer	
11. Indicates whether a ventilation opening is needed or not. Default is "N"	Yes	10. Height front. When appliance has more than one front, only the most bottom left front is described here (HF)	618 mm
12. Appliance can be used as base for other appliances from the same manufacturer. Default is "N"	No	11. Width front. When appliance has more than one front, only the most bottom left front is described here (WF)	540 mm
WOODEN CABINET - Door – Drawer		12. Depth front (DF)	0 mm
13. Height MIN Decorative Front, if appliance has more than one front, only the most bottom left front is described here (HMIF)	1006 mm	13. Maximum depth all protruding elements, e.g. handles, controls (DC)	0 mm
14. Width MIN Decorative Front, if appliance has more than one front, only the most bottom left front is described here (WMIF)	560 mm	14. Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90° (CC)	0 mm
15. Weight/Thickness of the decorative bottom front panel of the Kitchen manufacturer needs (essential)	No	15. Projection of front in relation to housing of appliance (FPT)	18 mm
16. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)	0 kg	16. Projection of front in relation to bearing area of the appliance. Taken at MIN height of appliance if adjustable height(FPB)	0 mm
17. Thickness MIN Decorative Front, if appliance has more than one front only the most bottom left front is described here(TMIF)	0 mm	17. Height Product Panel. When product panel is missing, set to 0 (HMAPP)	27 mm
18. Thickness MAX Decorative Front, if appliance has more than one front only the most bottom left front is described here(TMAF)	0 mm	18. Lateral projection of front including controls when door is opened totally. At the side where the hinge is mounted (FPOD)	0 mm
Additional Fronts (2 doors)		19. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)	0 mm
19. Height MIN Decorative Front, when appliance has more than one front, upper front is described here (HMIFU)	0 mm	20. Lateral projection of opened front at the side where the hinge is fixed (FPD)	0 mm
20. Width MIN Decorative Front, when appliance has more than one front, upper front is described here (WMIFU)	0 mm	21. Door hinge positioning and tipology	Right-changeable
21. Weight/Thickness of the decorative upper front panel of the Kitchen manufacturer needs (essential)	No	22. Type of preparation to fix the cover door	Sliding system
22. Weight MAX of the decorative upper front panel of the Kitchen manufacturer (WEMAFU)	0 kg	23. Maximum angle when door is opened totally (AOD)	0 °
23. Thickness MIN Decorative Front, when appliance has more than one front, upper front is described here (TMIFU)	0 mm	24. Maximum thickness of the upper front panel (TUFP)	4 mm
24. Thickness MAX Decorative Front, when appliance has more than one front, upper front is	0 mm	Additional Fronts (2 doors)	
		25. Height front, when appliance has more than one front, upper front is described here (HUF)	1006 mm
		26. Width front, when appliance has more than one front, upper front is described here (WUF)	540 mm
		27. Useful space between the 2 doors, including hinges size (HMAFG)	60 mm
		28. Distance between the bottom of the product and the center line between the fridge doors (HFG)	704 mm

discribed here (TMAFU)		
TALL WOODEN CABINET - Vent-shaft incoming		
25. Indicates the position of the freespace for the incoming airflow, tall wooden cabinet	Front- Bottom	
26. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TI)	50	mm
27. Ventilation cavity minimum, tall wooden cabinet (VC_TI)	200	cm ²
TALL WOODEN CABINET - Vent-shaft outgoing		
28. Indicates the position of the freespace for the outgoing airflow, tall wooden cabinet	-	
29. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TO)	50	mm
30. Ventilation cavity minimum, tall wooden cabinet (VC_TO)	200	cm ²
BASE WOODEN CABINET - Vent-shaft incoming		
31. Indicates the position of the freespace for the incoming airflow, base wooden cabinet	-	
32. Clearance MIN Ventilation, base wooden cabinet (CMIV_BI)	0	mm
33. Ventilation cavity minimum, base wooden cabinet (VC_BI)	0	cm ²
BASE WOODEN CABINET - Vent-shaft outgoing		
34. Indicates the position of the freespace for the outgoing airflow, base wooden cabinet	-	
35. Clearance MIN Ventilation, base wooden cabinet (CMIV_BO)	0	mm
36. Ventilation cavity minimum, base wooden cabinet (VC_BO)	0	cm ²