

## AKZ9 6220 IX

## 12NC/Fx: 859991530410

## GTIN (EAN) code: 8003437833816

ERALL CABINET Height of the wall cabinet niche, including all required space for installation or ventilation Height of the tall cabinet niche, including all required space for installation or ventilation Height of the base cabinet niche, including all required space for installation or ventilation K Height of the wall cabinet niche, including all required space for installation or ventilation K Height of the tall cabinet niche, including all required space for installation or ventilation K Height of the tall cabinet niche, including all required space for installation or ventilation K Height of the base cabinet niche, including all required space for installation or ventilation	0 583 600 0 585 601 0	mm mm mm mm
Height of the tall cabinet niche, including all required space for installation or ventilation Height of the base cabinet niche, including all required space for installation or ventilation X Height of the wall cabinet niche, including all required space for installation or ventilation X Height of the tall cabinet niche, including all required space for installation or ventilation	583 600 0 585 601	mm mm mm
Height of the base cabinet niche, including all required space for installation or ventilation X Height of the wall cabinet niche, including all required space for installation or ventilation X Height of the tall cabinet niche, including all required space for installation or ventilation	600 0 585 601	mm mm
X Height of the wall cabinet niche, including all required space for installation or ventilation X Height of the tall cabinet niche, including all required space for installation or ventilation	0 585 601	mm
X Height of the tall cabinet niche, including all required space for installation or ventilation	585 601	
	601	mn
K Height of the base cabinet niche, including all required space for installation or ventilation		
	0	mn
Width of the wall cabinet niche, including all required space for installation or ventilation		mn
Width of the tall cabinet niche, including all required space for installation or ventilation	560	mn
Width of the base cabinet niche, including all required space for installation or ventilation	560	mn
X Width of the wall cabinet niche, including all required space for installation or ventilation	0	mn
X Width of the tall cabinet niche, including all required space for installation or ventilation	568	mn
X Width of the base cabinet niche, including all required space for installation or ventilation	568	mn
Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mr
Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mr
Depth of the base cabinet niche, including all required space for installation or ventilation	550	mr
ce in front, which is required to install bottom trim	10	mr
cates whether a ventilation opening is needed or not. Default is "N"	Yes	
LL CABINET (vent-shaft incoming)		
cates the position of the freespace for the inbound airflow (wall cabinet)	Rear	
imum space or inbound ventilation (wall cabinet)	0	mr
imum area for inbound ventilation cavity (wall cabinet)	0	cm
LL CABINET (vent-shaft outgoing)		
cates the position of the freespace for the outbound airflow (wall cabinet)	Rear	
imum space or outbound ventilation (wall cabinet)	0	mn
imum area for outbound ventilation cavity (wall cabinet)	0	cm
L CABINET (vent-shaft incoming)		
cates the position of the freespace for the inbound airflow (tall cabinet)	Rear	
imum space for inbound ventilation (tall cabinet)	30	mr
imum area for inbound ventilation cavity (tall cabinet)	150	cm
L CABINET (vent-shaft outgoing)		
cates the position of the freespace for the outbound airflow (tall cabinet)	Rear	
imum space for outbound ventilation (tall cabinet)	0	mr
imum area for outbound ventilation cavity (tall cabinet)	150	cm
SE CABINET (vent-shaft incoming)		
cates the position of the freespace for the inbound airflow (base cabinet)	Rear	
imum space for inbound ventilation (base cabinet)	30	mr
imum area for inbound ventilation cavity (base cabinet)	150	cm
SE CABINET (vent-shaft outgoing)	100	
cates the position of the freespace for the outbound airflow (base cabinet)	Rear	
imum space for outbound ventilation (base cabinet)	0	mn
imum area for outbound ventilation (base cabinet)	150	cm

DIMENSION MI		URE
APPLIANCE		
Height of the front	595	mn
Width of the front	595	mn
Depth of the front	20	mn
Maximum depth all protruding elements, e.g. handles, controls	41	mn
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	37	mm
Projection of front in relation to housing of appliance	18	mn
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	5	mn
When product panel is missing, set to 0	97	mn
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	458	mn
Height from bearing area of appliances and lower handle	442	mn
Frontal handle thickness	30	mn
Frontal handle width	521	mn
MIN Height of the product body	572	mn
MAX Height of the product body	572	mn
Width of the product body	546	mn
Depth of the product body	543	mn
Full depth of product excluding protruding interface elements	564	mn
-	-	mn
Appliance can be used as base for other appliances from the same manufacturer. Default is "No	' No	
Appliance Flap door		
Projection of the opened flap in relation to bearing area	0	mn
Maximum angle when flap door is opened totally	89	mn
Appliance Side swing door		
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	6 0	mn
Lateral projection of opened front at the side where the hinge is fixed	0	mn
Maximum angle when door is opened totally	0	mn
Appliance other		
Depth from front end of the niche to the front end of the freespace of the retrace	345	mn
Height from niche to bottom end of freespace for the retrace	537	mn