

PRODUCT FICHE HOOD

Trademark	HOTPOINT
Model identifier	PHFG9.4FLMX
Annual Energy Consumption	65,0 kWh/a
Energy Efficiency Class	D
Fluid Dynamic Efficiency	11,7
Fluid Dynamic Efficiency class	E
Lighting efficiency in lux/Watt	29,0 lux/W
Lighting efficiency class	A
Grease filtering efficiency	76,0 %
Grease filtering efficiency class	C
Minimum air flow	320 m ³ /h
Maximum Air flow	432 m ³ /h
Air flow boost	0 m ³ /h
A-weighted sound power at min. speed	57 dB(A)
A-weighted sound power at max. speed	65 dB(A)
A-weighted sound power boost	0 dB(A)
Power consumption in off-mode	0,00 W
Power consumption in standby mode	0,00 W
Time increase factor (f)	1,6
Energy Efficiency Index (EEI_{hood})	85,8
Measured air flow rate at best efficiency point (Q_{BEP})	240,0 m ³ /h
Measured air pressure at best efficiency point (P_{BEP})	185 Pa
Measured electric power input at best efficiency point (W_{BEP})	105,0 W
Nominal power of the lighting system (W_L)	5,0 W
Average illumination of the lighting system on the cooking surface (E_{middle})	145 lux