

## **KCBWX 70600L**

## 12NC/Fx: 851328301110

DIMENSION		URE	DIMENSION		URE
WOODEN CABINET - Overall Wooden Cabinet - BI			APPLIANCE		
01. Height MIN of the tall cabinet Niche, including all required space for installation or ventilation	687	mm	Overall Appliance		
(HMIN_T)			01. Height MIN Product, watch the detail drawing for the exact position of the dimension line (HMIP	9) 682	mm
02. Height MAX of the tall cabinet Niche, including all required space for installation or ventilation (HMAN_T)	690	mm	02. Height MAX product, watch the detail drawing for the exact position of the dimension line (HMAP)	682	mm
03. Width MIN of the tall cabinet Niche, including all required space for installation or ventilation	560	mm	03. Width product, watch the detail drawing for the exact position of the dimension line (WP)	561	mn
(WMIN_T) 04. Width MAX of the tall cabinet Niche, including all required space for installation or ventilation	570	mm	04. Depth product without front, watch the detail drawing for the exact position of the dimension line (DP)	e 555	mn
(WMAN_T)			05. Depth product, watch the detail drawing for the exact position of the dimension line (D)	579	mn
05. Depth of the tall cabinet Niche, including all required space for installation or ventilation (DN_T)		mm	06. Depth MIN plinth return front (DMIPRF)	0	mn
06. Height MIN of the base cabinet Niche, including all required space for installation or ventilation	702		07. Depth MAX plinth return front (DMAPRF)	0	mm
(HMIN_B)	. 700		08. Height MIN Plinth return. This dimension is taken by minimum appliance height (HMIPR)	0	mm
07. Height MAX of the base cabinet Niche, including all required space for installation or ventila (HMAN_B)	n 703		09. Height MAX Plinth return. This dimension is taken at minimum appliance height (HMAPR)	0	mm
08. Width MIN of the base cabinet Niche, including all required space for installation or ventilation	560		Door or Drawer		
(WMIN_B) 09. Width MAX of the base cabinet Niche, including all required space for installation or ventilation			10. Height front. When appliance has more than one front, only the most bottom left front is discribed here (HF)	721	mm
(WMAN_B) 10. Depth of the base cabinet Niche, including all required space for installation or ventilation	560		11. Width front. When appliance has more than one front, only the most bottom left front is discribe here (WF)	d 588	mm
(DN_B)	500		12. Depth front (DF)	24	mm
11. Indicates whether a ventilation opening is needed or not. Default is "N"	Yes		13. Maximum depth all protruding elements, e.g. handles, controls (DC)	42	mm
12. Appliance can be used as base for other appliances from the same manufacturer. Default is "N"	No		14. Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90° (CC)	27	mm
WOODEN CABINET - Door – Drawer			15. Projection of front in relation to housing of appliance (FPT)	17	mm
13. Height MIN Decorative Front, if appliance has more than one front, only the most bottom left front is described here (HMIF)	0	mm	16. Projection of front in relation to bearing area of the appliance. Taken at MIN height of appliance if adjustable height(FPB)	17	mm
th MIN Decorative Front, if appliance has more than one front, only the most bottom left	0	mm	17. Height Product Panel. When product panel is missing, set to 0 (HMAPP)	0	mm
front is described here (WMIF)			18. Lateral projection of front including controls when door is opened totaly. At the side where the	42	mm
15. Weight/Thickness of the decorative bottom front panel of the Kitchen manufacturer needs (essential)	No		hinge is mounted (FPOD) 19. Space in front, which is required to guarantee full operability. The most protruding part gives thi	s 580	mm
16. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)	0	kg	dimension (RSF)		
17. Thickness MIN Decorative Front, if appliance has more than one front only the most bottom left	0	mm	20. Lateral projection of opened front at the side where the hinge is fixed (FPD)	0	mm
front is described here(TMIF)			21. Door hinge positiong and tipology	Righ	nt
	0	mm	22. Type of preparation to fix the cover door	N/A	
left front is described here(TMAF)			23. Maximum angle when door is opened totaly (AOD)	90	٥
Additional Fronts (2 doors)	0		24. Maximum thickness of the upper front panel (TUFP)	0	mm
19. Height MIN Decorative Front, when appliance has more than one front, upper front is discribed here (HMIFU)	0	mm	Additional Fronts (2 doors)		
20. Width MIN Decorative Front, when appliance has more than one front, upper front is discribed	0	mm	25. Height front, when appliance has more than one front, upper front is discribed here (HUF)	0	mm
here (WMIFU)	Ŭ		26. Width front, when appliance has more than one front, upper front is discribed here (WUF)	0	mm
21. Weight/Thickness of the decorative upper front panel of the Kitchen manufacturer needs (essential)	No		<ul><li>27. Useful space between the 2 doors, including hinges size (HMAFG)</li><li>28. Distance between the bottom of the product and the center line between the fridge doors (HFG)</li></ul>	0) 0	mm mm
22. Weight MAX of the decorative upper front panel of the Kitchen manufacturer (WEMAFU)	0	kg			
23. Thickness MIN Decorative Front, when appliance has more than one front, upper front is discribed here (TMIFU)	0	mm			

discribed here (TMAFU)		
TALL WOODEN CABINET - Vent-shaft incoming		
25. Indicates the position of the freespace for the incoming airflow, tall wooden cabinet	Front- Bottom	1
26. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TI)	50	mm
27. Ventilation cavity minimum, tall wooden cabinet (VC_TI)	200	cm <sup>2</sup>
TALL WOODEN CABINET - Vent-shaft outgoing		
28. Indicates the position of the freespace for the outgoing airflow, tall wooden cabinet	Front	
29. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TO)	0	mm
30. Ventilation cavity minimum, tall wooden cabinet (VC_TO)	0	cm <sup>2</sup>
BASE WOODEN CABINET - Vent-shaft incoming		
31. Indicates the position of the freespace for the incoming airflow, base wooden cabinet	Front- Bottom	
32. Clearance MIN Ventilation, base wooden cabinet (CMIV_BI)	50	mm
<ol> <li>Ventilation cavity minimum, base wooden cabinet (VC_BI)</li> </ol>	200	cm <sup>2</sup>
BASE WOODEN CABINET - Vent-shaft outgoing		
34. Indicates the position of the freespace for the outgoing airflow, base wooden cabinet	Front	
35. Clearance MIN Ventilation, base wooden cabinet (CMIV_BO)	0	mm
36. Ventilation cavity minimum, base wooden cabinet (VC_BO)	0	cm <sup>2</sup>