

W8I HP42 L UK

12NC/Fx: 859991657320

| DIMENSION | MEASURE | |
|--|----------------------------|----|
| OVERALL CABINET | | |
| 01. Height MIN of the base cabinet Niche, including all required space for installation or ventilation (HMIN_B) | 820 | mm |
| 02. Height MAX of the base cabinet Niche, including all required space for installation or ventilation (HMAN_B) | 900 | mm |
| 03. Width MIN of the base cabinet Niche, including all required space for installation or ventilation (WMIN_B) | 600 | mm |
| 04.Width MAX of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B) | 608 | mm |
| 05. Depth of the base cabinet Niche, including all required space for installation or ventilation (DN_B) | 560 | mm |
| 06. Indicates whether a ventilation opening is needed or not. Default is "N" | No | |
| 07. appliance can be used as base for other appliances from the same manufacturer. Default is "N" | No | |
| Built In - Floor Standing | | |
| 08. Height MIN Decorative Front (HMIF) | 715 | mm |
| 09. Height MAX Decorative Front (HMAF) | 760 | mm |
| 10. Width MIN Decorative Front (WMIF) | 596 | mm |
| 11. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF) | 10 | kg |
| 12. Weight MIN of the decorative front panel of the Kitchen manufacturer (WEMIF) | 3 | kg |
| 13. Thickness MAX of decorative front panel of the kitchen manufacturers (TMAF) | 25 | mm |
| 14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG) | 3 | mm |
| APPLIANCE | | |
| Overall Appliance | | |
| 01. Height MIN Product (HMIP) | 820 | mm |
| 02. Height MAX product (HMAP) | 900 | mm |
| 03. Width product (WP) | 598 | mm |
| 04. Depth product without front (DP) | 555 | mm |
| 05. Depth product (D) | 0 | mm |
| 06. Depth MIN of plinth return front (DMIPRF) | 78 | mm |
| 07. Depth MAX of plinth return front (DMAPRF) | 78 | mm |
| 08. Height MIN Plinth return. Dimension is taken by minimum appliance height (HMIMIPR) | 53 | mm |
| 09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMAPR) | 98 | mm |
| 10. Height MIN Plinth return. Dimension is taken by maximum appliance height (HMAMIPR) | 133 | mm |
| 11. Height MAX Plinth return. Dimension is taken at maximum appliance height (HMAMAPR) | 178 | mm |
| Built In - Floor Standing | | |
| 12. Height MIN Product Panel. When product panel is missing, set to 0 (HMIPP) | 0 | mm |
| 13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP) | 0 | mm |
| 14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF) | 630 | mm |
| 15. Type of preparation to fix the cover door | Drilling template standard | |
| Retrace back socle | | |
| 16. Depth of the socle retrace at the rear side (DBSR) | 45 | mm |
| 17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR) | 65 | mm |
| TEMPLATE NAME | | |
| 00. Name of the template to be used | DISH_FULLDOOR60CM_MAXI | |