
## KDSDM 82142 (UK)

12NC: 859991057770

GTIN (EAN) code: 8003437208966





Construction type Built-in Installation type Full-integrated Type of control Electronic Type of control Settings - Removable work top N/A Door decor panel N/A Main colour of product Inox Electrical connection rating (W) 1900 Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 150 Plug type UK Length inlet hose (cm) 155 Length outlet hose (cm) 150 Adjustable plinth No Height of removable worktop (mm) 0 Adjustable feet Yes - all from front Height of the product 598 Width of the product 598 Depth of the product 555 Depth with open door 90 degree (mm) - Minimum niche height 900 Maximum niche height 660 Maximum niche width 600 Niche depth 560 Net weight (kg) 35.5 Gross weight (kg) 37.5	MAIN FEATURES	
Type of control Type of control settings Removable work top N/A Door decor panel Main colour of product Electrical connection rating (W) Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Length inlet hose (cm) Length outlet hose (cm) Adjustable plinth No Height of removable worktop (mm) Adjustable feet Width of the product Width of the product Depth with open door 90 degree (mm) Minimum niche height Maximum niche width Mond Maximum niche width Mond Net weight (kg) S560 Net weight (kg) S560 Net weight (kg) S560 Net weight (kg)	Construction type	Built-in
Type of control settings  Removable work top  Door decor panel  Main colour of product  Electrical connection rating (W)  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  UK  Length inlet hose (cm)  Length outlet hose (cm)  Adjustable plinth  No  Height of removable worktop (mm)  Adjustable feet  Yes - all from front  Height of the product  Sobject  Depth with open door 90 degree (mm)  Minimum niche height  Maximum niche width  Model Cool  Model Cool  Not weight (kg)  35.5	Installation type	Full-integrated
Removable work top N/A  Door decor panel N/A  Main colour of product Inox  Electrical connection rating (W) 1900  Current (A) 13  Voltage (V) 220-240  Frequency (Hz) 50  Length of Electrical Supply Cord (cm) 150  Plug type UK  Length inlet hose (cm) 155  Length outlet hose (cm) 150  Adjustable plinth No  Height of removable worktop (mm) 0  Adjustable feet Yes - all from front  Height of the product 820  Width of the product 598  Depth of the product 555  Depth with open door 90 degree (mm)  Minimum niche height 900  Minimum niche width 600  Maximum niche width 600  Niche depth Net weight (kg) 35.5	Type of control	Electronic
Door decor panel N/A  Main colour of product Inox  Electrical connection rating (W) 1900  Current (A) 13  Voltage (V) 220-240  Frequency (Hz) 50  Length of Electrical Supply Cord (cm) 150  Plug type UK  Length inlet hose (cm) 155  Length outlet hose (cm) 150  Adjustable plinth No  Height of removable worktop (mm) 0  Adjustable feet Yes - all from front  Height of the product 598  Depth of the product 598  Depth with open door 90 degree (mm) -  Minimum niche height 900  Maximum niche width 600  Maximum niche width 600  Niche depth 560  Net weight (kg) 35.5	Type of control settings	-
Main colour of product  Electrical connection rating (W)  Current (A)  13  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  UK  Length inlet hose (cm)  Length outlet hose (cm)  Adjustable plinth  Height of removable worktop (mm)  Adjustable feet  Yes - all from front  Height of the product  B20  Width of the product  Depth of the product  Depth with open door 90 degree (mm)  Minimum niche height  Maximum niche width  Moo  Maximum niche width  Moo  Niche depth  No  150  150  150  150  150  150  150  15	Removable work top	N/A
Electrical connection rating (W)  Current (A)  13  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  UK  Length inlet hose (cm)  Length outlet hose (cm)  Adjustable plinth  No  Height of removable worktop (mm)  Adjustable feet  Width of the product  B20  Width of the product  Depth of the product  Depth with open door 90 degree (mm)  Minimum niche height  Maximum niche width  Maximum niche width  Maximum niche width  Mo  No  Maximum niche width  Mo  Maximum niche width  Mo  No  No  No  Maximum niche width  Mo  No  No  Maximum niche width  Mo  No  No  No  No  No  No  No  No  No	Door decor panel	N/A
Current (A) 13  Voltage (V) 220-240  Frequency (Hz) 50  Length of Electrical Supply Cord (cm) 150  Plug type UK  Length inlet hose (cm) 155  Length outlet hose (cm) 150  Adjustable plinth No  Height of removable worktop (mm) 0  Adjustable feet Yes - all from front  Height of the product 820  Width of the product 598  Depth of the product 555  Depth with open door 90 degree (mm) -  Minimum niche height 820  Maximum niche height 900  Minimum niche width 600  Maximum niche width 600  Niche depth (kg) 35.5	Main colour of product	Inox
Voltage (V) Frequency (Hz)  Length of Electrical Supply Cord (cm) Plug type  UK  Length inlet hose (cm)  Length outlet hose (cm)  Adjustable plinth  No  Height of removable worktop (mm)  Adjustable feet  Yes - all from front  Height of the product  B20  Width of the product  S98  Depth of the product  Depth with open door 90 degree (mm)  Maximum niche height  Maximum niche width  Mo  Maximum niche width  600  Maximum niche width  600  Niche depth  Net weight (kg)  35.5	Electrical connection rating (W)	1900
Frequency (Hz) 50  Length of Electrical Supply Cord (cm) 150  Plug type UK  Length inlet hose (cm) 155  Length outlet hose (cm) 150  Adjustable plinth No  Height of removable worktop (mm) 0  Adjustable feet Yes - all from front  Height of the product 820  Width of the product 598  Depth of the product 555  Depth with open door 90 degree (mm) -  Minimum niche height 900  Minimum niche width 600  Maximum niche width 600  Niche depth (kg) 35.5	Current (A)	13
Length of Electrical Supply Cord (cm)  Plug type  UK  Length inlet hose (cm)  155  Length outlet hose (cm)  Adjustable plinth  No  Height of removable worktop (mm)  Adjustable feet  Yes - all from front  Height of the product  820  Width of the product  598  Depth of the product  555  Depth with open door 90 degree (mm)  Minimum niche height  820  Maximum niche height  900  Minimum niche width  600  Maximum niche width  600  Niche depth  Net weight (kg)  35.5	Voltage (V)	220-240
Plug type  Length inlet hose (cm)  Length outlet hose (cm)  Adjustable plinth  Height of removable worktop (mm)  Adjustable feet  Yes - all from front  Height of the product  B20  Width of the product  S98  Depth of the product  Depth with open door 90 degree (mm)  Minimum niche height  Maximum niche width  Maximum niche width  Maximum niche width  Moo  Maximum niche width  Moo  Maximum niche width  Moo  Met weight (kg)  J55  Depth with open door 90 degree (mm)  Minimum niche width  Moo  Maximum niche width  Moo  Maximum niche width  Moo  Niche depth  S60  Net weight (kg)	Frequency (Hz)	50
Length inlet hose (cm) 155  Length outlet hose (cm) 150  Adjustable plinth No  Height of removable worktop (mm) 0  Adjustable feet Yes - all from front  Height of the product 820  Width of the product 598  Depth of the product 555  Depth with open door 90 degree (mm) - Minimum niche height 820  Maximum niche height 900  Minimum niche width 600  Maximum niche width 600  Niche depth 560  Net weight (kg) 35.5	Length of Electrical Supply Cord (cm)	150
Length outlet hose (cm)  Adjustable plinth  No  Height of removable worktop (mm)  Adjustable feet  Yes - all from front  Height of the product  820  Width of the product  598  Depth of the product  555  Depth with open door 90 degree (mm)  - Minimum niche height  820  Maximum niche height  900  Minimum niche width  600  Maximum niche width  600  Niche depth  560  Net weight (kg)  35.5	Plug type	UK
Adjustable plinth  Height of removable worktop (mm)  O  Adjustable feet  Yes - all from front  Height of the product  B20  Width of the product  Depth of the product  Depth with open door 90 degree (mm)  Minimum niche height  Maximum niche height  Maximum niche width  Mo  Maximum niche width  Miche depth  Niche depth  Net weight (kg)  No  No  No  No  No  No  No  No  No  N	Length inlet hose (cm)	155
Height of removable worktop (mm)  Adjustable feet Yes - all from front Height of the product 820 Width of the product 598  Depth of the product 555  Depth with open door 90 degree (mm) - Minimum niche height 820  Maximum niche height 900  Minimum niche width 600  Maximum niche width 600  Niche depth 560  Net weight (kg) 35.5	Length outlet hose (cm)	150
Adjustable feet Yes - all from front Height of the product 820 Width of the product 598 Depth of the product 555 Depth with open door 90 degree (mm) - Minimum niche height 820 Maximum niche height 900 Minimum niche width 600 Maximum niche width 600 Niche depth 560 Net weight (kg) 35.5	Adjustable plinth	No
Height of the product 820  Width of the product 598  Depth of the product 555  Depth with open door 90 degree (mm) -  Minimum niche height 820  Maximum niche height 900  Minimum niche width 600  Maximum niche width 600  Niche depth 560  Net weight (kg) 35.5	Height of removable worktop (mm)	0
Width of the product 598  Depth of the product 555  Depth with open door 90 degree (mm) -  Minimum niche height 820  Maximum niche height 900  Minimum niche width 600  Maximum niche width 600  Niche depth 560  Net weight (kg) 35.5	Adjustable feet	Yes - all from front
Depth of the product 555  Depth with open door 90 degree (mm) -  Minimum niche height 820  Maximum niche height 900  Minimum niche width 600  Maximum niche width 600  Niche depth 560  Net weight (kg) 35.5	Height of the product	820
Depth with open door 90 degree (mm) -  Minimum niche height 820  Maximum niche height 900  Minimum niche width 600  Maximum niche width 600  Niche depth 560  Net weight (kg) 35.5	Width of the product	598
Minimum niche height820Maximum niche height900Minimum niche width600Maximum niche width600Niche depth560Net weight (kg)35.5	Depth of the product	555
Maximum niche height         900           Minimum niche width         600           Maximum niche width         600           Niche depth         560           Net weight (kg)         35.5	Depth with open door 90 degree (mm)	-
Minimum niche width600Maximum niche width600Niche depth560Net weight (kg)35.5	Minimum niche height	820
Maximum niche width         600           Niche depth         560           Net weight (kg)         35.5	Maximum niche height	900
Niche depth 560 Net weight (kg) 35.5	Minimum niche width	600
Net weight (kg) 35.5	Maximum niche width	600
	Niche depth	560
Gross weight (kg) 37.5	Net weight (kg)	35.5
	Gross weight (kg)	37.5

TECHNICAL FEATURES	
Automatic programmes	Yes
Maximum temperature for water intake (°C)	60
Start delay options	Continuous
Start delay time max. (h)	12
Progress indicator	-
Digital countdown indicator	Yes
Salt light indicator	Yes
Rinse aid light indicator	Yes
Safety device	N/A
Adjustable upper basket	Yes
Largest loadable dish upper basket (cm)	0
Largest loadable dish lower basket (cm)	0
Number of place settings	14

PERFORMANCES	
Energy efficiency class - NEW (2010/30/EU)	A+++
Energy consumption annual (kWh/annum) - NEW (2010/30/EU)	238
Duration of the left-on mode - NEW (2010/30/EU)	12
Power consumption in left-on mode - NEW (2010/30/EU)	6
Power consumption in off-mode - NEW (2010/30/EU)	0.5
Water consumption annual (L/annum) - NEW (2010/30/EU)	2660
Noise level (dB(A) re 1 pW)	43