



DIMENSION	MEASURE		DIMENSION	MEASURE	
APPLIANCE					
Product width	860	mm	Indicates whether a protection tray against heat or contact is needed with oven. Default is "N"	No	
Product depth	510	mm	Indicates whether a ventilation opening in the back side of cabinet is needed or not with oven. Default is "Y"	No	
Radius of product corner	5	mm	Indicates the position of the opening in the back side of the cabinet with oven	N/A	
Product height (MAX protrusion from the worktop)	60	mm	MIN Width of rear opening required with oven	0	mm
Underneath the bearing area of the appliance	40	mm	MIN Depth of rear opening required with oven.	0	mm
Distance between cut out and top frontal projection	12	mm	MIN AREA of rear opening required with oven	0	cm ²
Distance between cut out and top lateral projection	10	mm	MIN distance from cabinet to rear wall, with oven	0	mm
Plateau thickness	10	mm	Indicates whether a ventilation opening in the top front side of cabinet is needed or not with oven. Default is "N"	No	
Gas outlet positioning	Rear right		MIN Frontal gap required, with oven (2)	0	mm
Gas outlet X positioning	35	mm	MIN frontal opening area required with oven	0	cm ²
Gas outlet Y positioning	38	mm	WITH CABINET		
Power cable	With product		MIN worktop thickness with cabinet	0	mm
Power cable positioning	Rear		MAX worktop thickness with cabinet	0	mm
CUT OUT			Indicates whether a protection tray against heat or contact is needed. Default is "Y"	Yes	
MIN front distance from cut-out to end worktop	0	mm	MIN distance from bottom line of appliance to protection tray	20	mm
MIN rear distance from cut out to wall/furniture	70	mm	Indicates whether a ventilation opening in the tray is needed or not with cabinet	No	
MIN lateral distance from cut out to wall/furniture	110	mm	Recess dimension X	0	mm
MIN height from worktop to above furniture	530	mm	Recess dimension Y	0	mm
MIN cut out width	837	mm	Positioning dimension X by axis	0	mm
MAX cut out width	839	mm	Distance of the tray from the back panel/wall	0	mm
MIN cut out depth	486	mm	Indicates whether a divider is available	N/A	
MAX cut out depth	488	mm	Indicates whether a ventilation opening in the back side of cabinet is needed or not. Default is "Y"	No	
MIN cut out radius	6.5	mm	Indicates the position of the opening in the back side of the cabinet.	N/A	
MAX cut out radius	8	mm	MIN Width of rear opening of the cabinet	0	mm
FLUSH INSTALLATION			MIN Depth of rear opening of the cabinet	0	mm
Indicates whether a flush installation is possible. Default is "N"	Yes		MIN AREA of rear opening of the cabinet	0	cm ²
MIN Milling rabbet width	863	mm	MIN distance from cabinet to rear wall	0	mm
MAX Milling rabbet width	865	mm	Indicates whether a ventilation opening in the top front side of cabinet is needed or not. Default is "N"	No	
MIN Milling rabbet depth	513	mm	MIN Frontal gap of the cabinet	0	mm
MAX Milling rabbet depth	515	mm	MIN frontal opening area of the cabinet	0	cm ²
Milling rabbet thickness	12	mm	INSTALLATION SPACE		
Radius milling rabbet	6.5	mm	Depth of immersion underneath the appliance	9	mm
Flush installation KIT (2)	N/A		Width protruding area below bottom box	95	mm
Indicates the minum worktop thickness with standard installation for gas	20	mm	Depth protruding area below bottom box	78	mm
Indicates the maximum worktop thickness with standard installation for gas	60	mm	Protruding area: X positioning	3	mm
Indicates the minum worktop thickness with flush installation for gas	30	mm	Protruding area: Y positioning	14	mm
Indicates the maximum worktop thickness with flush installation for gas	68	mm	ACCESSORIES FOR INSTALLATION		
WITH OVEN			Gasket	Separate KIT	
Indicates whether the cooktop can be installed above oven. Default is "Y"	Yes		Clips	Separate	
MIN worktop thickness with oven	0	mm			
MAX worktop thickness with oven	0	mm			

DIMENSION**MEASURE**

	KIT	
Injector KIT	Separate KIT	
Elbow KIT	N/A	
COOKTOP HOOD INSTALLATION ONLY FOR GAS		
MIN distance from cooktop to above furniture	700	mm
MIN distance between cabinets above the cooktop	600	mm
MAX distance between cabinets above the cooktop	750	mm