



DIMENSION	MEASURE		DIMENSION	MEASURE	
APPLIANCE					
Product width	580	mm	Indicates whether a protection tray against heat or contact is needed with oven. Default is "N"	No	
Product depth	510	mm	Indicates whether a ventilation opening in the back side of cabinet is needed or not with oven. Default is "Y"	No	
Radius of product corner	10	mm	Indicates the position of the opening in the back side of the cabinet with oven	N/A	
Product height (MAX protrusion from the worktop)	4	mm	MIN Width of rear opening required with oven	0	mm
Underneath the bearing area of the appliance	42	mm	MIN Depth of rear opening required with oven.	0	mm
Distance between cut out and top frontal projection	10	mm	MIN AREA of rear opening required with oven	0	cm ²
Distance between cut out and top lateral projection	10	mm	MIN distance from cabinet to rear wall, with oven	0	mm
Plateau thickness	4	mm	Indicates whether a ventilation opening in the top front side of cabinet is needed or not with oven. Default is "N"	No	
Gas outlet positioning	N/A		MIN Frontal gap required, with oven (2)	0	mm
Gas outlet X positioning	0	mm	MIN frontal opening area required with oven	0	cm ²
Gas outlet Y positioning	0	mm	WITH CABINET		
Power cable	N/A		MIN worktop thickness with cabinet	20	mm
Power cable positioning	Rear		MAX worktop thickness with cabinet	50	mm
CUT OUT			Indicates whether a protection tray against heat or contact is needed. Default is "Y"	Yes	
MIN front distance from cut-out to end worktop	0	mm	MIN distance from bottom line of appliance to protection tray	20	mm
MIN rear distance from cut out to wall/furniture	70	mm	Indicates whether a ventilation opening in the tray is needed or not with cabinet	No	
MIN lateral distance from cut out to wall/furniture	100	mm	Recess dimension X	0	mm
MIN height from worktop to above furniture	400	mm	Recess dimension Y	0	mm
MIN cut out width	560	mm	Positioning dimension X by axis	0	mm
MAX cut out width	562	mm	Distance of the tray from the back panel/wall	0	mm
MIN cut out depth	490	mm	Indicates whether a divider is available	N/A	
MAX cut out depth	492	mm	Indicates whether a ventilation opening in the back side of cabinet is needed or not. Default is "Y"	No	
MIN cut out radius	6.5	mm	Indicates the position of the opening in the back side of the cabinet.	N/A	
MAX cut out radius	8	mm	MIN Width of rear opening of the cabinet	0	mm
FLUSH INSTALLATION			MIN Depth of rear opening of the cabinet	0	mm
Indicates whether a flush installation is possible. Default is "N"	Yes		MIN AREA of rear opening of the cabinet	0	cm ²
MIN Milling rabbet width	583	mm	MIN distance from cabinet to rear wall	0	mm
MAX Milling rabbet width	585	mm	Indicates whether a ventilation opening in the top front side of cabinet is needed or not. Default is "N"	No	
MIN Milling rabbet depth	513	mm	MIN Frontal gap of the cabinet	0	mm
MAX Milling rabbet depth	515	mm	MIN frontal opening area of the cabinet	0	cm ²
Milling rabbet thickness	6	mm	INSTALLATION SPACE		
Radius milling rabbet	11.5	mm	Depth of immersion underneath the appliance	0	mm
Flush installation KIT (2)	Service KIT		Width protruding area below bottom box	0	mm
Indicates the minum worktop thickness with standard installation for gas	0	mm	Depth protruding area below bottom box	0	mm
Indicates the maximum worktop thickness with standard installation for gas	0	mm	Protruding area: X positioning	0	mm
Indicates the minum worktop thickness with flush installation for gas	0	mm	Protruding area: Y positioning	0	mm
Indicates the maximum worktop thickness with flush installation for gas	0	mm	ACCESSORIES FOR INSTALLATION		
WITH OVEN			Gasket	Pre assembled	
Indicates whether the cooktop can be installed above oven. Default is "Y"	Yes		Clips	Separate	
MIN worktop thickness with oven	20	mm			
MAX worktop thickness with oven	50	mm			

DIMENSION**MEASURE**

	KIT	
Injector KIT	N/A	
Elbow KIT	N/A	
COOKTOP HOOD INSTALLATION ONLY FOR GAS		
MIN distance from cooktop to above furniture	0	mm
MIN distance between cabinets above the cooktop	0	mm
MAX distance between cabinets above the cooktop	0	mm