



# WIC 3C26 PF SA

# 12NC/Fx: 859991026840

# GTIN (EAN) code: 8003437205552

DIMENSION	MEASURE	
<b>OVERALL CABINET</b>		
01. Height MIN of the base cabinet Niche, including all required space for installation or ventilation (HMIN_B)	820	mm
02. Height MAX of the base cabinet Niche, including all required space for installation or ventilation (HMAN_B)	900	mm
03. Width MIN of the base cabinet Niche, including all required space for installation or ventilation (WMIN_B)	600	mm
04. Width MAX of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B)	608	mm
05. Depth of the base cabinet Niche, including all required space for installation or ventilation (DN_B)	560	mm
06. Indicates whether a ventilation opening is needed or not. Default is "N"	No	
07. appliance can be used as base for other appliances from the same manufacturer. Default is "N"	No	
<b>Built In - Floor Standing</b>		
08. Height MIN Decorative Front (HMIF)	653	mm
09. Height MAX Decorative Front (HMAF)	720	mm
10. Width MIN Decorative Front (WMIF)	596	mm
11. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)	10	kg
12. Weight MIN of the decorative front panel of the Kitchen manufacturer (WEMIF)	2	kg
13. Thickness MAX of decorative front panel of the kitchen manufacturers (TMAF)	50	mm
14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG)	3	mm
<b>APPLIANCE</b>		
<b>Overall Appliance</b>		
01. Height MIN Product (HMIP)	820	mm
02. Height MAX product (HMAP)	900	mm
03. Width product (WP)	598	mm
04. Depth product without front (DP)	555	mm
05. Depth product (D)	0	mm
06. Depth MIN of plinth return front (DMIPRF)	87	mm
07. Depth MAX of plinth return front (DMAPRF)	87	mm
08. Height MIN Plinth return. Dimension is taken by minimum appliance height (HMIMIPR)	93	mm
09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMAPR)	160	mm
10. Height MIN Plinth return. Dimension is taken by maximum appliance height (HMAMIPR)	173	mm
11. Height MAX Plinth return. Dimension is taken at maximum appliance height (HMAMAPR)	240	mm
<b>Built In - Floor Standing</b>		
12. Height MIN Product Panel. When product panel is missing, set to 0 (HMIPP)	0	mm
13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)	0	mm
14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)	590	mm
15. Type of preparation to fix the cover door	Drilling template standard	
<b>Retrace back socle</b>		
16. Depth of the socle retrace at the rear side (DBSR)	48	mm
17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)	120	mm
<b>TEMPLATE NAME</b>		
00. Name of the template to be used	DISH_FULLLDOOR60CM	