



DIMENSION	MEASURE		DIMENSION	MEASURE	
<b>WOODEN CABINET - Overall Wooden Cabinet - BI</b>			<b>APPLIANCE</b>		
01. Height MIN of the tall cabinet Niche, including all required space for installation or ventilation (HMIN_T)			<b>Overall Appliance</b>		
01. Height MIN of the tall cabinet Niche, including all required space for installation or ventilation (HMIN_T)	1776	mm	01. Height MIN Product, watch the detail drawing for the exact position of the dimension line (HMIP)	1770	mm
02. Height MAX of the tall cabinet Niche, including all required space for installation or ventilation (HMAN_T)	1786	mm	02. Height MAX product, watch the detail drawing for the exact position of the dimension line (HMAP)	1770	mm
03. Width MIN of the tall cabinet Niche, including all required space for installation or ventilation (WMIN_T)	560	mm	03. Width product, watch the detail drawing for the exact position of the dimension line (WP)	540	mm
04. Width MAX of the tall cabinet Niche, including all required space for installation or ventilation (WMAN_T)	570	mm	04. Depth product without front, watch the detail drawing for the exact position of the dimension line (DP)	0	mm
05. Depth of the tall cabinet Niche, including all required space for installation or ventilation (DN_T)	550	mm	05. Depth product, watch the detail drawing for the exact position of the dimension line (D)	545	mm
06. Height MIN of the base cabinet Niche, including all required space for installation or ventilation (HMIN_B)	0		06. Depth MIN plinth return front (DMIPRF)	0	mm
07. Height MAX of the base cabinet Niche, including all required space for installation or ventilation (HMAN_B)	0		07. Depth MAX plinth return front (DMAPRF)	41	mm
08. Width MIN of the base cabinet Niche, including all required space for installation or ventilation (WMIN_B)	0		08. Height MIN Plinth return. This dimension is taken by minimum appliance height (HMIPR)	56	mm
09. Width MAX of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B)	0		09. Height MAX Plinth return. This dimension is taken at minimum appliance height (HMAPR)	56	mm
10. Depth of the base cabinet Niche, including all required space for installation or ventilation (DN_B)	0		<b>Door or Drawer</b>		
11. Indicates whether a ventilation opening is needed or not. Default is "N"	Yes		10. Height front. When appliance has more than one front, only the most bottom left front is described here (HF)	618	mm
12. Appliance can be used as base for other appliances from the same manufacturer. Default is "N"	No		11. Width front. When appliance has more than one front, only the most bottom left front is described here (WF)	540	mm
<b>WOODEN CABINET - Door – Drawer</b>			12. Depth front (DF)	0	mm
13. Height MIN Decorative Front, if appliance has more than one front, only the most bottom left front is described here (HMIF)	1006	mm	13. Maximum depth all protruding elements, e.g. handles, controls (DC)	0	mm
14. Width MIN Decorative Front, if appliance has more than one front, only the most bottom left front is described here (WMIF)	560	mm	14. Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90° (CC)	0	mm
15. Weight/Thickness of the decorative bottom front panel of the Kitchen manufacturer needs (essential)	No		15. Projection of front in relation to housing of appliance (FPT)	18	mm
16. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)	0	kg	16. Projection of front in relation to bearing area of the appliance. Taken at MIN height of appliance if adjustable height(FPB)	0	mm
17. Thickness MIN Decorative Front, if appliance has more than one front only the most bottom left front is described here(TMIF)	0	mm	17. Height Product Panel. When product panel is missing, set to 0 (HMAPP)	27	mm
18. Thickness MAX Decorative Front, if appliance has more than one front only the most bottom left front is described here(TMAF)	0	mm	18. Lateral projection of front including controls when door is opened totally. At the side where the hinge is mounted (FPOD)	0	mm
<b>Additional Fronts (2 doors)</b>			19. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)	0	mm
19. Height MIN Decorative Front, when appliance has more than one front, upper front is described here (HMIFU)	0	mm	20. Lateral projection of opened front at the side where the hinge is fixed (FPD)	0	mm
20. Width MIN Decorative Front, when appliance has more than one front, upper front is described here (WMIFU)	0	mm	21. Door hinge positioning and tipology		Right-changeable
21. Weight/Thickness of the decorative upper front panel of the Kitchen manufacturer needs (essential)	No		22. Type of preparation to fix the cover door		Sliding system
22. Weight MAX of the decorative upper front panel of the Kitchen manufacturer (WEMAFU)	0	kg	23. Maximum angle when door is opened totally (AOD)	0	°
23. Thickness MIN Decorative Front, when appliance has more than one front, upper front is described here (TMIFU)	0	mm	24. Maximum thickness of the upper front panel (TUFP)	4	mm
24. Thickness MAX Decorative Front, when appliance has more than one front, upper front is	0	mm	<b>Additional Fronts (2 doors)</b>		
			25. Height front, when appliance has more than one front, upper front is described here (HUF)	1006	mm
			26. Width front, when appliance has more than one front, upper front is described here (WUF)	540	mm
			27. Useful space between the 2 doors, including hinges size (HMAFG)	60	mm
			28. Distance between the bottom of the product and the center line between the fridge doors (HFG)	704	mm

discribed here (TMAFU)		
<b>TALL WOODEN CABINET - Vent-shaft incoming</b>		
25. Indicates the position of the freespace for the incoming airflow, tall wooden cabinet	Front- Bottom	
26. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TI)	50	mm
27. Ventilation cavity minimum, tall wooden cabinet (VC_TI)	200	cm <sup>2</sup>
<b>TALL WOODEN CABINET - Vent-shaft outgoing</b>		
28. Indicates the position of the freespace for the outgoing airflow, tall wooden cabinet	-	
29. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TO)	50	mm
30. Ventilation cavity minimum, tall wooden cabinet (VC_TO)	200	cm <sup>2</sup>
<b>BASE WOODEN CABINET - Vent-shaft incoming</b>		
31. Indicates the position of the freespace for the incoming airflow, base wooden cabinet	-	
32. Clearance MIN Ventilation, base wooden cabinet (CMIV_BI)	0	mm
33. Ventilation cavity minimum, base wooden cabinet (VC_BI)	0	cm <sup>2</sup>
<b>BASE WOODEN CABINET - Vent-shaft outgoing</b>		
34. Indicates the position of the freespace for the outgoing airflow, base wooden cabinet	-	
35. Clearance MIN Ventilation, base wooden cabinet (CMIV_BO)	0	mm
36. Ventilation cavity minimum, base wooden cabinet (VC_BO)	0	cm <sup>2</sup>