



# KOFCS 60900

# 12NC/Fx: 851352501100

# GTIN (EAN) code: 8003437219412

DIMENSION	MEASURE	
<b>OVERALL CABINET</b>		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	595	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	480	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	480	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	480	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	857	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	857	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	860	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	860	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	560	mm
Space in front, which is required to install bottom trim	0	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes	
<b>WALL CABINET (vent-shaft incoming)</b>		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm <sup>2</sup>
<b>WALL CABINET (vent-shaft outgoing)</b>		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm <sup>2</sup>
<b>TALL CABINET (vent-shaft incoming)</b>		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear	
Minimum space for inbound ventilation (tall cabinet)	50	mm
Minimum area for inbound ventilation cavity (tall cabinet)	280	cm <sup>2</sup>
<b>TALL CABINET (vent-shaft outgoing)</b>		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Front	
Minimum space for outbound ventilation (tall cabinet)	5	mm
Minimum area for outbound ventilation cavity (tall cabinet)	45	cm <sup>2</sup>
<b>BASE CABINET (vent-shaft incoming)</b>		
Indicates the position of the freespace for the inbound airflow (base cabinet)	Rear	
Minimum space for inbound ventilation (base cabinet)	50	mm
Minimum area for inbound ventilation cavity (base cabinet)	280	cm <sup>2</sup>
<b>BASE CABINET (vent-shaft outgoing)</b>		
Indicates the position of the freespace for the outbound airflow (base cabinet)	Front	
Minimum space for outbound ventilation (base cabinet)	5	mm
Minimum area for outbound ventilation cavity (base cabinet)	45	cm <sup>2</sup>

DIMENSION	MEASURE	
<b>APPLIANCE</b>		
Height of the front	477	mm
Width of the front	894	mm
Depth of the front	24	mm
Maximum depth all protruding elements, e.g. handles, controls	50	mm
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	83	mm
Projection of front in relation to housing of appliance	5	mm
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	0	mm
When product panel is missing, set to 0	135	mm
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	1000	mm
Height from bearing area of appliances and lower handle	417	mm
Frontal handle thickness	29	mm
Frontal handle width	588	mm
MIN Height of the product body	472	mm
MAX Height of the product body	472	mm
Width of the product body	849	mm
Depth of the product body	538	mm
Full depth of product excluding protruding interface elements	558	mm
-	-	mm
-	-	mm
-	-	mm
-	-	mm
-	-	mm
-	-	mm
-	-	mm
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No	
<b>Appliance Flap door</b>		
Projection of the opened flap in relation to bearing area	0	mm
Maximum angle when flap door is opened totally	85	mm
<b>Appliance Side swing door</b>		
Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted	0	mm
Lateral projection of opened front at the side where the hinge is fixed	0	mm
Maximum angle when door is opened totally	0	mm
<b>Appliance other</b>		
Depth from front end of the niche to the front end of the freespace of the retrace	538	mm
Height from niche to bottom end of freespace for the retrace	581	mm