
W7 OM4 4S1 H


12NC: 859991538890

GTIN (EAN) code: 8003437834356









- 6TH Sense technology
- Up to 40 6th SENSE Cooking Combinations
- SmartClean
- Energy class A+
- Cavity 73 L
- Cook4
- Ready2Cook
- Defrost function
- Forced Air Fan Cooking
- Grill
- Easy Clean Enamel Interior
- Turbo grill function
- Maxi cooking
- · Pastry function
- Pizza/Bread function
- Warm Keeping
- Soft closing door

Whirlpool built in electric oven: inox color, self cleaning - W7 OM4 4S1 H

This Whirlpool built in Oven features: smart Clean technology, that provides a self cleaning cycle that ensures ideal cleaning results, at the touch of a button. Advanced electric technology allowing you to cook dishes saving energy. Halogen lamp allowing a more energy-efficient performance. Exclusive 6th SENSE technology, that allows you to pick among a variety of pre-programmed recipes, and your oven will automatically adjust cooking, temperature and time settings, to ensure perfect results. Oven door with soft-close design, for increased ease of use.



Multifunction 8

Multiple cooking methods. The Multifunction 8 feature offers flexible cooking options, to ensure perfect results, whatever the recipe.



6th Sense W6 W7

No more guesswork. Simply pick your recipes, and let 6th SENSE cook them to perfection, every time. Up to 40 cooking combinations organized to fit your lifestyle and diet, for a full assisted cooking experience.



Ready2cook

No pre-heating required. The Ready2Cook function uses a powerful convection system to quickly reach the right temperature, and completely eliminate the need for pre-heating.



Forced Air

Seal in the taste. Thanks to the Forced Air technology, preheated air is circulated inside your Oven using an innovative convection system, giving you moist, juicy cooking results.



Smart clean

Effortless, eco-friendly cleaning. The innovative SmartClean technology cleans your oven thoroughly and efficiently in just 30 minutes, without the use of detergents. Simply add 200cc of water to the oven cavity, run the SmartClean cycle, then wipe with a dry cloth.



Soft closing

Slow-motion closing. Thanks to slow-closing hinges, the oven door shuts effortlessly, with a soft and silent motion.



Starclean

Effortless cleaning, at the touch of a button. StarClean technology provides an eco-friendly cleaning cycle that ensures ideal cleaning results in just 35 minutes, leaving your oven's cavity spotlessly clean. No harsh detergents: StarClean only uses water, and reduces energy consumption by 97%, compared to a conventional pyrolytic oven.

W7 OM4 4S1 H

12NC: 859991538890

GTIN (EAN) code: 8003437834356



SENSING THE DIFFERENCE

Construction type Built-in Type of control Electronic Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	MAIN FEATL	IRES
Main colour of product Inox Construction type Built-in Type of control Electronic Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 595 Depth of the product 504 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Product group	Oven
Construction type Built-in Type of control Electronic Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Commercial code	W7 OM4 4S1 H
Type of controlElectronicType of control settings-Are any hobs controls integrated?NoWhich kind of hobs can be controlled?-Automatic programmesYesCurrent (A)16Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)90Plug typeNoDepth with open door 90 degree (mm)-Height of the product595Width of the product595Depth of the product564Minimum niche height0Niche depth0Niche depth0Niche depth0Net weight (kg)40.5Usable volume (of cavity)73Integrated Cleaning systemHydrolyticGrids of the cavity2	Main colour of product	Inox
Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Construction type	Built-in
Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Type of control	Electronic
Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Type of control settings	-
Automatic programmes Yes Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Are any hobs controls integrated?	No
Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Which kind of hobs can be controlled?	-
Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Automatic programmes	Yes
Frequency (Hz)50/60Length of Electrical Supply Cord (cm)90Plug typeNoDepth with open door 90 degree (mm)-Height of the product595Width of the product595Depth of the product564Minimum niche height0Minimum niche width0Niche depth0Net weight (kg)40.5Usable volume (of cavity)73Integrated Cleaning systemHydrolyticGrids of the cavity2	Current (A)	16
Length of Electrical Supply Cord (cm)90Plug typeNoDepth with open door 90 degree (mm)-Height of the product595Width of the product595Depth of the product564Minimum niche height0Minimum niche width0Niche depth0Net weight (kg)40.5Usable volume (of cavity)73Integrated Cleaning systemHydrolyticGrids of the cavity2	Voltage (V)	220-240
Plug typeNoDepth with open door 90 degree (mm)-Height of the product595Width of the product595Depth of the product564Minimum niche height0Minimum niche width0Niche depth0Net weight (kg)40.5Usable volume (of cavity)73Integrated Cleaning systemHydrolyticGrids of the cavity2	Frequency (Hz)	50/60
Depth with open door 90 degree (mm) Height of the product Width of the product Depth of the product Seps Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Grids of the cavity	Length of Electrical Supply Cord (cm)	90
Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Plug type	No
Width of the product595Depth of the product564Minimum niche height0Minimum niche width0Niche depth0Net weight (kg)40.5Usable volume (of cavity)73Integrated Cleaning systemHydrolyticGrids of the cavity2	Depth with open door 90 degree (mm)	-
Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Height of the product	595
Minimum niche height Minimum niche width O Niche depth Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Grids of the cavity 2	Width of the product	595
Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Depth of the product	564
Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Minimum niche height	0
Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Minimum niche width	0
Usable volume (of cavity) 73 Integrated Cleaning system Hydrolytic Grids of the cavity 2	Niche depth	0
Integrated Cleaning system Hydrolytic Grids of the cavity 2	Net weight (kg)	40.5
Grids of the cavity 2	Usable volume (of cavity)	73
·	Integrated Cleaning system	Hydrolytic
Trays 2	Grids of the cavity	2
	Trays	2

TECHNICAL FEATURES	
Timer	-
Time control	Electronic
Time-setting options	Start and Stop
Safety device	-
Interior light	Yes
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Rear
Oven guides of the cavity	Telescopic
Probe of the cavity	No

PERFORMANCES	
Energy input	Electric
Type of energy of the cavity	Electricity
Energy efficiency class - NEW (2010/30/EU)	A+
Energy consumption per cycle conventional - NEW (2010/30/EU)	0.91
Energy consumption per cycle forced air convection - NEW (2010/30/EU)	0.70

